

TREMPROOF® PUMA PLANTER SYSTEMS

Features & Benefits

- No root barrier required
- Extreme durability with exceptional crack-bridging characteristics, eliminating the need for reinforcing fabric
- 30 to 45 minute cure time between coats; ability to proceed to overburden 1 hour after application
- Can be applied at temperatures as low as to 14 °F (-10 °C)
- Zero Volatile Organic Compounds (VOCs)
- Compatible with approved Tremco sealants and coatings
- Premium waterproofing system backed by an all-inclusive warranty




TREMPROOF® PUMA Planter Complete Project



TREMproof PUMA Planter System

PRODUCT	COVERAGE RATE	WET MILS	COMMENTS
1: Dymonic® 100	N/A	N/A	1" cant bead at all horizontal to vertical transitions
2: Tremco PUMA Primer	90 ft ² /gal	17	Lightly broadcast silica sand.
3: Tremco PUMA BC R	25 ft ² /gal	65	Allow 45 min to cure before proceeding.
4: Tremco PUMA BC/BC LM	20 ft ² /gal	80	Allow 45 min to cure before proceeding.
5: Tremco PUMA TC	105 ft ² /gal	15	Allow 60 min to cure.



For specific information, please reference the application instructions or contact your local Tremco representative.

Tremco Commercial Sealants & Waterproofing | 3735 Green Road | Beachwood, OH 44122 | US: 800.852.9068 | CAN: 800.363.3213 | tremcosealants.com

Tremco Construction Products Group (CPG) brings together Tremco Incorporated's Commercial Sealants & Waterproofing and Roofing & Building Maintenance operating divisions; Dryvit Systems, Inc.; Nudura Inc.; Willseal; Weatherproofing Technologies, Inc. and Weatherproofing Technologies Canada, Inc.



Tremco®, TREMproof® and Dymonic® are registered trademarks of Tremco Incorporated. Use of the ® symbol indicates registration with the US Patent & Trademark Office and the Canadian Intellectual Property Office.

1220/TPPPSS

tremcocpg.com