



TECHNICAL DATA SHEET

TREMproof® TRA SHEETING

Reinforced Flashing Membrane
Embedded in TREMproof 250GC

PRODUCT DESCRIPTION

TREMproof® TRA Sheeting is a protective waterproofing course that is compounded from a blend of EPDM and SBR thermostat elastomers. This sheet is reinforced with a high-strength, polyester-woven scrim.

BASIC USES

TREMproof TRA Elastomeric Sheeting is designed to provide a durable, flexible, tear-resistant bridge in areas of high movement where cold- and hot-applied membranes are being utilized. TRA Elastomeric Sheeting can also be used as a secondary layer of waterproofing for the TREMproof 250GC Cold-Applied, Heavy-Duty Waterproofing System.

FEATURES & BENEFITS

- EPDM/SBR blend provides flexibility for ease of installation.
- Woven polyester scrim for added durability and puncture resistance.
- TRA Sheeting has the versatility to be utilized in TREMproof 250GC applications.
- TRA Sheeting provides an additional waterproofing layer for ultimate protection.
- Superior tensile and tear strength for high stress, heavy-duty applications.

AVAILABILITY

Immediately available from your local Tremco Sales Representative or Tremco Distributor. For distributor locations, visit www.tremcosealants.com.

PACKAGING

12' (305 mm), 20" (508 mm), 24" (610 mm), and 36" (914 mm) x 50' (15.24 M) rolls
60" (1,524 mm) x 100' (30.48 M) rolls

STORAGE

TREMproof TRA Sheeting should be stored out of direct sunlight. Vertical storage is recommended.

LIMITATIONS

- Not for use beneath sand-set vehicular pavers.

WARRANTY

A repair or replacement warranty is available on all Tremco products. Visit <https://www.tremcosealants.com/warranties/> for details.

TYPICAL PHYSICAL PROPERTIES

PROPERTY	TEST METHOD	TYPICAL VALUES
Color		Black
Thickness	ASTM D751-89	0.045" (1.1 mm)
Weight	ASTM D751-89	41.6 oz/yd ² (1,422 g/M ²)
Breaking Strength	ASTM D751-89	261 lbf (1,443 N) MD 150 lbf (1,288 N) XMD
Tear Strength	ASTM D751-89	94 lbf (313 N) MD 59 lbf (348 N) XMD
Low Temperature Flexibility (-40 °F)	ASTM D2136-84	Pass

Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

TRADS/0823

Tremco Construction Products Group (CPG) brings together Tremco CPG Inc. and its Dryvit and Nudura brands; Willseal; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc. and its Pure Air Control Services and Canam Building Envelope Specialists offerings; and Weatherproofing Technologies Canada, Inc.



tremcosealants.com | 800.321.7906



Construction Products Group

3735 Green Rd. | Beachwood, OH 44122
800.321.7906 | tremcocpg.com