

Product Description

TREMstop® SuperStrip is made of a flexible graphite-based intumescent compound with polyethylene backer. It is designed to expand when exposed to a fire to fill any voids left as the combustible materials burn away.

Basic Uses

TREMstop SuperStrip is used with plastic pipe in concrete assemblies and wood floor/ceiling assemblies. It can also be used with fluted metal decks.

Features and Benefits

- TREMstop SuperStrip is flexible enough to easily wrap around the pipe.
- TREMstop SuperStrip is packaged in rolls and pre-cut strips to reduce waste and accommodate a variety of pipe diameters and types.

Availability

Immediately available from your local Tremco Field Representative, Tremco Distributor or Tremco Warehouse.

Applicable Standards

- ASTM E814
- CAN4-S115M

Limitations

- Not recommended for use with passive fire containment systems not listed or approved by Tremco.

Warranty

Tremco warrants its Products to be free of defects in materials, but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, Tremco makes no other warranty, expressed or implied including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE, with respect to Tremco Products. Tremco's sole obligation shall be, at its option, to replace, or refund the purchase price of the quantity of Tremco Products proven to be defective and Tremco shall not be liable for any loss or damage.


Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements

TYPICAL PHYSICAL PROPERTIES

PROPERTY	PRE-CUT STRIPS			ROLLS		
	SS-T2	SS-T3	SS-T4	SS-R2	SS-R3	SS-R4
Color	Dark Gray	Dark Gray	Dark Gray	Dark Gray	Dark Gray	Dark Gray
Width (in.)	1.5	1.5	1.5	1.5	1.5	1.5
Thickness (in.)	.125	.25	.375	.125	.25	.375
Nominal Pipe Size	2	3	4	2	3	4
Case Quantity	10	10	10	9	4	1
Length	8"	11.34"	15"	144"	144"	144"

0716/TSSPSDS-ST



Tremco Commercial Sealants & Waterproofing

3735 Green Rd
Beachwood OH 44122
216.292.5000 / 800.321.7906

1451 Jacobson Ave
Ashland OH 44805
419.289.2050 / 800.321.6357

220 Wicksteed Ave
Toronto ON M4H1G7
416.421.3300 / 800.363.3213

1445 Rue de Coulomb
Boucherville QC J4B 7L8
514.521.9555