



TECHNICAL DATA SHEET

TREMPro®RV ROOF SEALANT

100% Solids, Self-Leveling Sealant

PRODUCT DESCRIPTION

TremPRO® RV Roof Sealant is a high performance, low modulus, one component, self-leveling sealant designed for RV roof penetrations as a primary seal. The sealant cures to a flexible rubber when exposed to atmospheric moisture.

BASIC USES

TremPRO® RV Roof Sealant is specially designed for sealing level or slightly sloped joints, seams and penetrations in recreational vehicle and trailer roofs.

FEATURES AND BENEFITS

- TremPRO® RV Roof Sealant cures to withstand movement, shear, deflection and moisture in lap and butt joint applications.
- TremPRO® RV Roof Sealant exhibits excellent adhesion to steel, painted metal, wood, vinyl, concrete and composite surfaces.
- The product can be painted shortly after it has developed a robust skin.

AVAILABILITY

Immediately available from your local Tremco Field Representative, Tremco Distributor or Tremco Warehouse.

PACKAGING

11 oz. (300ml)

COLORS

White.

LIMITATIONS

- Do not apply over damp or contaminated surfaces.

SUBSTRATE PREPARATION

For best adhesion, the surface must be sound, clean and dry. Depending on the substrate, the surface may require mechanical cleaning such as a thorough wire brushing with steel wool or Scotch Brite pad and/ or solvent wipe. Old sealant must also be removed prior to application.

APPLICATION

TremPRO® RV Roof Sealant is easy to apply with conventional caulking equipment. Fill seam completely and tool. Ensure 1" overlap. At 75 °F (23.9 °C), 50% RH, a durable skin forms within hours after application.

Damaged Sealant can be repaired. Consult Tremco Technical Service or your Tremco sales representative for repair procedures.

CLEAN UP

Tooling is recommended immediately after application to ensure firm, intimate contact with the joint interface. Dry tooling is preferred. Excess sealant and smears adjacent to the joint can be removed with Xylol or Toluol before sealant cures.

WARRANTY

A repair or replacement warranty is available on all Tremco products. Visit <https://www.tremcosealants.com/warranties/> for details.

TYPICAL PHYSICAL PROPERTIES

PROPERTY	TEST METHOD	TYPICAL VALUES
Effects of Accelerated Weathering		Passes
Extrusion Rate		10 to 15 sec
Rheological Properties		Levels Moderately; Holds up to 5 to 6% slope
Skin Formation		45 to 60 min (typical)
Tack Free Time		1 to 2 hr
Adhesion to EPDM	180° Peel Adhesion Test	7.64 dry lbf
Adhesion to Galvanized Metal	180° Peel Adhesion Test	10.58 dry lbf
Adhesion to PVC	180° Peel Adhesion Test	10.13 dry lbf
Adhesion to TPO	180° Peel Adhesion Test	.61 dry lbf
Adhesion to TremPRO RV Premium Roof Coating	180° Peel Adhesion Test	4.92 dry lbf
Adhesion to Vinyl	180° Peel Adhesion Test	6.97 dry lbf

Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

TPRVRS-DS/1222

Tremco Construction Products Group (CPG) brings together the Commercial Sealants & Waterproofing and Roofing & Building Maintenance divisions of Tremco CPG Inc.; Dryvit and Willseal brands; Nudura Inc.; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc.; Weatherproofing Technologies Canada, Inc.; and Pure Air Control Services, Inc.



tremcosealants.com | 800.321.7906



Construction Products Group

3735 Green Rd. | Beachwood, OH 44122
800.321.7906 | tremcocpg.com