

---

## PRODUCT DESCRIPTION

Tremco® 2450 Protection Board is an extruded, hollow-core polypropylene/polyethylene copolymer. The board is grey in color with a standard thickness of 0.08" (2.2 mm).

---

## BASIC USES

Tremco 2450 provides protection for most commonly used waterproofing membranes, both during and after construction. Typical applications include plaza decks, roof terraces, landscaped decks, planters, and foundation walls.

---

## FEATURES & BENEFITS

- Provides protection from normal construction traffic for most waterproofing membranes. Its light weight provides economic advantages in both application and on-site handling.
- Easily cut or folded to conform to difficult site conditions. Positive adhesion to membranes makes it ideal for vertical applications such as planters and foundation walls.
- Tremco 2450 remains inert in landscaped areas and will not absorb moisture, thus providing long-term protection to the waterproofing membrane.

---

## PACKAGING

Sheets are 0.08" (2.2 mm) thick, 4' x 3' (1.2 M 0.9 M)  
Fifty sheets = 600 ft<sup>2</sup> (55.7 M<sup>2</sup>) per bundle

---

## LIMITATIONS

- Not intended for use directly under asphalt paving.
- Not recommended for permanent UV exposure.

---

## WARRANTY

A repair or replacement warranty is available on all Tremco products. Visit <https://www.tremcosealants.com/warranties/> for details.

Please refer to our website at [www.tremcosealants.com](http://www.tremcosealants.com) for the most up-to-date Product Data Sheets.

**NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.**

T2450DS/1122

Tremco Construction Products Group (CPG) brings together Tremco CPG Inc. and its Dryvit and Nudura brands; Willseal; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc. and its Pure Air Control Services and Canam Building Envelope Specialists offerings; and Weatherproofing Technologies Canada, Inc.