

Tremco Commercial Sealants & Waterproofing 3735 Green Road Beachwood, OH 44122 US: 800.852.9068

Canada: 800.363.3213 www.tremcosealants.com



September 30, 2020

To Whom It May Concern:

RE: Tremco 830—Green Building Product Information (LEED v4.1 Information)

Tremco Incorporated is an organization that is committed to quality, our employees, and our environment. We are responsive to both internal and external customers, and we pledge to treat everyone with good stewardship and respect.

Tremco Incorporated certifies the following for Tremco 830:

Building Product Disclosure and Optimization:

Tremco 830 is manufactured in Toronto, Ontario, Canada.

No single extracted material is used to produce the majority of this product.

Recycled content for Tremco 830 is not available, and for the purposes of LEED reporting should be assumed to be zero.

Low Emitting Materials - VOC Content Information:

Tremco 830 is a specialty sealant with a VOC content of 330g/L equaling 35% as applied/mixed. As such, this product exceeds the VOC level limits set by SCAQMD rule 1168, except for Clear, which is exempt from regulation.

Note: VOC content values are as reported for the highest VOC content color for all Tremco 830 colors. Other colors may have a lower VOC content reported on their SDS.

Green Chemistry:

Tremco Incorporated is dedicated to the environment and prides itself on making its products as sustainable as possible. We are pleased to report that this product, depending on the color, is produced without any Red List chemicals. As such, it can be used to assist in finishing projects aimed towards achieving a Living Building Challenge certification. Please reach out to Tremco for assistance on which colors can be used for the credit.



Tremco Commercial Sealants & Waterproofing 3735 Green Road Beachwood, OH 44122 US: 800.852.9068 Canada: 800.363.3213

www.tremcosealants.com

Manufacture Inventory (reported to 1000ppm):

| Chemical Name or Role | CAS Number | Amount | GHS Hazard |
|--------------------------|------------|--------|---------------|
| Xylene | 1330-20-7 | | |
| Hydrocarbon Resin | | 0-40% | Non-Hazardous |
| SEBS Polymer | | <15% | Non-Hazardous |
| Filler | | <15% | Non-Hazardous |
| Polybutene | | <15% | Non-Hazardous |
| Ethylbenzene | 100-41-4 | | |
| SEPS Polymer | | <15% | Non-Hazardous |
| Titanium dioxide | 13463-67-7 | | |
| Adhesion Promoter | | <1% | Non-Hazardous |
| Toluene | 108-88-3 | | |
| UV Stabilizer | | <1% | Non-Hazardous |
| Butylated hydroxytoluene | 128-37-0 | | |
| Carbon Black | 1333-86-4 | | |
| Pigment | | <15% | Non-Hazardous |
| Colorant | | <1% | Non-Hazardous |
| Iron oxide | 1309-37-1 | | |
| Phthalocyanine green | 1328-53-6 | | |
| Plasticizer | | <1% | Non-Hazardous |
| Aluminum oxide | 1344-28-1 | | |

Additional Information:

Should you have any questions or require additional information, please do not hesitate to contact Technical Services or your local Tremco Field Representative.

Sincerely,

Joe Kravetz

Product Steward

Compliance and Regulatory Affairs