



# LEED™ 4.1 GREEN BUILDING PRODUCT INFORMATION GUIDE

## COATINGS, SEALANTS & ADHESIVES

William J. Clinton Presidential Library and Museum  
Little Rock, AR | Tremco Vegetative Roofing System

 **TREMCO**  
Construction Products Group







Tremco CPG supports sustainable design and green building for energy efficient building. As part of Tremco CPG's vision, we manufacture several sustainable building design solutions to achieve social and environmental objectives while providing economic balance.

The Leadership in Energy and Environmental Design (LEED) program was originally developed by the United States Green Building Council (USGBC), Department of Energy and Environmental Protection Agency (EPA) in 1997 and formalized thereafter by USGBC as a guide for sustainable building design.



LEED stands as the planet's most prevalent green building assessment system. LEED certification establishes a structure for creating environmentally-friendly, cost-effective, and health-conscious green structures. These buildings not only deliver advantages in terms of the environment, society, and governance but also represent a globally acknowledged symbol of accomplishment in sustainability.



- 🍃 **LEED Credits:** Tremco CPG actively contributes to sustainability by providing products and information that can offer LEED category credits. Visit the US Green Building Council LEED rating system at <https://www.usgbc.org/leed>
- 🍃 **Building Product Disclosure and Optimization:** No single extracted material is used to produce the majority of Tremco CPG Sealant products.
- 🍃 **Recycled Content** for Tremco CPG Sealant and Coating products is not available, and for the purposes of LEED reporting, should be assumed to be zero unless otherwise noted.
- 🍃 **Greenguard Gold Certification:** UL Greenguard Gold Certified products comply with the requirements of the California Department of Public Health (CDPH) Standard Method v1.2-2017.
- 🍃 **Living Building Challenge:** Many Tremco products free of Red List Chemicals can be used in projects while helping achieve a Living Building Challenge Certification.

# COATINGS

Product	Product Category	Description	Location of Manufacture	Sealant VOC (grams/L)	Sealant VOC % by Weight	Single Extracted Material	Manufacturing Inventory Available	Lower than SCAQMD rule 1113	Living Building Challenge	Additional Info
Corner Guard	Waterproofing	Exterior applied drainage product	Fitzgerald, Georgia	<1 g/L	<1%	no	not available	yes	Red List Free	
Drainstar 5X	Waterproofing	Multi-Composite Drainage and Protection Board	Toronto, Ontario, Canada	N/A	N/A	no	not available	yes		
Enviro-Dri	Air, Vapor, & Weather Resistant	Permeable membrane	Medina, Ohio	66 g/L	<5%	no	not available	yes	Red List Free	
Extrusions	Gaskets, Tapes & Extrusions	Glazing article	Ashland, Ohio	<1 g/L	<1%	no	not available	yes		 
Gaskets	Gaskets, Tapes & Extrusions	Glazing article	Ashland, Ohio	<1 g/L	<1%	no	not available	yes		 
ExoAir 110 and TWF	Air, Vapor, & Weather Resistant	Self-Adhered Air and Vapor Barrier Membrane (*Air barrier)	Brentwood, New Hampshire	<1 g/L	<1%	no	not available	yes	Red List Free	
ExoAir 110AT	Air, Vapor, & Weather Resistant	Self-Adhered Air and Vapor Barrier Membrane (*Air barrier)	Newburyport, Massachusetts	<1 g/L	<1%	no	yes	yes		
ExoAir 120	Air, Vapor, & Weather Resistant	Fluid-Applied, Asphaltic Air & Vapor Barrier Membrane (*Air barrier)	Medina, Ohio	72 g/L	5%	no	yes	no	Red List Free	
ExoAir 130	Air, Vapor, & Weather Resistant	Fluid-Applied, Synthetic Air and Vapor Retarder Membrane (*Air Barrier)	Toronto, Ontario, Canada	<1 g/L	<1%	no	yes	yes		
ExoAir 2000	Air, Vapor, & Weather Resistant	Flexible, polymer- based, non-cementitious, air/water-resistive barrier membrane	North Kingstown, Rhode Island	<42 g/L	<3%	no	no	yes		
ExoAir 210AT	Air, Vapor, & Weather Resistant	Self-adhered permeable air barrier membrane (*Air Barrier)	Sparta, MI	<1g/L	<1%	no	yes	yes	Red List Free	
ExoAir 220	Air, Vapor, & Weather Resistant	Fluid-Applied, Asphaltic Air & Vapor Permeable Membrane (*Air Barrier)	Medina, Ohio	2g/L	<1%	no	yes	yes	Red List Free	
ExoAir 230	Air, Vapor, & Weather Resistant	Fluid-Applied, Synthetic Air & Vapor Permeable Membrane (*Air Barrier)	Toronto, Ontario, Canada	35 g/L	1%	no	yes	yes	Red List Free	
ExoAir 230LT	Air, Vapor, & Weather Resistant	Fluid-Applied, Synthetic Air & Vapor Permeable Membrane (*Air Barrier)	Toronto, Ontario, Canada	146 g/L	8.35%	no	yes	no		

Product	Product Category	Description	Location of Manufacture	Sealant VOC (grams/L)	Sealant VOC % by Weight	Single Extracted Material	Manufacturing Inventory Available	Lower than SCAQMD rule 1113	Greenguard Certified	Living Building Challenge	Additional Info
<b>ExoAir 430 (Securock)</b>	Air, Vapor, & Weather Resistant	Pre-applied fluid synthetic air & vapor permeable membrane (Exterior use)	Jacksonville, FL	7 g/L	<1%	no	not available	yes			USG LEED information: <a href="https://www.tremcosealants.com/fileshare/LEEDLetters/Securock_ExoAir_430_LEED.pdf">https://www.tremcosealants.com/fileshare/LEEDLetters/Securock_ExoAir_430_LEED.pdf</a>
<b>ExoAir Dual-flash SSG, R</b>	Air, Vapor, & Weather Resistant	Liquid applied flashing membrane	Toronto, Ontario, Canada	1 g/L	<1 %	no	not available	yes			
<b>ExoAir Primer</b>	Air, Vapor, & Weather Resistant	A VOC-Compliant Adhesive Primer	Rockland, Massachusetts	236.1 g/L	13%	no	not available	no		Red List Free	
<b>Paramastic</b>	Waterproofing	Expandable mastic for use with Paraseal waterproofing membrane.	Spearfish, South Dakota	48 g/L	4%	Bentonite is used to produce approximately 56% (by weight) of this product.	yes	yes		Red List Free	
<b>Paraseal</b>	Waterproofing	Exterior applied waterproofer	Spearfish, South Dakota	<1 g/L	<1%	Bentonite is used to produce approximately 89% (by weight) of this product.	yes	yes		Red List Free	
<b>Paraseal GM</b>	Waterproofing	Exterior applied waterproofer	Spearfish, South Dakota	<1 g/L	<1%	Bentonite is used to produce approximately 89% (by weight) of this product.	yes	yes		Red List Free	
<b>Paraseal GM/LG</b>	Waterproofing	Exterior applied waterproofer	Spearfish, South Dakota	<1 g/L	<1%	Bentonite is used to produce approximately 89% (by weight) of this product.	yes	yes		Red List Free	
<b>Paraseal LG</b>	Waterproofing	Exterior applied waterproofer	Spearfish, South Dakota	<1 g/L	<1%	Bentonite is used to produce approximately 89% (by weight) of this product.	yes	yes		Red List Free	
<b>Paraseal Paraboot</b>	Waterproofing	Exterior applied waterproofer	Spearfish, South Dakota	<1 g/L	<1%	no	not available	yes			

Product	Product Category	Description	Location of Manufacture	Sealant VOC (grams/L)	Sealant VOC % by Weight	Single Extracted Material	Manufacturing Inventory Available	Lower than SCAQMD rule 1113	Greenguard Certified	Living Building Challenge	Additional Info
<b>Paraseal Paraprimer</b>	Waterproofing	Adhesive primer formulated to prepare construction surfaces	Rockland, Massachusetts	236 g/L	13%	no	not available	yes		Red List Free	This product is defined as an Adhesive Primer under rule 1168. VOC levels are lower than the limits set in rule 1168.
<b>Paraseal Paragranular</b>	Waterproofing	Exterior applied waterproofer	Spearfish, South Dakota	<1 g/L	<1%	Bentonite is used to produce approximately 100% (by weight) of this product.	yes	yes		Red List Free	
<b>Paraseal Para JT (Joint Tape)</b>	Waterproofing	Exterior applied waterproofer (Article)	Los Angeles, California	<1 g/L	<1%	no	not available	yes			
<b>Paraseal Paramastic</b>	Waterproofing	Expandable mastic for use with Paraseal waterproofing membrane	Spearfish, South Dakota	48 g/L	4%	Bentonite is used to produce approximately 56% (by weight) of this product.	yes	yes		Red List Free	
<b>Paraseal Parastick 'n' Dry</b>	Waterproofing	Exterior applied waterproofer (Article)	Spearfish, South Dakota	<1 g/L	<1%	Bentonite is used to produce approximately 89% (by weight) of this product.	not available	yes		Red List Free	
<b>Paraseal Paraterm Bar</b>	Waterproofing	Exterior applied waterproofer	Spearfish, South Dakota	<1 g/L	<1%	no	not available	yes			Recycled content for this product is 60% (36% Post-Industrial and 24% Post Consumer). Because this product is partially created with recycled content, consumers are able to work towards one Building Product Disclosure and Optimization - Raw Materials Extraction point.
<b>Paraseal Permanent Seam Tape</b>	Waterproofing	Exterior applied waterproofer (Article)	Hickory, North Carolina	<1 g/L	<1%	no	not available	yes			
<b>Permaquik Crystalline Waterproofing</b>	Waterproofing	Exterior applied waterproofer	Cleveland, Ohio	<1 g/L	<1%	no	not available	yes		Red List Free	
<b>Polyschim II Tape</b>	Gaskets, Tapes & Extrusions	High-performance glazing butyl tape	Toronto, Ontario, Canada	<1 g/L	<1%	no	not available	yes	 	Red List Free	
<b>Powerply Standard Smooth</b>	Waterproofing	Exterior applied bitumen sheet	Cleveland, Ohio	<1 g/L	<1%	no	not available	yes			
<b>Powerply Standard White Granular</b>	Waterproofing	Exterior applied bitumen sheet	Cleveland, Ohio	<1 g/L	<1%	no	not available	yes		Red List Free	

Product	Product Category	Description	Location of Manufacture	Sealant VOC (grams/L)	Sealant VOC % by Weight	Single Extracted Material	Manufacturing Inventory Available	Lower than SCAQMD rule 1113	Greenguard Certified	Living Building Challenge	Additional Info
<b>Permaquik 200 Crystalline Waterproofing</b>	Waterproofing	Capillary waterproofing formulation of proprietary blends of chemicals, quartz sand and cement	Cleveland, Ohio	<1 g/L	<1%	no	yes	yes		Red List Free	
<b>SuperStop</b>	Waterproofing	Bentonite waterproofer (Article)	Spearfish, South Dakota	<1 g/L	<1%	Bentonite is used to produce approximately 98% (by weight) of this product.	yes	yes	 	Red List Free	
<b>Tremco 2011</b>	Waterproofing	Exterior applied waterproofer (Article)	Dover, Ohio	<1 g/L	<1%	no	not available	yes			
<b>Tremco 2178</b>	Waterproofing	Exterior applied waterproofer (Article)	Concord, Ontario, Canada	<1 g/L	<1%	no	not available	yes			
<b>Tremco 2190</b>	Waterproofing	Exterior applied waterproofer (Article)	Drummonville, Quebec, Canada	<1 g/L	<1%	no	not available	yes			
<b>Tremco 2550/2560</b>	Waterproofing	Exterior applied waterproofer (Article)	Milton, Ontario, Canada	<1 g/L	<1%	no	not available	yes			
<b>Tremco Dualflex</b>	Waterproofing	Exterior applied waterproofer (Article)	Rochester, New Hampshire	<1 g/L	<1%	no	not available	yes		Red List Free	
<b>Tremco Epoxy Primer</b>	Waterproofing	Two-component (1:1) primer recommended for use as a porous primer	Cleveland, Ohio	<1 g/L	<1%	no	not available	yes			
<b>Tremco Protection Mat</b>	Waterproofing	Exterior applied waterproofer	Dalton, Georgia	<1 g/L	<1%	no	not available	yes			
<b>Tremco PUMA BC (all grades)</b>	Traffic Coating, Waterproofing	Polyurethane-methacrylate (PUMA) base coat	Twisttringen, Germany	<1 g/L	<1%	no	yes	yes			
<b>Tremco PUMA Cleaner</b>	Traffic Coating, Waterproofing	One-part MMA cleaner for all tools such as mixing paddles, squeegees, spiked rollers and spatulas.	Twisttringen, Germany	0 g/L	0%	no	yes	yes			
<b>Tremco PUMA Flashing</b>	Traffic Coating, Waterproofing	Modified polyurethane-methacrylate (PUMA) base coat.	Twisttringen, Germany	0 g/L	0%	no	not available	yes			
<b>Tremco PUMA Initiator+</b>	Traffic Coating, Waterproofing	Benzoyl peroxide-based filler	Los Reyes, La Paz, Mexico	0 g/L	0%	no	yes	yes			
<b>Tremco PUMA TC</b>	Traffic Coating, Waterproofing	Methyl-methacrylate (MMA) top coat.	Twisttringen, Germany	<1 g/L	<1%	no	yes	yes			
<b>Tremco PUMA WC</b>	Traffic Coating, Waterproofing	Polyurethane-methacrylate (PUMA) wear coat	Twisttringen, Germany	<1 g/L	<1%	no	yes	yes			
<b>Tremco PUMA Filler Powder</b>	Traffic Coating, Waterproofing	Non-reactive, white, filler powder	Twisttringen, Germany	<1 g/L	<1%	no	not available	yes			

Product	Product Category	Description	Location of Manufacture	Sealant VOC (grams/L)	Sealant VOC % by Weight	Single Extracted Material	Manufacturing Inventory Available	Lower than SCAQMD rule 1113	Greenguard Certified	Living Building Challenge	Additional Info
<b>Tremco PUMA Primer</b>	Traffic Coating, Waterproofing	Methyl-methacrylate (MMA), two-component primer for porous and non-porous substrates	Twistringen, Germany	0 g/L	0%	no	yes	yes			
<b>Tremco Retention Squares</b>	Waterproofing	Exterior applied waterproofer	Stuttgart, Germany	<1 g/L	<1%	no	not available	yes			
<b>Tremco Rubber Aggregate</b>	Traffic Coating	Exterior applied waterproofing product	Wapakoneta, Ohio	<1 g/L	<1%	no	not available	yes			
<b>**TREMDrain</b>	Waterproofing	Exterior applied drainage product (Article)	Monroe, North Carolina & Carson City, Nevada	<1 g/L	<1%	no	not available	yes		Red List Free	Recycled content is 70% (Post-Industrial). Because this product is partially created with recycled content, consumers are able to work towards one Building Product Disclosure and Optimization Raw Materials Extraction point.
<b>**TREMDrain 1000</b>	Waterproofing	Exterior applied drainage product	Monroe, North Carolina & Carson City, Nevada	<1 g/L	<1%	no	yes	yes		Red List Free	Recycled content is 70% (Post-Industrial). Because this product is partially created with recycled content, consumers are able to work towards one Building Product Disclosure and Optimization Raw Materials Extraction point.
<b>**TREMDrain 2000 NW</b>	Waterproofing	Exterior applied drainage product	Monroe, North Carolina & Carson City, Nevada	<1 g/L	<1%	no	not available	yes		Red List Free	Recycled content is 60% (Post-Industrial). Because this product is partially created with recycled content, consumers are able to work towards one Building Product Disclosure and Optimization Raw Materials Extraction point.
<b>**TREMDrain 3000 NW</b>	Waterproofing	Exterior applied drainage product	Monroe, North Carolina & Carson City, Nevada	<1 g/L	<1%	no	not available	yes		Red List Free	Recycled content is 74% (Post-Industrial). Because this product is partially created with recycled content, consumers are able to work towards one Building Product Disclosure and Optimization Raw Materials Extraction point.
<b>**TREMDrain 6000</b>	Waterproofing	Exterior applied drainage product	Monroe, North Carolina & Carson City, Nevada	<1 g/L	<1%	no	not available	yes		Red List Free	Recycled content is 25.5% (Post-Industrial). Because this product is partially created with recycled content, consumers are able to work towards one Building Product Disclosure and Optimization Raw Materials Extraction point.
<b>**TremDrain 6000X</b>	Waterproofing	Exterior applied drainage product (Article)	Toronto, Ontario, Canada	<1 g/L	<1%	no	not available	yes		Red List Free	
<b>**TREMDrain 6600</b>	Waterproofing	Exterior applied drainage product	Monroe, North Carolina & Carson City, Nevada	<1 g/L	<1%	no	not available	yes		Red List Free	Recycled content is 70% (Post-Industrial). Because this product is partially created with recycled content, consumers are able to work towards one Building Product Disclosure and Optimization Raw Materials Extraction point.
<b>**TREMDrain Corner Guard</b>	Waterproofing	Exterior applied drainage product	Fitzgerald, Georgia	<1 g/L	<1%	no	not available	yes		Red List Free	
<b>**TREMDrain DPI</b>	Waterproofing	Exterior applied drainage product	Toledo, Ohio	<1 g/L	<1%	no	not available	yes			Recycled content is 35% (Post-Industrial). Because this product is partially created with recycled content, consumers are able to work towards one Building Product Disclosure and Optimization Raw Materials Extraction point.

Product	Product Category	Description	Location of Manufacture	Sealant VOC (grams/L)	Sealant VOC % by Weight	Single Extracted Material	Manufacturing Inventory Available	Lower than SCAQMD rule 1113	Greenguard Certified	Living Building Challenge	Additional Info
<b>**TREMDrain QSP</b>	Waterproofing	Exterior applied drainage product	Monroe, North Carolina & Carson City, Nevada	<1 g/L	<1%	no	not available	yes		Red List Free	Recycled content is 70% (Post-Industrial). Because this product is partially created with recycled content, consumers are able to work towards one Building Product Disclosure and Optimization Raw Materials Extraction point.
<b>**TREMDrain S</b>	Waterproofing	Exterior applied drainage product	Monroe, North Carolina & Carson City, Nevada	<1 g/L	<1%	no	not available	yes		Red List Free	Recycled content is 70% (Post-Industrial). Because this product is partially created with recycled content, consumers are able to work towards one Building Product Disclosure and Optimization Raw Materials Extraction point.
<b>Tremprime HR Primer</b>	Waterproofing	Hot-applied rubberized asphalt Primer	Delta, British Columbia, Canada	145 g/L	10%	no	yes	yes		Red List Free	This product is typically used as an exterior applied product, as such, it does apply to the Low Emitting Materials credit in LEED v4.1.
<b>TREMprime LV</b>	Waterproofing	Non-porous one-part primer	Chicago, Illinois	0 g/L	0%	no	not available	yes		Red List Free	
<b>TREMprime Multisurface Urethane Primer</b>	Waterproofing	Two-component, quick drying, epoxy-based, VOC-compliant primer	Cleveland, Ohio	0 g/L	0%	no	yes	yes		Red List Free	
<b>TREMprime Non-porous Primer</b>	Waterproofing	Water-based, quick-drying, one-part primer	Erie, Pennsylvania	7 g/L	0%	no	yes	yes		Red List Free	This product is typically used as an exterior applied product, as such, it does apply to the Low Emitting Materials credit in LEED v4.1.
<b>TREMprime QD Low-Odor Primer</b>	Waterproofing	Quick drying, high-solids, solvent-based modified bituminous roofing primer	Toronto, Ontario, Canada	410 g/L	46%	no	not available	no		Red List Free	
<b>TREMprime Silicone Metal Primer</b>	Waterproofing	One-component silicone sealant primer					not available			Red List Free	
<b>TREMprime VB</b>	Waterproofing	Two-component, epoxy-based, solvent-free vapor barrier	Twisttringen, Germany	0 g/L	0%	no	not available	yes			
<b>TREMprime WB Primer</b>	Waterproofing	High-solids, water-based primer	Toronto, Ontario, Canada	<1 g/L	<1%	no	not available	yes		Red List Free	
<b>TREMprime VB Plus Primer</b>	Waterproofing	Two-component silicone sealant primer	Batavia, Ohio	22 g/L	<5%	no	not available	yes			
<b>Trempro 640/642</b>	Waterproofing	One-part liquid polyurethane coatings	Cleveland, Ohio	0 g/L	0%	no	yes	yes		Red List Free	
<b>TREMproof 201/60 LV - R, SL, T</b>	Waterproofing	Fluid-applied, elastomeric waterproofing	Toronto, Ontario, Canada	R=82 g/L SL=95 g/L T=55 g/L	R=6.75% SL=6.36% T=4.92%	no	yes	yes		Red List Free	For LEED v4.1 credit, this level meets California Air Resources Board (CARB) 2007 Suggested Control Measure (SCM) for Architectural Coatings.
<b>TREMproof 250GC-LV - R, SL, T</b>	Waterproofing	Single-component, rapid curing, fluid-applied elastomeric waterproofing membrane	Cleveland, Ohio	R=177 g/L SL=157 g/L T=166 g/L	R=8% SL=8% T=14%	no	yes	no			



Product	Product Category	Description	Location of Manufacture	Sealant VOC (grams/L)	Sealant VOC % by Weight	Single Extracted Material	Manufacturing Inventory Available	Lower than SCAQMD rule 1113	Greenguard Certified	Living Building Challenge	Additional Info
<b>TREMproof 260</b>	Waterproofing	Single-component asphalt emulsion waterproofing membrane	Medina, Ohio	0 g/L	0%	no	yes	yes		Red List Free	
<b>TREMproof 500 Series</b>	Waterproofing	Exterior applied waterproofer (Article)	Newburyport, Massachusetts	<1 g/L	<1%	no	not available	yes			
<b>TREMproof 560A</b>	Waterproofing	Sheet applied waterproofing membrane (Article)	Umm Al-Quwain, UAE	<1 g/L	<1%	no	yes	yes		Red List Free	
<b>TREMproof 6100</b>	Waterproofing	Multi-layered, fabric-reinforced, hot-applied, rubberized asphalt waterproofing membrane	Missauga, Ontario, Canada	0 g/L	0%	no	yes	yes		Red List Free	
<b>TREMproof 6100 BM</b>	Waterproofing	Multi-layered, fabric-reinforced, hot-applied, rubberized asphalt waterproofing membrane	Missauga, Ontario, Canada	<1 g/L	<1%	no	yes	yes		Red List Free	Recycled content for TREMproof 6100BM is 6.34% (post industrial). Because this product is partially created with recycled content, consumers are able to work towards one Building Product Disclosure and Optimization Raw Materials Extraction point.
<b>TREMproof Amphibia</b>	Waterproofing	Sheet applied waterproofing membrane (Article)	Ponzano Veneto, Italy	<1 g/L	<1%	no	yes	yes		Red List Free	
<b>Universal Outlet</b>	Waterproofing	Exterior applied drainage product (Article)	Trenton, South Carolina	<1 g/L	1%	no	not available	yes		Red List Free	Recycled content for Universal Outlet is varies between 15% to 90% (Pre-consumer). Because this product is partially created with recycled content, consumers are able to work towards one Building Product Disclosure and Optimization Raw Materials Extraction point
<b>Universal Tee</b>	Waterproofing	Exterior applied drainage product (Article)	Monroe, North Carolina	<1 g/L	1%	no	not available	yes		Red List Free	Recycled content for Universal Tee is 100% (Pre-Consumer). Because this product is partially created with recycled content, consumers are able to work towards one Building Product Disclosure and Optimization Raw Materials Extraction point
<b>VISIONstrip</b>	Waterproofing	Precision-extruded glazing seal (Article)	Ashland, Ohio	<1 g/L	1%	no	yes	yes		Red List Free	
<b>Vulkem 171 Primer</b>	Traffic Coating	Quick-drying, one-part, moisture-curing primer	Cleveland, Ohio	559 g/L	58.25%	no	yes	yes		Red List Free	
<b>Vulkem 191 Primer</b>	Traffic Coating	Quick drying, one-part, moisture-curing primer	Cleveland, Ohio	<1 g/L	<1%	no	yes	yes		Red List Free	Vulkem 191 Primer has 19% rapidly renewable content.
<b>Vulkem 346</b>	Traffic Coating	Aliphatic one-component polyurethane intermediate or top coat	Cleveland, Ohio	353 g/L	27%	no	yes	yes		Red List Free	
<b>Vulkem 350</b>	Traffic Coating	Single-component urethane membrane base coat	Cleveland, Ohio	159 g/L	15%	no	yes	yes			

Product	Product Category	Description	Location of Manufacture	Sealant VOC (grams/L)	Sealant VOC % by Weight	Single Extracted Material	Manufacturing Inventory Available	Lower than SCAQMD rule 1113	Greenguard Certified	Living Building Challenge	Additional Info
<b>Vulkem 350FC</b>	Traffic Coating	Two-component, fast-curing, VOC-compliant, chemically-curing urethane membrane base coat	Cleveland, Ohio	<100 g/L	10%	no	not available	yes			
<b>Vulkem 350NF R, SL</b>	Traffic Coating	Single-component, low odor, low VOC, urethane membrane base coat	Cleveland, Ohio	R=86 g/L SL = 93 g/L	R=7% SL=27%	no	yes	yes			
<b>Vulkem 350FC</b>	Traffic Coating	Two-component, fast-curing, VOC-compliant, chemically-curing urethane membrane base coat	Cleveland, Ohio	<100 g/L	10%	no	not available	yes			
<b>Vulkem 351</b>	Traffic Coating	Single-component polyurethane, intermediate or top coat	Cleveland, Ohio	353 g/L	27%	no	yes	yes		Red List Free	
<b>Vulkem 351NF</b>	Traffic Coating	Two-component, polyurethane, intermediate or top coat	Cleveland, Ohio	94 g/L	0.06%	no	yes	yes		Red List Free	
<b>Vulkem 360NF</b>	Traffic Coating	Low odor, low VOC, water-cured, rapid setting urethane membrane base coat	Cleveland, Ohio	58 g/L	5.69%	no	yes	yes			
<b>Vulkem 801</b>	Traffic Coating	Liquid-applied, single-component, heavy duty, aluminized polyurethane coating system	Cleveland, Ohio	47 g/L	1%	no	yes	yes		Red List Free	Vulkem 950NF has 48.64% rapidly renewable content. Also, Vulkem 950NF's VOC level is below limits set by SCAQMD.
<b>Vulkem 950NF</b>	Traffic Coating	Two-component polyurethane, intermediate or top coat	Toronto, Ontario, Canada	18 g/L	<1%	no	yes	yes			
<b>Vulkem 951NF</b>	Traffic Coating	Two-component polyurethane intermediate coat or top coat	Cleveland, Ohio	94 g/L	4%	no	yes	yes		Red List Free	
<b>Vulkem OC810</b>	Traffic Coating	One-coat, high-solids, aliphatic, polyurethane membrane	Cleveland, Ohio	22 g/L	1%	no	yes	yes			
<b>Weatherlastic HB</b>	Waterproofing	Fiber reinforced, texturized, elastomeric, acrylic wall coating	Medina, OH	21 g/L	<1%	no	yes	yes			VOC content values are as reported for the highest VOC content color for all Weatherlastic HB colors. Other colors may have a lower VOC content reported on the SDS.

\*Air barrier systems, when properly installed, have been shown to reduce energy costs for HVAC by as much as 40% versus buildings without fully-adhered air barriers. This is important to remember as utilizing such an air barrier system such as ExoAir may assist in earning points within LEED.



















\*\*TREMDrain products are an excellent way to gather and redirect rainwater for reuse in non-potable applications, which can help contribute to water conservation efforts and points for water use reduction in LEED.

Products that adhere to the California Department of Public Health (CDPH) Standard Method V1.1-2010, is a standard vital to demonstrate compliance with LEED.

We are pleased to report that products without any Red List Chemicals can be used to assist in finishing projects aimed towards achieving a Living Building Challenge Certification.






# SEALANTS & ADHESIVES

Product	Product Category	Description	Location of Manufacture	Sealant VOC (grams/L)	Sealant VOC % by Weight	Single Extracted Material	Manufacturing Inventory Available	Lower than SCAQMD rule 1113	Adheres to CFPH Standard V1.1-2010	Living Building Challenge	Greenguard Certified	Additional Info
<b>440 Tape</b>	Selants & Mastics	Polyisobutylene cross-linked butyl, preformed sealant tape (Article)	Toronto, Ontario, Canada	<1 g/L	<1%	no	yes	yes	yes	Red List Free	 	
<b>Dymonic 100</b>	Selants & Mastics	Single-component, medium-modulus, non-sag polyurethane sealant	Cleveland, Ohio	40 g/L	3%	no	yes	yes	yes			
<b>Dymonic FC</b>	Selants & Mastics	Fast-curing, single-component, low-modulus, hybrid sealant	Toronto, Ontario, Canada	6 g/L	<1%	no	yes	yes	yes			
<b>Elastomeric and Butyl</b>	Selants & Mastics	Uncured neoprene sheeting (Article)	Toronto, Ontario, Canada	<1 g/L	<1%	no	not available	yes				
<b>EnerEDGE</b>	IG Spacers & Edge Sealants	EPDM insulating glass spacer (Article)	Ashland, Ohio	<1 g/L	<1%	no	yes	yes				
<b>EnerSEAL 332</b>	IG Spacers & Edge Sealants	Hot melt butyl IG perimeter sealant	Cleveland, Ohio	0 g/L	0%	no	not available	yes				
<b>EnerSEAL 340R</b>	IG Spacers & Edge Sealants	Reactive hot melt IG perimeter sealant	Cleveland, Ohio	0 g/L	0%	no	not available	yes				
<b>EnerSEAL JS680</b>	IG Spacers & Edge Sealants	Polyisobutylene primary sealant for framed IG spacers	Cleveland, Ohio	0 g/L	0%	no	not available	yes	yes		 	
<b>EnerSEAL JS780S</b>	IG Spacers & Edge Sealants	Polyisobutylene IG primary sealant for desiccated foam spacers	Cleveland, Ohio	0 g/L	0%	no	not available	yes				
<b>ExoAir Flex Foam</b>	Selants & Mastics	Single-component, polyurethane flexible foam sealant (*Air barrier)	Arkel, Zuid-Holland	153 g/L	15.4%	no	not available	yes				This product is typically used as an exterior applied product, as such, it does apply to the Low Emitting Materials credit in LEED v4.1.
<b>ExoAir LEF</b>	Selants & Mastics	Single-component, polyurethane foam sealant (*Air barrier)	Arkel, Zuid-Holland	210 g/L	<1%	no	not available	yes	yes		 	
<b>GUTTERSEAL + (Clear)</b>	Selants & Mastics	Gutter sealing elastomeric sealant	Toronto, Ontario, Canada	334 g/L	36%	no	not available	yes	Clear is exempt			VOC content values are as reported for the highest VOC content color for all Gutter Seal colors. Other colors may have a lower VOC content reported on their SDS
<b>GUTTERSEAL+ (White and Colors)</b>	Selants & Mastics	Gutter sealing elastomeric sealant	Toronto, Ontario, Canada	<20 g/L	<4%	no	not available	yes				

Product	Product Category	Description	Location of Manufacture	Sealant VOC (grams/L)	Sealant VOC % by Weight	Single Extracted Material	Manufacturing Inventory Available	Lower than SCAQMD rule 1113	Adheres to CFPH Standard V1.1-2010	Living Building Challenge	Greenguard Certified	Additional Info
<b>HDPE Protection/Barrier Courses (Root and Vapor)</b>	Selants & Mastics	High-density polyurethane protection sheet barrier	Spearfish, South Dakota	0 g/L	0%	no	not available	yes				
<b>Proglaze</b>	Selants & Mastics	Single-Component, moisture cure, acetoxysilicone sealant for glazing	Cleveland, Ohio	36 g/L	3.5%	no	yes	yes	yes	Red List Free	 	VOC content values are as reported for the highest VOC content color for all Proglaze colors. Other colors may have a lower VOC content reported on their SDS.
<b>Proglaze ETA</b>	Gaskets, Tapes & Extrusions	Silicone sealant	Ashland, Ohio	0 g/L	0%	no	yes	yes	yes	Red List Free	 	
<b>Proglaze ETA Extruded Aluminum Adapter</b>	Gaskets, Tapes & Extrusions	Silicone sealant	Newnan, Georgia	0 g/L	0%	no	not available	yes	yes		 	Recycled content for this product is 60% (55% Post-Industrial and 5% Post Consumer). Because this product is partially created with recycled content, consumers are able to work towards one Building Product Disclosure and Optimization - Raw Materials Extraction point. 100% recyclable after reaching end of life.
<b>Proglaze SSG</b>	Selants & Mastics	Single-component, neutral-cure, silicone sealant for structural glazing	Toronto, Ontario, Canada	14 g/L	1.20%	no	yes	yes	yes	Red List Free	 	
<b>Reinforcing Fabric</b>	Selants & Mastics	Polyester fabric	Toronto, Ontario, Canada	0 g/L	0%	no	yes	yes	yes			
<b>SGT-900 Series Tape</b>	Gaskets, Tapes & Extrusions	Polyurethane foam tape (Article)	Ashland, Ohio	0 g/L	0%	no	not available	yes	yes		 	
<b>Spectrem 1</b>	Selants & Mastics	Single-component, moisture cure, ultra-low modulus silicone sealant.	Toronto, Ontario, Canada	1 g/L	<1%	no	yes	yes	yes	Red List Free	 	*Red List Free dependent upon color.
<b>Spectrem 2</b>	Selants & Mastics	Single-component, neutral-cure, silicone sealant for 2-sided structural glazing	Toronto, Ontario, Canada	42 g/L	3%	no	yes	yes	yes	Red List Free	 	VOC content values are as reported for the highest VOC content color for all Spectrem 2 colors. Other colors may have a lower VOC content reported on the SDS.  *Red List Free dependent upon color.
<b>Spectrem 3</b>	Selants & Mastics	Single-component, non-staining sealant with advanced silicone technology	Toronto, Ontario, Canada	18 g/L	1%	no	yes	yes	yes		 	VOC content values are as reported for the highest VOC content color for all Spectrem 2 colors. Other colors may have a lower VOC content reported on the SDS.
<b>Spectrem 4-TS</b>	Selants & Mastics	Multi-component, non-staining sealant with advanced silicone technology	Toronto, Ontario, Canada	18 g/L	1%	no	yes	yes	yes		 	



Product	Product Category	Description	Location of Manufacture	Sealant VOC (grams/L)	Sealant VOC % by Weight	Single Extracted Material	Manufacturing Inventory Available	Lower than SCAQMD rule 1113	Adheres to CFPH Standard V1.1-2010	Living Building Challenge	Greenguard Certified	Additional Info
<b>Spectrem 800</b>	Selants & Mastics	Single-component, moisture cure, silicone sealants for highway and parking applications	Toronto, Ontario, Canada	1 g/L	<1%	no	yes	yes	yes	Red List Free	 	*Red List Free dependent upon color.
<b>Spectrem 900SL</b>	Selants & Mastics	Single-component, moisture-cure, silicone sealants for highway and parking application	Toronto, Ontario, Canada	1 g/L	<1%	no	yes	yes				
<b>Spectrem Simple Seal</b>	Gaskets, Tapes & Extrusions	Silicone extrusion (Article)	Harbor Springs, Michigan	0 g/L	0%	no	not available	yes	yes		 	
<b>Tremco Acoustical Sealant</b>	Selants & Mastics	One-part, non-skinning, sound damping sealant	Toronto, Ontario, Canada	155 g/L	10%	no	yes	no		Red List Free		
<b>Tremco ET 675</b>	Gaskets, Tapes & Extrusions	Extruded flow-resistant butyl tape	Toronto, Ontario, Canada	0 g/L	0%	no	not available	yes		Red List Free		
<b>Tremflex 834</b>	Selants & Mastics	Siliconized acrylic latex sealant	Toronto, Ontario, Canada	22 g/L	<1%	no	yes	yes	yes	Red List Free	 	VOC content values are as reported for the highest VOC content color for all Tremflex 834 colors. Other colors may have a lower VOC content reported on the SDS.
<b>Tremflex 834 Clear</b>	Selants & Mastics	Siliconized acrylic latex sealant	Toronto, Ontario, Canada	22 g/L	<1%	no	yes	yes	yes	Red List Free	 	VOC content values are as reported for the highest VOC content color for all Tremflex 834 colors. Other colors may have a lower VOC content reported on the SDS.
<b>TremGlaze S500+</b>	Selants & Mastics	One-part, medium-modulus, neutral-curing, silicone sealant ideal for window and door glazing	Toronto, Ontario, Canada	34 g/L	3.3	no	not available	yes		Red List Free	 	VOC content values are as reported for the highest VOC content color for all TremGlaze S500 + colors. Other colors may have a lower VOC content reported on the SDS.
<b>TremGlaze S600</b>	Selants & Mastics	One-part, medium-modulus, in-plant silicone glazing sealant	Toronto, Ontario, Canada	33 g/L	2	no	yes	yes				VOC content values are as reported for the highest VOC content color for all TremGlaze 600 colors. Other colors may have a lower VOC content reported on the SDS.
<b>TremGlaze S700</b>	Selants & Mastics	Single-component, high-modulus, neutral-cure silicone sealant glazing sealant	Toronto, Ontario, Canada	9 g/L	<1%	no	yes	yes		Red List Free		
<b>TremGlaze S900</b>	Selants & Mastics	Multi-component, reactive back bedding sealant	Toronto, Ontario, Canada	0 g/L	0	no	yes	yes				
<b>TremGlaze SA1100</b>	Selants & Mastics	Paintable siliconized acrylic latex sealant	Toronto, Ontario, Canada	14 g/L	0.65%	no	yes	yes	yes	Red List Free	 	
<b>TremGlaze UA1300</b>	Selants & Mastics	Single-component, urethane acrylic sealant	Greenville, South Carolina	18 g/L	1%	no	not available	yes		Red List Free		
<b>TremGlaze U1600</b>	Selants & Mastics	Low modulus, single-component, moisture curing, hybrid sealant	Toronto, Ontario, Canada	6 g/L	0%	no	yes	yes				

Product	Product Category	Description	Location of Manufacture	Sealant VOC (grams/L)	Sealant VOC % by Weight	Single Extracted Material	Manufacturing Inventory Available	Lower than SCAQMD rule 1113	Adheres to CFPH Standard V1.1-2010	Living Building Challenge	Greenguard Certified	Additional Info
<b>TREMgrip</b>	Selants & Mastics	Single-component, quick tack adhesive	Toronto, Ontario, Canada	<1 g/L	<1%	no	yes	yes				
<b>TREMprime Silicone Metal Primer</b>	Selants & Mastics	Single-component primer used to enhance adhesion of silicone sealants on nonporous surfaces	Toronto, Ontario, Canada	671 g/L	85%	no	yes	no		Red List Free		
<b>TREMprime Silicone Porous Primer</b>	Selants & Mastics	Single-component primer used to enhance adhesion of silicone sealant to porous surfaces	Munich, Germany	252 g/L	11%	no	not available	yes		Red List Free		
<b>TremPro 626</b>	Selants & Mastics	One-part, medium, gun grade polyurethane sealant	Cleveland, Ohio	47 g/L	2.60%	no	yes	yes				
<b>TremPro 635</b>	Selants & Mastics	Low-to-medium modulus, single-component, gun grade polyurethane sealant	Cleveland, Ohio	5 g/L	0%	no	yes	yes				
<b>TremPro 638 SSL</b>	Selants & Mastics	Low-modulus, one-component, semi-self-leveling polyurethane sealant	Cleveland, Ohio	0 g/L	0%	no	yes	yes				
<b>TremPro 644 HT</b>	Selants & Mastics	One-part, high temperature, silicone sealant	Cleveland, Ohio	30 g/L	2%	no	yes	yes	yes	Red List Free*	 	*Red List Free dependent upon color.
<b>TremPro 644 RTV</b>	Selants & Mastics	One-part, general purpose, acetoxy silicone sealant	Nunschritz, Germany	1 g/L	0%	no	yes	yes	yes	Red List Free	 	
<b>TremPro 645</b>	Selants & Mastics	Single-component, medium-modulus, neutral-cure silicone sealant	Toronto, Ontario, Canada	30 g/L	2%	no	yes	yes	yes	Red List Free		
<b>TREMPRO 830+ (Clear)</b>	Selants & Mastics	One-part, thermoplastic, elastomeric glass and siding sealant	Toronto, Ontario, Canada	334 g/L	36.25%	no	not available	yes	Clear is exempt	Red List Free		VOC content values are as reported for Tremco 830+ Clear. Tremco 830+ colors have a lower VOC content reported on the SDS.
<b>TREMPRO 830+ (White and Colors)</b>	Selants & Mastics	One-part, thermoplastic, elastomeric glass and siding sealant	Toronto, Ontario, Canada	<20 g/L	<4%	no	not available	yes		Red List Free*		VOC content values are as reported for all Tremco 830+ colors. Tremco 830+ clear has a higher VOC content reported on the SDS. *Red List Free dependent upon color.
<b>TremPro JS-773+</b>	Selants & Mastics	Non-skinning, non-drying, flexible, synthetic butyl elastomer acoustical sealant	Toronto, Ontario, Canada	151	<10%	no	not available	no				
<b>TremPro PU1000</b>	Selants & Mastics	Single component collapsible foam adhesive	Arkel, the Netherlands	153 g/L	15.18%	no	not available	yes				
<b>Tremsil 200</b>	Selants & Mastics	Single-component, acetoxy silicone sealant	Toronto, Ontario, Canada	1 g/L	0%	no	yes	yes	yes	Red List Free	 	

Product	Product Category	Description	Location of Manufacture	Sealant VOC (grams/L)	Sealant VOC % by Weight	Single Extracted Material	Manufacturing Inventory Available	Lower than SCAQMD rule 1113	Adheres to CFPH Standard V1.1-2010	Living Building Challenge	Greenguard Certified	Additional Info
<b>Tremsil 400</b>	Selants & Mastics	Single-component, neutral-cure silicone sealant	Toronto, Ontario, Canada	42 g/L	3%	no	yes	yes		Red List Free		VOC content values are as reported for the highest VOC content color for all Tremsil 400 colors. Other colors may have a lower VOC content reported on their SDS
<b>Tremsil 600</b>	Selants & Mastics	Single-component, neutral cure, fast skinning, medium modulus silicone sealant for glazing	Toronto, Ontario, Canada	33 g/L	2%	no	yes	yes	yes		 	VOC content values are as reported for the highest VOC content color for all Tremsil 600 colors. Other colors may have a lower VOC content reported on their SDS
<b>TREMstop Acrylic</b>	Firestopping	Acrylic latex sealant for use in firestop applications	Toronto, Ontario, Canada	38 g/L	1%	no	yes	yes	yes	Red List Free	 	VOC content values are as reported for the highest VOC content color for all Tremstop Acrylic colors. Other colors may have a lower VOC content reported on their SDS.
<b>TREMstop Acrylic Spray</b>	Firestopping	Sprayable acrylic latex sealant for use in firestop applications	Toronto, Ontario, Canada	40 g/L	1%	no	not available	yes	yes	Red List Free	 	
<b>TREMstop Fire Mortar</b>	Firestopping	One-part, fast setting, fire resistive microsilica compound	Toronto, Ontario, Canada	0 g/L	0%	no	yes	yes		Red List Free		
<b>TREMstop FS Blanket</b>	Firestopping	Firestopping fiber insulation blanket (Article)	Toronto, Ontario, Canada	<1 g/L	1%	no	not available	yes				
<b>TREMstop Fyre-Sil</b>	Firestopping	Gun-grade, neutral-cure, silicone sealant for use in firestop applications	Toronto, Ontario, Canada	26 g/L	2%	no	yes	yes	yes	Red List Free*	 	Please reach out to Tremco for assistance on which colors can be used for Living Building Challenge credit. *Red List Free depending on grade
<b>TREMstop Smoke and Sound Sealant</b>	Firestopping	Gun-grade, acrylic latex sealant	Toronto, Ontario, Canada	14 g/L	0.67%	no	yes	yes		Red List Free		
<b>TREMstop Smoke and Sound Spray</b>	Firestopping	Sprayable acrylic latex sealant	Toronto, Ontario, Canada	35 g/L	1%	no	yes	yes	yes	Red List Free	 	
<b>TREMstop SuperStrip</b>	Firestopping	Graphite-based intumescent wrap strip	Burlington Township, New Jersey	<1 g/L	1%	no	yes	yes	yes	Red List Free	 	VOC content values are lower than the limits set by SCAQMD Rule 1113.
<b>Vulkem 116</b>	Selants & Mastics	Textured, single-component polyurethane sealant	Cleveland, Ohio	<50 g/L	<2%	no	yes	yes				VOC content values are as reported for the highest VOC content color for all Vulkem 116 colors. Other colors may have a lower VOC content reported on their SDS.
<b>Vulkem 445SSL</b>	Selants & Mastics	Field-tintable, semi-self-leveling, multi-component, polyurethane sealant.	Cleveland, Ohio	106 g/L	8.42%	no	yes	yes				
<b>Vulkem 45SSL</b>	Selants & Mastics	Semi-self-leveling, single-component, polyurethane sealant	Cleveland, Ohio	108 g/L	8.19%	no	yes	yes				

Product	Product Category	Description	Location of Manufacture	Sealant VOC (grams/L)	Sealant VOC % by Weight	Single Extracted Material	Manufacturing Inventory Available	Lower than SCAQMD rule 1113	Adheres to CFPH Standard V1.1-2010	Living Building Challenge	Greenguard Certified	Additional Info
<b>Willseal 250-B</b>	Expansion Joints & Transitions	Precompressed expansion joint (Article)	Hudson, New Hampshire	<1g/L	<1%	no	not available	yes	yes		 	
<b>Willseal 250-CM</b>	Expansion Joints & Transitions	Precompressed expansion joint (Article)	Hudson, New Hampshire	<1g/L	<1%	no	not available	yes	yes		 	
<b>Willseal 250-R</b>	Expansion Joints & Transitions	Precompressed expansion joint (Article)	Hudson, New Hampshire	<1g/L	<1%	no	not available	yes	yes		 	
<b>Willseal 600</b>	Expansion Joints & Transitions	Precompressed expansion joint (Article)	Bodenwohr, Bavaria, Germany	<1g/L	<1%	no	not available	yes	yes	Red List Free	 	
<b>Willseal STC</b>	Expansion Joints & Transitions	Precompressed expansion joint (Article)	Hudson, New Hampshire	<1g/L	<1%	no	not available	yes	yes	Red List Free	 	
<b>Willseal Backer Roll</b>	Expansion Joints & Transitions	Precompressed expansion joint (Article)	Bodenwohr, Bavaria, Germany	<1g/L	<1%	no	not available	yes	yes	Red List Free	 	
<b>Willseal Coreseal</b>	Expansion Joints & Transitions	Precompressed expansion joint (Article)	Hudson, New Hampshire	<1g/L	<1%	no	not available	yes	yes		 	
<b>Willseal Coresal H</b>	Expansion Joints & Transitions	Precompressed expansion joint (Article)	Hudson, New Hampshire	<1g/L	<1%	no	not available	yes	yes		 	
<b>Willseal Coresal V</b>	Expansion Joints & Transitions	Precompressed expansion joint (Article)	Hudson, New Hampshire	<1g/L	<1%	no	not available	yes	yes		 	
<b>Willseal Coresal-CM</b>	Expansion Joints & Transitions	Precompressed expansion joint (Article)	Hudson, New Hampshire	<1g/L	<1%	no	not available	yes	yes		 	
<b>Willseal Coresal-R</b>	Expansion Joints & Transitions	Precompressed expansion joint (Article)	Hudson, New Hampshire	<1g/L	<1%	no	not available	yes	yes		 	
<b>Willseal Seismic</b>	Expansion Joints & Transitions	Precompressed expansion joint (Article)	Hudson, New Hampshire	<1g/L	<1%	no	not available	yes	yes		 	
<b>Willseal Seismic HS</b>	Expansion Joints & Transitions	Precompressed expansion joint (Article)	Hudson, New Hampshire	<1g/L	<1%	no	not available	yes	yes		 	

Tremco CPG is a RPM International Inc. brand.  
View the RPM International Inc. Sustainability Report at <https://sustainability.rpminc.com/>

Products that adhere to the California Department of Public Health (CDPH) Standard Method V1.1-2010, is a standard vital to demonstrate compliance with LEED.

We are pleased to report that products without any Red List Chemicals can be used to assist in finishing projects aimed towards achieving a Living Building Challenge Certification.





**TREMCO**  
*Construction Products Group*



Tremco Construction Products Group (CPG) brings together Tremco CPG Inc. and its Dryvit and Nudura brands; Willseal; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc. and its Pure Air Control Services and Canam Building Envelope Specialists offerings; and Weatherproofing Technologies Canada, Inc.



Tremco CPG Inc.  
3735 Green Road | Beachwood, OH 44122  
US: 800.852.9068 | CAN: 800.263.6046  
[tremcocpg.com](http://tremcocpg.com)  
CSWLEED 08.15.2024