



Waterproofing and Drainage Selection Guide*

TREMproof®, Paraseal® and TREMDrain®

	FLUID	TREMproof 250GC	TREMproof 201/60	TREMproof 260	TREMproof 6100	TREMproof PUMA	SHEET	Paraseal	Paraseal LG	Paraseal GM	Paraseal GM/LG 20mil	Paraseal GM/LG 60mil	TREMproof Amphibia	TREMproof 545	TREMproof 560	DRAINAGE	TREMDrain	TREMDrain S	TREMDrain 1000	TREMDrain 1000 PF	TREMDrain 2000	TREMDrain Total Drain	TREMDrain QSP
Vertical																							
Backfilled Wall (<20')		•	•	•				•	•					•	•							•	•
Backfilled Wall (>20')		•	•	•				•	•					•	•					•	•	•	•
Blindside/Lagging Wall (<20')				•				•	•		•	•	•							•		•	•
Blindside/Lagging Wall (>20')				•				•	•		•	•	•							•	•	•	•
Horizontal																							
Split Slab or Paver		•	•		•	•																	
Below Slab on Grade								•		•	•	•											
Vegetated Roofs		•			•	•				•	•	•											
Planters		•			•	•																	•
Other																							
Methane Barrier**		•		•					•	•	•												
Submerged Conditions**		•		•						•	•	•											
Green/Damp Concrete		•		•				•	•	•	•			•	•					•	•	•	•

* The Waterproofing and Drainage Selection Guide is to be used as a general reference and reflects two of the components that become integrated into a waterproofing system. Please consult your local Tremco Manufacturer's Representative for regional recommendations based on your local building practices and warranty requirements.

** Please consult your local Tremco Manufacturer's Representative for recommendations and approval of your specific application. Reference the current product data sheet on our website at www.tremcosealants.com for more specific product information. For priming recommendations, please contact Tremco Technical Services or reference the Primer Guide on our web site.

