



WATERPROOFING AND DRAINAGE SELECTION GUIDE*

TREMproof®, Paraseal® and TREMDrain®

| | Fluid | TREMproof 250GC | TREMproof 201/160 | TREMproof 260 | TREMproof 6100 | TREMproof PU/MA | Sheet | Paraseal | Paraseal LG | Paraseal GM | Paraseal GM/LG 20mil | Paraseal GM/LG 60mil | TREMproof Amphibia | TREMproof 360A | Drainage | TREMDrain | TREMDrain S | TREMDrain 1000 | TREMDrain 1000 PF | TREMDrain 2000 | TREMDrain Total Drain | TREMDrain QSP |
|-------------------------------|-------|-----------------|-------------------|---------------|----------------|-----------------|-------|----------|-------------|-------------|----------------------|----------------------|--------------------|----------------|----------|-----------|-------------|----------------|-------------------|----------------|-----------------------|---------------|
| Vertical | | | | | | | | | | | | | | | | | | | | | | |
| Backfilled Wall (<20') | | ● | ● | ● | | | | ● | ● | | | | | ● | ● | | | | | ● | ● | |
| Backfilled Wall (>20') | | ● | ● | ● | | | | ● | ● | | | | ● | | | | ● | ● | | ● | ● | |
| Blindside/Lagging Wall (<20') | | | | ● | | | | | ● | ● | ● | | | | ● | | | | | | ● | |
| Blindside/Lagging Wall (>20') | | | | ● | | | | ● | ● | ● | ● | | | | | | ● | ● | | ● | | |
| Horizontal | | | | | | | | | | | | | | | | | | | | | | |
| Split Slab or Paver | | ● | ● | | ● | ● | | | | | | | | | | | ● | | ● | ● | | |
| Below Slab on Grade | | | | | | | | ● | | ● | ● | ● | | | | | ● | | | | | |
| Vegetated Roofs | | ● | | | ● | ● | | | | | | | | | | | | | | | | |
| Planters | | ● | | | ● | ● | | | | | | | | | | | | | | | ● | |
| Other | | | | | | | | | | | | | | | | | | | | | | |
| Methane Barrier** | | ● | | ● | | | | | ● | ● | ● | | | | | | | | | | | |
| Submerged Conditions** | | ● | | | ● | | | | | ● | ● | ● | | | | | | | | | | |
| Green/Damp Concrete | | ● | | ● | | | | ● | ● | ● | ● | | ● | | ● | ● | ● | ● | ● | ● | ● | |

* The Waterproofing and Drainage Selection Guide is to be used as a general reference and reflects two of the components that become integrated into a waterproofing system.

Please consult your local Tremco Manufacturer's Representative for regional recommendations based on your local building practices and warranty requirements.

** Please consult your local Tremco Manufacturer's Representative for recommendations and approval of your specific application.

Reference the current product data sheet on our website at www.tremcosealants.com for more specific product information.

For priming recommendations, please contact Tremco Technical Services or reference the Primer Guide on our web site.

Tremco Commercial Sealants & Waterproofing | 3735 Green Road | Beachwood, OH 44122 | US: 800.852.9068 | CAN: 800.363.3213 | tremcosealants.com

Tremco Construction Products Group (CPG) brings together Tremco Incorporated's Commercial Sealants & Waterproofing and Roofing & Building Maintenance operating divisions; Dryvit Systems, Inc.; Nudura Inc.; Willseal; Weatherproofing Technologies, Inc. and Weatherproofing Technologies Canada, Inc.

Tremco®, TREMproof®, Paraseal® and TREMDrain® are registered trademarks of Tremco Incorporated. Willseal is a registered trademark of Use of the ® symbol indicates registration with the US Patent & Trademark Office and the Canadian Intellectual Property Office.



Construction Products Group