

VR SlopeLoc


GROWING MEDIA RETENTION SYSTEM
FOR SLOPED APPLICATIONS

PRODUCT DESCRIPTION

Description Expandable sheet strip assembly with welded seams, which, when expanded, create a 3-dimensional cellular containment system for sloped green roofs.

Options

VR SlopeLoc 4 4" SST cabled systems for slopes >15° <45°
VR SlopeLoc 6 6" SST cabled systems for slopes >15° <45°
VR SlopeLoc 8 8" SST cabled systems for slopes >15° <45°



PRODUCT PROPERTIES

Material High-density polypropylene

Dimensions

Width x Length 8 ft x 21 ft
(2.5 m x 6.5 m)
Strip Thickness ASTM D-5199:
0.05-inch (1.25 mm) +/- 5%

Weight per section

VR SlopeLoc 4 57 lbs. (25.9 kg)
VR SlopeLoc 6 86 lbs. (39 kg)
VR SlopeLoc 8 114 lbs. (51.7 kg)

Sections per Pallet

VR SlopeLoc 4 50
VR SlopeLoc 6 30
VR SlopeLoc 8 25

Seam Peel Strength

VR SlopeLoc 4 1420 N (240 lbs.)
VR SlopeLoc 6 2130 N (480 lbs.)
VR SlopeLoc 8 2840 N (640 lbs.)

Fabric 120 lbs.

Polymer Density ASTM D-1505:
0.941 - 0.960 g/cc min.

Additional Information Environmental Stress Crack
Resistance per ASTM D-1693:
3000 hrs.min.

Tremco Commercial Sealants & Waterproofing

UNITED STATES
3735 Green Road
Beachwood, Ohio,
44122
T: 1.800.321.7906

CANADA
220 Wicksteed Avenue
Toronto, Ontario
M4H 1G7
T: 1.800.363.3213

Tremco Roofing & Building Maintenance

UNITED STATES
3735 Green Road,
Beachwood, Ohio
44122
T: 1.800.526.2728

CANADA
50 Beth Neelson Drive
Toronto, Ontario
M4H 1M6
T: 1.800.668.9879

PRODUCT SPECIFICATION DATA SHEET

VR SlopeLoc

GROWING MEDIA RETENTION SYSTEM
FOR SLOPED APPLICATIONS

GUARANTEE / WARRANTY

Tremco Incorporated warrants VR SlopeLoc to be free of defects and to meet published physical properties when tested according to ASTM and Tremco standards. Under this warranty, any VR SlopeLoc product that is proved to be defective when applied in accordance to our written instructions, and in applications recommended by Tremco as suitable for this product will be replaced with like product at no charge.

THIS IS BUYER'S SOLE AND EXCLUSIVE REMEDY.

All claims concerning product defects must be made in writing within twelve (12) months of shipment. The absence of such claims in writing during this period will constitute a waiver of all claims with respect to such product. This warranty shall be IN LIEU OF any other warranty, express or implied, including but not limited to, any implied warranty of MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

TREMCO[®]

www.tremcosealants.com
www.tremcoroofing.com

© 2017 Tremco Incorporated

Tremco Commercial Sealants & Waterproofing

UNITED STATES
3735 Green Road
Beachwood, Ohio,
44122
T: 1.800.321.7906

CANADA
220 Wicksteed Avenue
Toronto, Ontario
M4H 1G7
T: 1.800.363.3213

Tremco Roofing & Building Maintenance

UNITED STATES
3735 Green Road,
Beachwood, Ohio
44122
T: 1.800.526.2728

CANADA
50 Beth Nealson Dr
Toronto, Ontario
M4H 1M6
T: 1.800.668.9879