

# VR MOD

SYSTEM	Components
<b>VR MOD SEDUM</b>	<b>VR Mod</b> Modular Tray, with Integrated Filter Fabric and Drainage/Retention Panel <b>VR AeroMix</b> Growing Media <b>Pre-Vegetated Sedum Blend*</b>
<b>VR MOD MEADOW</b>	<b>VR Mod</b> Modular Tray, with Integrated Filter Fabric and Drainage/Retention Panel <b>VR HydraMix</b> Growing Media <b>Pre-Vegetated Shortgrass Meadow Blend*</b>

VEGETATION OPTIONS	Minimum System Requirement	Maintenance	Minimum Lead Time
<b>Custom Sedum Blends</b>	VR MOD SEDUM	<i>High</i> Irrigation, erosion control measures and weeding required more frequently until full coverage is established.	4 months (Excluding off-season in cold climate regions.)
<b>Custom Shortgrass Meadow Blends</b>	VR MOD MEADOW	<i>High</i> Irrigation, erosion control measures and weeding required more frequently until full coverage is established.	2 months (Excluding off-season in cold climate regions.)
<b>Assorted Perennials</b>	VR MOD MEADOW	<i>High</i> Irrigation, erosion control measures and weeding required more frequently until full coverage is established.	3 months (Excluding off-season in cold climate regions.)

ADDITIONAL OPTIONS	Description	Important Factors
<b>VR RootBloc 10</b> 10 mil Root Barrier	This Standard Polyethylene Root Barrier is 4 ply embedded with a polyester corded grid, Class A fire-rated.	Not all roofing systems require a root barrier. Check your roofing system specs for more guidance. Seams and projections require Manufacturer's Technical Tape.
<b>VR RootBloc 40</b> 40 mil Root Barrier	This Polyethylene Root Barrier is extra high strength with Carbon black for UV resistance.	Not all roofing systems require a root barrier. Check your roofing system specs for more guidance. Seams and projections require full seaming, with Manufacturer's Technical Tape or heat welding.

ACCESSORIES (required)	Description	Important Factors
<b>VR DrainGuard</b> Drain Inspection Box	Aluminum. 15 x 15 inch box with drainage holes and lockable lid. Standard height: 6 inches.	Check roof drain sizing to ensure outer flange does not exceed 15-inches in diameter. Custom drain inspection boxes are available.
<b>VR EdgeGuard</b> Edging for VR Systems	Extruded Aluminum. L-shaped with drainage holes. 96-inch long pieces. Use with edging connectors, corners, and leveling strips, as needed. Standard heights: 6 inches.	Edging comes complete with Manufacturer's Sealing Tape for perimeter modular side walls, to prevent soil erosion through the side wall.

ACCESSORIES (optional)	Description	Important Factors
<b>High Efficiency Rotary Irrigation</b>	Hydro-Rain Programmable Controller, Valves, Rain Sensor, Blu-Lock Pipe and Fittings, Hunter Sprinkler Bodies with Rotary Heads.	Hose bibs are required per separate roof area. 110V GFCI receptacle is required where Controller is to be mounted (unless choosing Solar Option, see below).
<b>Rotary Irrigation w/ Solar Option</b>	Solar Panels are available to be added to the systems where power supply is difficult to attain.	

\*All Plantings options comprise of Standard species mixes. Quote for Custom mixes.



[www.tremcosealants.com](http://www.tremcosealants.com)  
[www.tremcoroofing.com](http://www.tremcoroofing.com)

© 2017 Tremco Incorporated

## Tremco Commercial Sealants & Waterproofing

**UNITED STATES**  
3735 Green Road  
Beachwood, Ohio,  
44122  
T: 1.800.321.7906

**CANADA**  
220 Wicksteed Avenue  
Toronto, Ontario  
M4H 1G7  
T: 1.800.363.3213

## Tremco Roofing & Building Maintenance

**UNITED STATES**  
3735 Green Road,  
Beachwood, Ohio  
44122  
T: 1.800.526.2728

**CANADA**  
50 Beth Nealson Drive  
Toronto, Ontario  
M4H 1M6  
T: 1.800.668.9879

