

## PRODUCT SPECIFICATION DATA SHEET VR FabricLok

DOUBLE-COATED TECHNICAL TAPE FOR SEALING SEAMS IN VEGETATED ROOF ASSEMBLIES

### **PRODUCT DESCRIPTION**

Description	High strength double coated tape	
	Appropriate for most surfaces.	
	Excellent on plastics such as	
	polypropylene and powder-coated	
	paints.	

Options

None



## **PRODUCT PROPERTIES**

	<b>B 1 1 1 1 1 1 1 1 1 1</b>		
Material	Polyester, double-coated w/ adhesive	Adhesion Properties	
		15 min dwell @RT:	
Dimensions		Stainless Steel	85 oz./inch (9.3 N/cm)
Width x Length of roll	2-inch x 60 yd (50 mm x 55 m)	Polycarbonate	110 oz./inch (12.3 N/cm)
		ABS	80 oz./inch (8.8 N/cm)
Tape Thickness	7.9 mil (0.20 mm)	Polypropylene	95 oz./inch (10.4 N/cm)
		72 hr dwell @RT:	
Breakdown Voltage	7500 volts	Stainless Steel	110 oz./inch (12 N/cm)
		Polycarbonate	140 oz./inch (15.3 N/cm)
Dielectric Strength	900 volts/mil	ABS	110 oz./inch (12 N/cm)
		Polypropylene	110 oz./inch (12 N/cm)
Shear Strength			
@ RT, 1000 grams	10,000 min	Temperature Resist	tance
@ 158°F, 500 grams	10,000 min	Long Term	250°F (121°C)
		Short Term	300°F (149°C)

Additional Info

Use

Required for sealing VR Filter Fabric to VR EdgeGuard in VR Systems

#### Tremco Commercial Sealants & Waterproofing

 UNITED STATES
 CANADA

 3735 Green Road
 220 Wickst

 Beachwood, Ohio,
 Toronto, Or

 44122
 M4H 1G7

 T: 1.800.321.7906
 T: 1.800.36

CANADA 220 Wicksteed Avenue Toronto, Ontario M4H 1G7 T: 1.800.363.3213

#### Tremco Roofing & Building Maintenance

UNITED STATES 3735 Green Road, Beachwood, Ohio 44122 T: 1.800.526.2728 CANADA 50 Beth Nealson Drive Toronto, Ontario M4H 1M6 T: 1.800.668.9879



# PRODUCT SPECIFICATION DATA SHEET VR FabricLok

DOUBLE-COATED TECHNICAL TAPE FOR SEALING SEAMS IN VEGETATED ROOF ASSEMBLIES

## **GUARANTEE / WARRANTY**

Tremco Incorporated warrants VR FabricLok to be free of defects and to meet published physical properties when tested according to ASTM and Tremco standards. Under this warranty, any VR FabricLok product that is proved to be defective when applied in accordance to our written instructions, and in applications recommended by Tremco as suitable for this product will be replaced with like product at no charge.

THIS IS BUYER'S SOLE AND EXCLUSIVE REMEDY.

All claims concerning product defects must be made in writing within twelve (12) months of shipment. The absence of such claims in writing during this period will constitute a waiver of all claims with respect to such product. This warranty shall be IN LIEU OF any other warranty, express or implied, including but not limited to, any implied warranty of MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.



#### Tremco Commercial Sealants & Waterproofing

UNITED STATES 3735 Green Road Beachwood, Ohio, 44122 T: 1.800.321.7906 CANADA 220 Wicksteed Avenue Toronto, Ontario M4H 1G7 T: 1.800.363.3213

UNITED STATES e 3735 Green Road, Beachwood, Ohio 44122 T: 1.800.526.2728 CANADA 50 Beth Nealson Dr Toronto, Ontario M4H 1M6 T: 1.800.668.9879

Tremco Roofing & Building Maintenance