

# VR FabricLok

DOUBLE-COATED TECHNICAL TAPE FOR SEALING SEAMS  
IN VEGETATED ROOF ASSEMBLIES

### PRODUCT DESCRIPTION

**Description** High strength double coated tape. Appropriate for most surfaces. Excellent on plastics such as polypropylene and powder-coated paints.

**Options** None



### PRODUCT PROPERTIES

**Material** Polyester, double-coated w/ adhesive

#### Dimensions

**Width x Length of roll** 2-inch x 60 yd (50 mm x 55 m)

**Tape Thickness** 7.9 mil (0.20 mm)

**Breakdown Voltage** 7500 volts

**Dielectric Strength** 900 volts/mil

#### Shear Strength

@ RT, 1000 grams 10,000 min

@ 158°F, 500 grams 10,000 min

#### Adhesion Properties

15 min dwell @RT:

Stainless Steel 85 oz./inch (9.3 N/cm)

Polycarbonate 110 oz./inch (12.3 N/cm)

ABS 80 oz./inch (8.8 N/cm)

Polypropylene 95 oz./inch (10.4 N/cm)

72 hr dwell @RT:

Stainless Steel 110 oz./inch (12 N/cm)

Polycarbonate 140 oz./inch (15.3 N/cm)

ABS 110 oz./inch (12 N/cm)

Polypropylene 110 oz./inch (12 N/cm)

#### Temperature Resistance

Long Term 250°F (121°C)

Short Term 300°F (149°C)

#### Additional Info

**Use** Required for sealing VR Filter Fabric to VR EdgeGuard in VR Systems

### Tremco Commercial Sealants & Waterproofing

UNITED STATES  
3735 Green Road  
Beachwood, Ohio,  
44122  
T: 1.800.321.7906

CANADA  
220 Wicksteed Avenue  
Toronto, Ontario  
M4H 1G7  
T: 1.800.363.3213

### Tremco Roofing & Building Maintenance

UNITED STATES  
3735 Green Road,  
Beachwood, Ohio  
44122  
T: 1.800.526.2728

CANADA  
50 Beth Neelson Drive  
Toronto, Ontario  
M4H 1M6  
T: 1.800.668.9879

# PRODUCT SPECIFICATION DATA SHEET

## VR FabricLok

DOUBLE-COATED TECHNICAL TAPE FOR SEALING SEAMS  
IN VEGETATED ROOF ASSEMBLIES

### GUARANTEE / WARRANTY

Tremco Incorporated warrants VR FabricLok to be free of defects and to meet published physical properties when tested according to ASTM and Tremco standards. Under this warranty, any VR FabricLok product that is proved to be defective when applied in accordance to our written instructions, and in applications recommended by Tremco as suitable for this product will be replaced with like product at no charge.

THIS IS BUYER'S SOLE AND EXCLUSIVE REMEDY.

All claims concerning product defects must be made in writing within twelve (12) months of shipment. The absence of such claims in writing during this period will constitute a waiver of all claims with respect to such product. This warranty shall be IN LIEU OF any other warranty, express or implied, including but not limited to, any implied warranty of MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

**TREMCO**<sup>®</sup>

[www.tremcosealants.com](http://www.tremcosealants.com)  
[www.tremcoroofing.com](http://www.tremcoroofing.com)

© 2017 Tremco Incorporated

### Tremco Commercial Sealants & Waterproofing

UNITED STATES  
3735 Green Road  
Beachwood, Ohio,  
44122  
T: 1.800.321.7906

CANADA  
220 Wicksteed Avenue  
Toronto, Ontario  
M4H 1G7  
T: 1.800.363.3213

### Tremco Roofing & Building Maintenance

UNITED STATES  
3735 Green Road,  
Beachwood, Ohio  
44122  
T: 1.800.526.2728

CANADA  
50 Beth Nealson Dr  
Toronto, Ontario  
M4H 1M6  
T: 1.800.668.9879