

# SAFETY DATA SHEET

## 1. Identification

**Material name:** VULKEM 45 SSL WHITE QT CTG  
**Material:** 445806A 333

### Recommended use and restriction on use

**Recommended use:** Sealant  
**Restrictions on use:** Not known.

### Manufacturer/Importer/Supplier/Distributor Information

Tremco Canadian Sealants  
220 Wicksteed Ave  
Toronto ON M4H 1G7  
CA

**Contact person:** EH&S Department  
**Telephone:** 1-800-263-6046  
**Emergency telephone number:** 1-800-424-9300 (US); 1-613-996-6666 (Canada)

## 2. Hazard(s) identification

### Hazard Classification

#### Health Hazards

Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Carcinogenicity	Category 1A

#### Unknown toxicity - Health

Acute toxicity, oral	55.79 %
Acute toxicity, dermal	63.63 %
Acute toxicity, inhalation, vapor	98.18 %
Acute toxicity, inhalation, dust or mist	90.7 %

### Environmental Hazards

Acute hazards to the aquatic environment	Category 3
------------------------------------------	------------

#### Unknown toxicity - Environment

Acute hazards to the aquatic environment	88.92 %
Chronic hazards to the aquatic environment	98.19 %

### Label Elements

**Hazard Symbol:**



**Signal Word:** Danger

**Hazard Statement:** May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
May cause an allergic skin reaction.  
May cause cancer.  
Harmful to aquatic life.

**Precautionary Statements**

**Prevention:** Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid release to the environment.

**Response:** IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor/... IF ON SKIN: Wash with plenty of water/... If skin irritation or rash occurs: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Wash contaminated clothing before reuse.

**Storage:** Store locked up.

**Disposal:** Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

**Hazard(s) not otherwise classified (HNOC):** None.

**3. Composition/information on ingredients**

**Mixtures**

Chemical Identity	CAS number	Content in percent (%)*
-------------------	------------	-------------------------

Calcium Carbonate (Limestone)	1317-65-3	10 - <20%
Polyvinyl chloride	9002-86-2	10 - <20%
Titanium dioxide	13463-67-7	1 - <5%
Petroleum distillates	64742-47-8	1 - <5%
Aliphatic naphtha	64742-88-7	1 - <5%
Calcium oxide	1305-78-8	1 - <5%
Xylene	1330-20-7	1 - <5%
Isophorone Diisocyanate	4098-71-9	0.1 - <1%
Aluminum oxide	1344-28-1	0.1 - <1%
Ethylbenzene	100-41-4	0.1 - <1%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - <1%
Nonane	111-84-2	0.1 - <1%
Iodopropynyl butylcarbamate	55406-53-6	0.01 - <1%

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

#### 4. First-aid measures

- Ingestion:** Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
- Inhalation:** Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
- Skin Contact:** If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
- Eye contact:** Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.

#### Most important symptoms/effects, acute and delayed

**Symptoms:** May cause skin and eye irritation.

#### Indication of immediate medical attention and special treatment needed

**Treatment:** Symptoms may be delayed.

#### 5. Fire-fighting measures

**General Fire Hazards:** No unusual fire or explosion hazards noted.

#### Suitable (and unsuitable) extinguishing media

**Suitable extinguishing media:** Use fire-extinguishing media appropriate for surrounding materials.

**Unsuitable extinguishing media:** Do not use water jet as an extinguisher, as this will spread the fire.

**Specific hazards arising from the chemical:** During fire, gases hazardous to health may be formed.

**Special protective equipment and precautions for firefighters**

**Special fire fighting procedures:** No data available.

**Special protective equipment for fire-fighters:** Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

**6. Accidental release measures**

**Personal precautions, protective equipment and emergency procedures:** Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

**Methods and material for containment and cleaning up:** Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

**Notification Procedures:** In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

**Environmental Precautions:** Avoid release to the environment. Prevent further leakage or spillage if safe to do so.

**7. Handling and storage**

**Precautions for safe handling:** Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling.

**Conditions for safe storage, including any incompatibilities:** Store locked up.

**8. Exposure controls/personal protection**

**Control Parameters**

**Occupational Exposure Limits**

Chemical Identity	Type	Exposure Limit Values	Source
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air

(Limestone) - Respirable fraction.			Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values (2011)
Polyvinyl chloride - as vinyl chloride monomer	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	OSHA_AC T	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
Polyvinyl chloride - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Polyvinyl chloride - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Polyvinyl chloride - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Titanium dioxide - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	200 mg/m3	US. ACGIH Threshold Limit Values (2011)
Aliphatic naphtha - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Aliphatic naphtha	PEL	100 ppm 400 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (01 2017)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Xylene	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	STEL	150 ppm 655 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)

	TWA	100 ppm	435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm	435 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	150 ppm	655 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL		350 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	ST ESL		80 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL		42 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	AN ESL		180 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	STEL	150 ppm	655 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	Ceiling	300 ppm		US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA PEL	100 ppm	435 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA	100 ppm		US. ACGIH Threshold Limit Values (2011)
	STEL	150 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Isophorone Diisocyanate	TWA	0.005 ppm		US. ACGIH Threshold Limit Values (2011)
Aluminum oxide - Respirable fraction.	TWA		1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Aluminum oxide - Total dust.	PEL		15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA		50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Aluminum oxide - Respirable fraction.	TWA		15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
	TWA		5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Aluminum oxide - Total dust.	TWA		15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Ethylbenzene	TWA	20 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm	2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Nonane	TWA	200 ppm		US. ACGIH Threshold Limit Values (02 2012)

Chemical name	Type	Exposure Limit Values	Source
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Petroleum distillates	TWA	525 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWA	200 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWA	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	STEL	150 ppm 651 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)

Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Ethylbenzene	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Hydrotreated heavy naphthenic distillate - Mist.	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)



Chemical name	Type	Exposure Limit Values	Source
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Polyvinyl chloride - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polyvinyl chloride - Respirable fraction.	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polyvinyl chloride - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Petroleum distillates	TWA	525 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Petroleum distillates - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWA	200 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)

Aliphatic naphtha - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Aliphatic naphtha - Non-aerosol. - as total hydrocarbon vapor	TWA	200 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Aliphatic naphtha	TWA	400 ppm 1,590 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWA	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Xylene	TWA	100 ppm 434 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
	STEL	150 ppm 651 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
Xylene	TWA	100 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	150 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Xylene	TWA	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	150 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Xylene	STEL	150 ppm 651 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Isophorone Diisocyanate	TWA	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)

Isophorone Diisocyanate	TWA	0.005 ppm 0.045 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Aluminum oxide - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Aluminum oxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Aluminum oxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Aluminum oxide - Respirable fraction.	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Aluminum oxide - Inhalable fraction.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Aluminum oxide - Respirable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Aluminum oxide - Total dust. - as Al	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Ethylbenzene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Ethylbenzene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Ethylbenzene	STEL	125 ppm 543 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	100 ppm 434 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Hydrotreated heavy naphthenic distillate - Mist.	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Nonane	TWA	200 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Nonane	TWA	200 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Nonane	TWA	200 ppm 1,050 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Zirconium dioxide - as Zr	STEL	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Zirconium dioxide - as Zr	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Zirconium dioxide - as Zr	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Amorphous silica - Total	TWA	4 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Amorphous silica - Respirable.	TWA	1.5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Amorphous silica - Respirable dust.	TWA	6 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Toluene	TWA	20 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Toluene	TWA	20 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Toluene	TWA	50 ppm 188 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
1,2,4-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,2,4-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Cumene	STEL	75 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Cumene	TWA	50 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Cumene	TWA	50 ppm	246 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Benzene	STEL	2.5 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.5 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Benzene	TWA	0.5 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	STEL	2.5 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Benzene	TWA	1 ppm	3 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	STEL	5 ppm	15.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Naphthalene	STEL	15 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Naphthalene	TWA	10 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Naphthalene	TWA	10 ppm	52 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	STEL	15 ppm	79 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Methanol	STEL	250 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	200 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Methanol	STEL	250 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	TWA	200 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Methanol	STEL	250 ppm	328 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	200 ppm	262 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
1,3,5-Trimethylbenzene	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,3,5-Trimethylbenzene	TWA	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,3,5-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Allyl glycidyl ether	TWA	1 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Allyl glycidyl ether	TWA	1 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Allyl glycidyl ether	STEL	10 ppm 47 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	5 ppm 23 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Phenol	TWA	5 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Phenol	TWA	5 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Phenol	TWA	5 ppm 19 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
2-Ethylhexanoic acid - Vapor and aerosol, inhalable.	TWA	5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
2-Ethylhexanoic acid - Inhalable fraction and vapor.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Vinyl chloride	TWA	1 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Vinyl chloride	TWA	1 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Vinyl chloride	TWA	1 ppm 2.6 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

### Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Xylene (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEI (03 2013)
Ethylbenzene (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEI (02 2014)

**Appropriate Engineering Controls** Mechanical ventilation or local exhaust ventilation may be required. Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

**Individual protection measures, such as personal protective equipment**

- General information:** Use personal protective equipment as required.
- Eye/face protection:** Wear goggles/face shield.
- Skin Protection**
- Hand Protection:** Use suitable protective gloves if risk of skin contact.
- Other:** Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
- Respiratory Protection:** If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.
- Hygiene measures:** Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

**9. Physical and chemical properties**

**Appearance**

- Physical state:** solid
- Form:** Paste
- Color:** White
- Odor:** Mild
- Odor threshold:** No data available.
- pH:** No data available.
- Melting point/freezing point:** No data available.
- Initial boiling point and boiling range:** No data available.
- Flash Point:** > 93 °C > 199 °F (Setaflash Closed Cup)
- Evaporation rate:** Slower than n-Butyl Acetate
- Flammability (solid, gas):** No
- Upper/lower limit on flammability or explosive limits**
- Flammability limit - upper (%):** No data available.
- Flammability limit - lower (%):** No data available.
- Explosive limit - upper (%):** No data available.
- Explosive limit - lower (%):** No data available.
- Vapor pressure:** No data available.

---

<b>Vapor density:</b>	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
<b>Relative density:</b>	1.32
<b>Solubility(ies)</b>	
<b>Solubility in water:</b>	Insoluble in water
<b>Solubility (other):</b>	No data available.
<b>Partition coefficient (n-octanol/water):</b>	No data available.
<b>Auto-ignition temperature:</b>	No data available.
<b>Decomposition temperature:</b>	No data available.
<b>Viscosity:</b>	No data available.

## 10. Stability and reactivity

<b>Reactivity:</b>	No data available.
<b>Chemical Stability:</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions:</b>	No data available.
<b>Conditions to avoid:</b>	Avoid heat or contamination.
<b>Incompatible Materials:</b>	Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.
<b>Hazardous Decomposition Products:</b>	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation:</b>	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
<b>Skin Contact:</b>	Causes mild skin irritation. May cause an allergic skin reaction.
<b>Eye contact:</b>	Eye contact is possible and should be avoided.
<b>Ingestion:</b>	May be ingested by accident. Ingestion may cause irritation and malaise.

### Symptoms related to the physical, chemical and toxicological characteristics

<b>Inhalation:</b>	No data available.
<b>Skin Contact:</b>	No data available.
<b>Eye contact:</b>	No data available.
<b>Ingestion:</b>	No data available.



---

## Information on toxicological effects

### Acute toxicity (list all possible routes of exposure)

#### Oral

**Product:** Not classified for acute toxicity based on available data.

#### Specified substance(s):

Titanium dioxide LD 50 (Rat): > 5,000 mg/kg

Petroleum distillates LD 50 (Rat): > 5,000 mg/kg

Aliphatic naphtha LD 50 (Rat): > 5,000 mg/kg

Xylene LD 50 (Rat): 3,523 mg/kg

Isophorone Diisocyanate LD 50 (Rat): 4,814 mg/kg

Aluminum oxide LD 50 (Rat): > 10,000 mg/kg

Ethylbenzene LD 50 (Rat): 3,500 mg/kg

Hydrotreated heavy naphthenic distillate LD 50 (Rat): > 5,000 mg/kg

Nonane LD 50 (Rat): > 5,000 mg/kg

Iodopropynyl butylcarbamate LD 50 (Rat): 1.1 g/kg

#### Dermal

**Product:** Not classified for acute toxicity based on available data.

**Specified substance(s):**

Petroleum distillates LD 50 (Rabbit): &gt; 2,000 mg/kg

Aliphatic naphtha LD 50 (Rabbit): &gt; 2,000 mg/kg

Xylene LD 50 (Rabbit): 12,126 mg/kg

Isophorone Diisocyanate LD 50 (Rat): &gt; 7,000 mg/kg

Ethylbenzene LD 50 (Rabbit): 17,800 mg/kg

Hydrotreated heavy  
naphthenic distillate LD 50 (Rabbit): > 5,000 mg/kg

Nonane LD 50 (Rabbit): &gt; 2,000 mg/kg

Iodopropynyl  
butylcarbamate LD 50 (Rabbit): > 2,000 mg/kg**Inhalation****Product:**

ATEmix: 12.34 mg/l

**Repeated dose toxicity****Product:**

No data available.

**Skin Corrosion/Irritation****Product:**

No data available.

**Specified substance(s):**

Titanium dioxide	in vivo (Rabbit): Not irritant Experimental result, Supporting study
Petroleum distillates	in vivo (Rabbit): Irritating Experimental result, Key study
Aliphatic naphtha	in vivo (Rabbit): Irritating Experimental result, Key study
Xylene	in vivo (Rabbit): Moderate irritant Experimental result, Weight of Evidence study
Aluminum oxide	in vivo (Rabbit): Not irritant Experimental result, Key study
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit): Not irritant Experimental result, Key study
Nonane	in vivo (Rabbit): Irritating Read-across based on grouping of substances (category approach), Key study

**Serious Eye Damage/Eye Irritation**

**Product:** No data available.

**Specified substance(s):**

Titanium dioxide	Rabbit, 24 hrs: Not irritating
Petroleum distillates	Rabbit, 24 - 72 hrs: Not irritating
Aliphatic naphtha	Rabbit, 24 - 72 hrs: Not irritating
Xylene	Rabbit, 24 hrs: Moderately irritating
Aluminum oxide	Rabbit, 24 hrs: Not irritating
Ethylbenzene	Rabbit, 7 d: Slightly irritating
Hydrotreated heavy naphthenic distillate	Rabbit, 24 hrs: Not irritating
Nonane	Rabbit, 24 - 72 hrs: Not irritating

**Respiratory or Skin Sensitization**

**Product:** May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
May cause sensitization by inhalation.

**Carcinogenicity**

**Product:** No data available.

---

**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

Titanium dioxide	Overall evaluation: Possibly carcinogenic to humans.
Ethylbenzene	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

**US. National Toxicology Program (NTP) Report on Carcinogens:**

Hydrotreated heavy naphthenic distillate	Known To Be Human Carcinogen.
------------------------------------------	-------------------------------

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):**

Polyvinyl chloride	Cancer
--------------------	--------

**Germ Cell Mutagenicity**

<b>In vitro</b> Product:	No data available.
-----------------------------	--------------------

<b>In vivo</b> Product:	No data available.
----------------------------	--------------------

<b>Reproductive toxicity</b> Product:	No data available.
------------------------------------------	--------------------

<b>Specific Target Organ Toxicity - Single Exposure</b> Product:	No data available.
---------------------------------------------------------------------	--------------------

<b>Specific Target Organ Toxicity - Repeated Exposure</b> Product:	No data available.
-----------------------------------------------------------------------	--------------------

<b>Aspiration Hazard</b> Product:	No data available.
--------------------------------------	--------------------

<b>Other effects:</b>	No data available.
-----------------------	--------------------

<b>12. Ecological information</b>
-----------------------------------

**Ecotoxicity:**

**Acute hazards to the aquatic environment:**

**Fish**

**Product:** No data available.

**Specified substance(s):**

Petroleum distillates	LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 96 h): 2.9 mg/l Mortality
Xylene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13.41 mg/l Mortality
Ethylbenzene	LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 96 h): 4.2 mg/l Mortality
Iodopropynyl butylcarbamate	LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 96 h): 0.05 - 0.089 mg/l Mortality

**Aquatic Invertebrates**

**Product:** No data available.

**Specified substance(s):**

Titanium dioxide	EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication
Ethylbenzene	EC 50 (Water flea (Daphnia magna), 48 h): 1.37 - 4.4 mg/l Intoxication

**Chronic hazards to the aquatic environment:**

**Fish**

**Product:** No data available.

**Specified substance(s):**

Aliphatic naphtha	NOAEL (Oncorhynchus mykiss, 28 d): 0.098 mg/l QSAR QSAR, Key study
Hydrotreated heavy naphthenic distillate	NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR QSAR, Supporting study

**Aquatic Invertebrates**

**Product:** No data available.

**Toxicity to Aquatic Plants**

**Product:** No data available.

**Persistence and Degradability**

**Biodegradation**

**Product:** No data available.

**BOD/COD Ratio**

**Product:** No data available.

**Bioaccumulative potential**

**Bioconcentration Factor (BCF)**

**Product:** No data available.

**Partition Coefficient n-octanol / water (log Kow)**

**Product:** No data available.

**Specified substance(s):**

Xylene Log Kow: 3.12 - 3.20

Ethylbenzene Log Kow: 3.15

Nonane Log Kow: 5.46

**Mobility in soil:** No data available.

**Other adverse effects:** Harmful to aquatic organisms.

**13. Disposal considerations**

**Disposal instructions:** Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

**Contaminated Packaging:** No data available.

**14. Transport information**

**TDG:**

Not Regulated

**CFR / DOT:**

Not Regulated

**IMDG:**

Not Regulated

**15. Regulatory information**

**US Federal Regulations**

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

None present or none present in regulated quantities.

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Polyvinyl chloride	Blood Liver Cancer Flammability Central nervous system
Benzene	Blood respiratory tract irritation Central nervous system Flammability Cancer Skin Aspiration Eye
Crystalline Silica (Quartz)/ Silica Sand	kidney effects lung effects immune system effects Cancer
Vinyl chloride	Blood Liver Flammability Central nervous system Cancer

**CERCLA Hazardous Substance List (40 CFR 302.4):**

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Ethylbenzene	1000 lbs.
Nonane	100 lbs.
Toluene	1000 lbs.
Cumene	5000 lbs.
Benzene	10 lbs.
Naphthalene	100 lbs.
Methanol	5000 lbs.
Phenol	1000 lbs.
Vinyl chloride	1 lbs.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories**

- Delayed (Chronic) Health Hazard
- Immediate (Acute) Health Hazards
- Respiratory or Skin Sensitization
- Carcinogenicity

**SARA 302 Extremely Hazardous Substance**

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500 lbs.	500 lbs.
Phenol	1000 lbs.	- - -

**SARA 304 Emergency Release Notification**

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	100 lbs.
Isophorone Diisocyanate	
Ethylbenzene	1000 lbs.
Nonane	100 lbs.
Toluene	1000 lbs.
Cumene	5000 lbs.
Benzene	10 lbs.
Naphthalene	100 lbs.
Methanol	5000 lbs.
Phenol	1000 lbs.
Vinyl chloride	1 lbs.

**SARA 311/312 Hazardous Chemical**

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Isophorone Diisocyanate	500lbs
Phenol	500lbs
Calcium Carbonate (Limestone)	10000 lbs
Polyvinyl chloride	10000 lbs
Titanium dioxide	10000 lbs
Petroleum distillates	10000 lbs
Aliphatic naphtha	10000 lbs
Calcium oxide	10000 lbs
Xylene	10000 lbs
Aluminum oxide	10000 lbs
Ethylbenzene	10000 lbs
Hydrotreated heavy naphthenic distillate	10000 lbs
Nonane	10000 lbs
Iodopropynyl butylcarbamate	10000 lbs

**SARA 313 (TRI Reporting)**

<u>Chemical Identity</u>
Xylene
Ethylbenzene

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Vinyl chloride	lbs

**Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)**

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Xylene	Reportable quantity: lbs.

**US State Regulations**



## US. California Proposition 65



### WARNING

Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## US. New Jersey Worker and Community Right-to-Know Act

### Chemical Identity

Calcium Carbonate (Limestone)  
Polyvinyl chloride  
Titanium dioxide  
Petroleum distillates  
Aliphatic naphtha  
Calcium oxide  
Xylene  
Ethylbenzene  
Hydrotreated heavy naphthenic distillate

## US. Massachusetts RTK - Substance List

### Chemical Identity

Calcium Carbonate (Limestone)  
Titanium dioxide  
Petroleum distillates  
Aliphatic naphtha  
Xylene  
Isophorone Diisocyanate  
Benzene  
Crystalline Silica (Quartz)/ Silica Sand  
Phenol

## US. Pennsylvania RTK - Hazardous Substances

### Chemical Identity

Calcium Carbonate (Limestone)  
Titanium dioxide  
Petroleum distillates  
Aliphatic naphtha  
Calcium oxide  
Xylene

## US. Rhode Island RTK

### Chemical Identity

Calcium Carbonate (Limestone)  
Polyvinyl chloride  
Titanium dioxide  
Petroleum distillates  
Aliphatic naphtha  
Xylene

## International regulations

### Montreal protocol

Not applicable

### Stockholm convention

Not applicable

**Rotterdam convention**

Not applicable

**Kyoto protocol**

Not applicable

**VOC:**

Regulatory VOC (less water and  
exempt solvent) : 108 g/l

VOC Method 310 : 8.16 %

---

**Inventory Status:**

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	One or more components in this product are not listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	One or more components in this product are not listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	One or more components in this product are not listed on or exempt from the Inventory.
Ontario Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Mexico INSQ:	One or more components in this product are not listed on or exempt from the Inventory.
Taiwan Chemical Substance Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	One or more components in this product are not listed on or exempt from the Inventory.

---

<b>16. Other information, including date of preparation or last revision</b>
------------------------------------------------------------------------------

**Revision Date:** 03/28/2019

**Version #:** 1.1

**Further Information:** No data available.

**Disclaimer:** For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.