

SAFETY DATA SHEET

1. Identification

Material name: Tremco PUMA TC Gray - 6 GAL Material: 470718 805

Recommended use and restriction on use

Recommended use: Coatings Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants 3735 Green Road Beachwood OH 44122 US

Contact person:
Telephone:
Emergency telephone number:

EH&S Department 216-292-5000 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Category 2

Health Hazards

Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2A
Skin sensitizer	Category 1

Unknown toxicity - Health

Acute toxicity, oral	26.3 %
Acute toxicity, dermal	36.2 %
Acute toxicity, inhalation, vapor	67.8 %
Acute toxicity, inhalation, dust or mist	100 %

Danger

Label Elements

Hazard Symbol:



Signal Word:

_



Hazard Statement:	Highly flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction.
Precautionary Statements	
Prevention:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting/] equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing must not be allowed out of the workplace.
Response:	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see this label). Wash contaminated clothing before reuse. In case of fire: Use to extinguish.
Storage:	Store in well-ventilated place. Keep cool.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Hazard(s) not otherwise classified (HNOC):	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Methyl methacrylate	80-62-6	30 - 60%
2-Propenoic acid, 2-ethylhexyl ester	103-11-7	15 - 40%
Barium sulfate	7727-43-7	7 - 13%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:

Call a POISON CENTRE/doctor/ if you feel unwell. Rinse mouth.

Inhalation:

Move to fresh air.



Skin Contact:	Take off immediately all contaminated clothing. Get medical attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.	
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.	
Most important symptoms/effects	s, acute and delayed	
Symptoms:	Respiratory tract irritation. Prolonged or repeated contact with skin may cause redness, itching, irritation and eczema/chapping.	
Indication of immediate medical att	ention and special treatment needed	
Treatment:	Get medical attention if symptoms occur.	
5. Fire-fighting measures		
General Fire Hazards:	Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.	
Suitable (and unsuitable) extinguishing media		
Suitable extinguishing media:	Use fire-extinguishing media appropriate for surrounding materials.	
Unsuitable extinguishing media:	Avoid water in straight hose stream; will scatter and spread fire.	
Specific hazards arising from the chemical:	Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of vapors or gases to explosive concentrations.	
Special protective equipment and	precautions for firefighters	
Special fire fighting procedures:	No data available.	
Special protective equipment for fire-fighters:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.	
6. Accidental release measures		
Personal precautions, protective equipment and emergency procedures:	Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.	



Methods and material for containment and cleaning up:	Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.
Notification Procedures:	In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.
Environmental Precautions:	Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.
7. Handling and storage	
Precautions for safe handling:	Avoid contact with eyes. Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Avoid contact with skin. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities:	Store in a well-ventilated place. Store in a cool place.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Туре	Exposure Limit Values	Source
Methyl methacrylate	TWA	50 ppm	US. ACGIH Threshold Limit Values (2011)
	STEL	100 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 410 mg/r	n3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Barium sulfate - Inhalable fraction.	TWA	5 mg/r	n3 US. ACGIH Threshold Limit Values (02 2014)
Barium sulfate - Total dust.	PEL	15 mg/r	n3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Barium sulfate - Respirable fraction.	PEL	5 mg/r	n3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Barium sulfate - Total dust.	TWA	15 mg/r	n3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
Barium sulfate - Respirable fraction.	TWA	5 mg/r	n3 US. OSHA Table Z-3 (29 CFR 1910.1000) (03 2016)
	TWA	15 millions particles p cubic foot	per 2016)
Barium sulfate - Total dust.	TWA	50 millions particles p cubic foot	per 2016)



Chemical name	Туре	Exposure Limi	t Values	Source
Methyl methacrylate	TWA	50 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	STEL	100 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Methyl methacrylate	TWA	50 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Methyl methacrylate	TWA	50 ppm	205 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Barium sulfate - Total dust.	TWA		10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Barium sulfate - Respirable fraction.	TWA		3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Barium sulfate	TWA		10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Barium sulfate - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Barium sulfate - Respirable dust.	TWA		5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

General information:	Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof ventilation equipment.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.



Hygiene measures: Avoid contact with eyes. Observe good industrial hygiene practices. When using do not smoke. Wash contaminated clothing before reuse. Avoid contact with skin. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

_

Appearance	
Physical state:	liquid
Form:	liquid
Color:	Gray
Odor:	Mild petroleum/solvent
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	100.3 °C 212.5 °F
Flash Point:	11.5 °C 52.7 °F(Closed Cup)
Evaporation rate:	Slower than Ether
Flammability (solid, gas):	No
Upper/lower limit on flammability or explos	sive limits
Flammability limit - upper (%):	12.5 %(V)
Flammability limit - lower (%):	2.1 %(V)
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.1
Solubility(ies)	
Solubility in water:	Practically Insoluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Heat, sparks, flames.



Incompatible Materials:	Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases.	
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.	
11. Toxicological information		

Information on likely routes of exposure Inhalation: In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.		
Skin Contact:	Causes skin irritation. May cause an allergic skin reaction.	
Eye contact:	Causes serious eye irritation.	
Ingestion:	May be ingested by accident. Ingestion may cause irritation and mala	ise.
Symptoms related to the physica	Symptoms related to the physical, chemical and toxicological characteristics	
Inhalation:	No data available.	
Skin Contact:	No data available.	
Eye contact:	No data available.	
Ingestion:	No data available.	
Information on toxicological effects		
Acute toxicity (list all possible routes of exposure)		
Oral Product:	ATEmix: 15,790.31 mg/kg	
Dermal Product:	ATEmix: 11,706.42 mg/kg	
Inhalation Product:	Not classified for acute toxicity based on available data.	
Specified substance(s): Methyl methacrylate	LC 50 (Rat): 29.8 mg/l	
Repeated dose toxicity Product:	No data available.	
Skin Corrosion/Irritation Product:	No data available.	7/14



Specified substance(s): Methyl methacrylate	in vivo (Rabbit): irritating after 4/24h occluded exposure Experimental result, Weight of Evidence study	
2-Propenoic acid, 2- ethylhexyl ester	in vivo (Rabbit): Irritating Experimental result, Key study	
Barium sulfate	validated "in vitro" test method Not irritant Read-across from supporting substance (structural analogue or surrogate), Key study	
Serious Eye Damage/Eye Irritatio Product: Specified substance(s):	n No data available.	
2-Propenoic acid, 2- ethylhexyl ester	Rabbit, 24 - 48 hrs: Not irritating	
Barium sulfate	Rabbit, 24 - 72 hrs: Not irritating	
Respiratory or Skin Sensitization Product:	No data available.	
Carcinogenicity Product:	No data available.	
	IARC Monographs on the Evaluation of Carcinogenic Risks to Humans: No carcinogenic components identified	
US. National Toxicology Program No carcinogenic components		
US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): No carcinogenic components identified		
Germ Cell Mutagenicity		
In vitro Product:	No data available.	
In vivo Product:	No data available.	
Reproductive toxicity Product:	No data available.	
Specific Target Organ Toxicity - S Product:	Single Exposure No data available.	
Specific Target Organ Toxicity - Product:	Repeated Exposure No data available. 8/14	



Aspiration Hazard Product:

Other effects:	No data available.	
10 Feelewisel information		
12. Ecological information		
Ecotoxicity:		
Acute hazards to the aquatic e	environment:	
Fish Product:	No data available.	
Specified substance(s): Methyl methacrylate	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 130 mg/l Mortality	
Aquatic Invertebrates Product:	No data available.	
Specified substance(s): Barium sulfate	EC 50 (Tubificid worm (Tubifex tubifex), 24 h): 34.2 - 57.71 mg/l Intoxication	
Chronic hazards to the aquation	Chronic hazards to the aquatic environment:	
Fish Product:	No data available.	
Specified substance(s): Barium sulfate	LC 1 (Oncorhynchus mykiss, 28 d): 2,813 μg/l Experimental result, Supporting study LC 50 (Oncorhynchus mykiss, 28 d): 42,700 μg/l Experimental result, Supporting study LC 10 (Oncorhynchus mykiss, 28 d): 9,543 μg/l Experimental result, Supporting study	
Aquatic Invertebrates Product:	No data available.	
Toxicity to Aquatic Plants Product:	No data available.	
Persistence and Degradability		
Biodegradation Product:	No data available.	

No data available.



BOD/COD Ratio Product:	No data available.
Bioaccumulative potential	
Bioconcentration Factor (BCF Product:) No data available.
Partition Coefficient n-octanol / wa Product:	ter (log Kow) No data available.
Specified substance(s): Methyl methacrylate	Log Kow: 1.38
Mobility in soil:	No data available.
Other adverse effects:	No data available.
13. Disposal considerations	
Disposal instructions:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Contaminated Packaging:	No data available.
14. Transport information	

TDG:

UN1866, RESIN SOLUTION, 3, PG II

CFR / DOT:

UN1866, Resin solution, 3, PG II

IMDG:

UN1866, RESIN SOLUTION, 3, PG II

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.



US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity

Methyl methacrylate	100
Barium sulfate	100

Reportable quantity 1000 lbs. 1000 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

SARA 304 Emergency Release Notification

Chemical Identity	Reportable quantity
Methyl methacrylate	1000 lbs.
Barium sulfate	1000 lbs.

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Methyl methacrylate	10000 lbs
2-Propenoic acid, 2-	10000 lbs
ethylhexyl ester	
Barium sulfate	10000 lbs

SARA 313 (TRI Reporting)

Chemical Identity

Methyl methacrylate

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65

No ingredient regulated by CA Prop 65 present.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Methyl methacrylate 2-Propenoic acid, 2-ethylhexyl ester Barium sulfate



US. Massachusetts RTK - Substance List

<u>Chemical Identity</u> Methyl methacrylate 2-Propenoic acid, 2-ethylhexyl ester Barium sulfate

US. Pennsylvania RTK - Hazardous Substances

<u>Chemical Identity</u> Methyl methacrylate 2-Propenoic acid, 2-ethylhexyl ester Barium sulfate

US. Rhode Island RTK

Chemical Identity

Methyl methacrylate

International regulations

Montreal protocol

not applicable

Stockholm convention

not applicable

Rotterdam convention

not applicable

Kyoto protocol

not applicable

VOC: When appropriately mixed with the other part, product has a VOC less water and exempt solvent of: 0 g/l

Regulatory VOC (less water and
exempt solvent): 0 g/l 0 g/lVOC Method 310: 0.00 %



Inventory Status:

Australia AICS:

Canada DSL Inventory List:

EINECS, ELINCS or NLP:

Japan (ENCS) List:

China Inv. Existing Chemical Substances:

Korea Existing Chemicals Inv. (KECI):

Canada NDSL Inventory:

Philippines PICCS:

US TSCA Inventory:

New Zealand Inventory of Chemicals:

Japan ISHL Listing:

Japan Pharmacopoeia Listing:

All components in this product are listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

All components in this product are listed on or exempt from the Inventory.

All components in this product are listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

All components in this product are listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

One or more components in this product are not listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date:	02/17/2017
Version #:	2.0
Further Information:	No data available.



Disclaimer:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.