

AlphaGuard[®] PUMA Catalyst

Powder reactive catalyst

DESCRIPTION:	AlphaGuard PUMA Catalyst is a low odor, powder reactive agent used to catalyze AlphaGuard PUMA liquid products.
BASIC USES:	AlphaGuard PUMA Catalyst is mixed with AlphaGuard PUMA liquid products to initiate the curing process.
PACKAGING:	55 lbs (25 kg) bag packaged in a 6 gallon (22.7 L) container 22 lbs (10 kg) bag packaged in a 2 gallon (7.6 L) container
COLOR:	White
GRADE:	Powder
POT LIFE:	10 - 15 minutes. <i>*Pot life dependent on ambient, substrate, and product temperature and the amount of AlphaGuard PUMA Catalyst used.</i>
STORAGE LIFE:	<p>12 months in unopened containers. Recommended storage conditions are indoors in a ventilated, dry area removed from heat, open flame, ignition sources, and direct sunlight. Storage temperatures should range from 60-70°F (15-21°C) and must not exceed 110°F (43°C).</p> <p>On the job site, materials should remain on the pallet until use and be stored in a shaded, ventilated area. Materials should be covered with a light-colored, reflective tarp for protection against the elements. Allow for adequate air flow inside the pallets.</p> <p>Shelf life could be effected if the product is not stored properly.</p>
APPLICATION:	<p>Usage: AlphaGuard PUMA Catalyst is used in a range of 1 - 7% of the weight of the AlphaGuard PUMA liquid product selected. The amount of AlphaGuard PUMA Catalyst required is based on the type and amount of liquid product used as well as the ambient temperature.</p> <p>Mixing: Use a heavy duty power drill with Jiffy Mixer attachment. Cordless drills are not recommended and may not properly mix the materials.</p> <p>Mix the AlphaGuard PUMA liquid product to achieve a uniform distribution and appearance of the product. Once properly mixed, AlphaGuard PUMA liquid products can be poured off in smaller quantities into a second container. Add the appropriate amount of AlphaGuard PUMA Catalyst to the selected amount of liquid product and mix thoroughly until powder catalyst is completely dissolved. Catalyze only the amount of liquid product intended to be used within the expected pot life. The amount of AlphaGuard PUMA Catalyst required is based on the type and amount of liquid product used as well as the ambient temperature. Refer mixing charts located on individual product data sheets for specific recommendations and requirements.</p>
PRECAUTIONS:	Use Tremco AlphaGuard PUMA with adequate ventilation. If the product is applied in enclosed areas without natural ventilation, forced ventilation must be arranged. Avoid strong concentration of vapor as well as direct contact with skin or eyes. Users must read container labels and Material Safety Data Sheets for health and safety precautions prior to use.

AlphaGuard® PUMA Catalyst

MAINTENANCE:

Your local Tremco Roofing Representative can provide you with effective maintenance procedures which may vary, depending upon specific conditions. Periodic inspections, early repairs and preventative maintenance are all part of a sound roof program.

TECHNICAL SERVICES:

Your local Tremco Representative, working with the Technical Service Staff, can help analyze conditions and needs to develop recommendations for special applications. The services of the Tremco Research Center, which has earned a unique reputation in weatherproofing technology, complement and extend the services of the Tremco Technical Service Staff.



7057
7/31/18

www.tremcoroofing.com
3735 Green Road
Beachwood, Ohio 44122
1.800.852.6013



50 Beth Neelson Drive
Toronto, Ontario M4H 1M6
1.800.668.9879

AlphaGuard is a U.S. registered trademark of Tremco Incorporated

The information provided on this data sheet is effective as of July 2018 and supersedes all previous data concerning this product and its application.

The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Tremco DOES NOT MAKE NOR DOES IT AUTHORIZE ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO TREMCO'S PRODUCT SAMPLE. Buyer and user accept the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handling, storage or use of the product, whether or not it is handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCES SHALL TREMCO BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY. IN ALL CASES, TREMCO'S LIABILITY IS LIMITED, AT TREMCO'S OPTION, TO THE REPLACEMENT OF GOODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING.