

# SAFETY DATA SHEET

## 1. Identification

**Material name:** ALUMINUM MASTIC 3 GL  
**Material:** 360700 803

**Recommended use and restriction on use**

**Recommended use:** Coatings  
**Restrictions on use:** Not known.

**Manufacturer/Importer/Supplier/Distributor Information**

Tremco Incorporated  
3735 Green Road  
BEACHWOOD OH 44122  
US

<b>Contact person:</b>	EH&S Department
<b>Telephone:</b>	216-292-5000
<b>Emergency telephone number:</b>	1-800-424-9300 (US); 1-613-996-6666 (Canada)

## 2. Hazard(s) identification

**Hazard Classification**

**Physical Hazards**

Flammable liquids	Category 3
-------------------	------------

**Health Hazards**

Acute toxicity (Inhalation - dust and mist)	Category 4
Serious Eye Damage/Eye Irritation	Category 2A
Germ Cell Mutagenicity	Category 1B
Carcinogenicity	Category 1B

**Unknown toxicity - Health**

Acute toxicity, oral	38.04 %
Acute toxicity, dermal	60.78 %
Acute toxicity, inhalation, vapor	100 %
Acute toxicity, inhalation, dust or mist	88.32 %

**Environmental Hazards**

Acute hazards to the aquatic environment	Category 2
--	------------

**Unknown toxicity - Environment**

Acute hazards to the aquatic environment	88.32 %
Chronic hazards to the aquatic environment	100 %

**Label Elements**

**Hazard Symbol:**



- Signal Word:** Danger
- Hazard Statement:** Flammable liquid and vapor.  
Harmful if inhaled.  
Causes serious eye irritation.  
May cause genetic defects.  
May cause cancer.  
Toxic to aquatic life.
- Precautionary Statement:**
- Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wash thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
- Response:** IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a POISON CENTER/doctor if you feel unwell. In case of fire: Use ... to extinguish.
- Storage:** Store in well-ventilated place. Keep cool. Store locked up.
- Disposal:** Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
- Other hazards which do not result in GHS classification:** Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

### 3. Composition/information on ingredients

#### Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Asphalt	8052-42-4	30 - 60%
Stoddard solvent (Mineral Spirits)	8052-41-3	15 - 40%

Talc	14807-96-6	10 - 30%
Aluminum	7429-90-5	10 - 30%
Magnesite	546-93-0	5 - 10%
Fibrous Glass	65997-17-3	3 - 7%
Cellulose	9004-34-6	3 - 7%
Silicon dioxide, amorphous	112945-52-5	0.1 - 1%

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

#### 4. First-aid measures

**Ingestion:** Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.

**Inhalation:** Move to fresh air.

**Skin Contact:** Wash skin thoroughly with soap and water. Get medical attention if symptoms occur. Take off immediately all contaminated clothing.

**Eye contact:** Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.

#### Most important symptoms/effects, acute and delayed

**Symptoms:** Respiratory tract irritation.

#### Indication of immediate medical attention and special treatment needed

**Treatment:** Symptoms may be delayed.

#### 5. Fire-fighting measures

**General Fire Hazards:** Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

#### Suitable (and unsuitable) extinguishing media

**Suitable extinguishing media:** Use fire-extinguishing media appropriate for surrounding materials.

**Unsuitable extinguishing media:** Avoid water in straight hose stream; will scatter and spread fire.

**Specific hazards arising from the chemical:** Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of vapors or gases to explosive concentrations.

#### Special protective equipment and precautions for firefighters

**Special fire fighting procedures:** No data available.

**Special protective equipment for fire-fighters:** Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

**6. Accidental release measures**

- Personal precautions, protective equipment and emergency procedures:** Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind.
- Methods and material for containment and cleaning up:** Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.
- Notification Procedures:** In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.
- Environmental Precautions:** Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

**7. Handling and storage**

- Precautions for safe handling:** Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with eyes. Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Take precautionary measures against static discharges. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
- Conditions for safe storage, including any incompatibilities:** Store locked up. Store in a well-ventilated place. Store in a cool place.

**8. Exposure controls/personal protection**

**Control Parameters**

**Occupational Exposure Limits**

Chemical Identity	type	Exposure Limit Values	Source
Asphalt - Inhalable fraction. - as benzene solubles	TWA	0.5 mg/m <sup>3</sup>	US. ACGIH Threshold Limit Values (2011)
Stoddard solvent (Mineral Spirits)	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	500 ppm      2,900 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Talc - Respirable fraction.	TWA	2 mg/m <sup>3</sup>	US. ACGIH Threshold Limit Values (2011)
Talc	TWA	20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Talc - Respirable.	TWA	2.4 millions of particles	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

		per cubic foot of air	
	TWA	0.1 mg/m <sup>3</sup>	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Talc - Total dust.	TWA	0.3 mg/m <sup>3</sup>	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Aluminum - Respirable fraction.	TWA	1 mg/m <sup>3</sup>	US. ACGIH Threshold Limit Values (2011)
Aluminum - Respirable dust. - as Al	PEL	5 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Aluminum - Total dust. - as Al	PEL	15 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Magnesite - Total dust.	PEL	15 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Magnesite - Respirable fraction.	PEL	5 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Fibrous Glass - Inhalable fraction.	TWA	5 mg/m <sup>3</sup>	US. ACGIH Threshold Limit Values (03 2014)
Fibrous Glass - Fiber.	TWA	1 fibers/cm <sup>3</sup>	US. ACGIH Threshold Limit Values (03 2014)
	TWA	1 fibers/cm <sup>3</sup>	US. ACGIH Threshold Limit Values (03 2014)
	TWA	1 fibers/cm <sup>3</sup>	US. ACGIH Threshold Limit Values (03 2014)
	TWA	1 fibers/cm <sup>3</sup>	US. ACGIH Threshold Limit Values (03 2014)
	TWA	1 fibers/cm <sup>3</sup>	US. ACGIH Threshold Limit Values (03 2014)
	TWA	0.2 fibers/cm <sup>3</sup>	US. ACGIH Threshold Limit Values (03 2014)
Cellulose	TWA	10 mg/m <sup>3</sup>	US. ACGIH Threshold Limit Values (2011)
Cellulose - Total dust.	PEL	15 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Cellulose - Respirable fraction.	PEL	5 mg/m <sup>3</sup>	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Silicon dioxide, amorphous	TWA	20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA	0.8 mg/m <sup>3</sup>	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)

<b>Chemical name</b>	<b>type</b>	<b>Exposure Limit Values</b>	<b>Source</b>
Asphalt - Aerosol, inhalable. - as benzene solubles	TWA	0.5 mg/m <sup>3</sup>	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Asphalt - Inhalable fraction. - as benzene solubles	TWAEV	0.5 mg/m <sup>3</sup>	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Asphalt - Fume.	TWA	5 mg/m <sup>3</sup>	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Stoddard solvent (Mineral Spirits)	STEL	580 mg/m <sup>3</sup>	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	290 mg/m <sup>3</sup>	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Stoddard solvent (Mineral Spirits)	TWAEV	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Stoddard solvent (Mineral Spirits)	TWA	100 ppm 525 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Talc - Respirable.	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Talc - Respirable particles.	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Talc	TWAEV	2 fibers/mL	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Talc - Respirable dust.	TWA	3 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Aluminum - Respirable.	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Aluminum - Respirable fraction.	TWAEV	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Aluminum	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Aluminum - Welding fume. - as Al	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Aluminum - as Al	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Magnesite - Total dust.	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Magnesite - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Fibrous Glass - Fiber.	TWA	0.2 fibers/cm3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	1 fibers/cm3	Canada. British Columbia OELs. (Occupational Exposure Limits for

			Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Fibrous Glass - Inhalable fibers.	TWA	5 mg/m <sup>3</sup>	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Fibrous Glass - Inhalable	TWAEV	5 mg/m <sup>3</sup>	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Fibrous Glass - Respirable fibers.	TWAEV	1 fibers/mL	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Fibrous Glass - Fiber.	TWAEV	0.2 fibers/mL	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Fibrous Glass - Total dust.	TWA	10 mg/m <sup>3</sup>	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Fibrous Glass - Fiber.	TWA	1 fibres/cm <sup>3</sup> (non-asbestos fibres) -- size restrictions apply	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	TWA	2 fibres/cm <sup>3</sup> (non-asbestos fibres) -- size restrictions apply	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Cellulose - Respirable fraction.	TWA	3 mg/m <sup>3</sup>	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Cellulose - Total dust.	TWA	10 mg/m <sup>3</sup>	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Cellulose	TWAEV	10 mg/m <sup>3</sup>	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Cellulose - Total dust.	TWA	10 mg/m <sup>3</sup>	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)



**Appropriate Engineering Controls**                      Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

**Individual protection measures, such as personal protective equipment**

- General information:**                      Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Use explosion-proof ventilation equipment.
- Eye/face protection:**                      Wear safety glasses with side shields (or goggles).
- Skin Protection**
- Hand Protection:**                      Use suitable protective gloves if risk of skin contact.
- Other:**                                      Wear suitable protective clothing.
- Respiratory Protection:**                      In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.
- Hygiene measures:**                      Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Avoid contact with eyes. When using do not smoke.

**9. Physical and chemical properties**

**Appearance**

- Physical state:**                              liquid
- Form:**    liquid
- Color:**    Gray
- Odor:**    Mild petroleum/solvent
- Odor threshold:**                              No data available.
- pH:**    No data available.
- Melting point/freezing point:**                      No data available.
- Initial boiling point and boiling range:**                      149 °C 300 °F
- Flash Point:**                                      41 °C 105 °F(Tag closed cup)
- Evaporation rate:**                              Slower than Ether
- Flammability (solid, gas):**                      No
- Upper/lower limit on flammability or explosive limits**
- Flammability limit - upper (%):**                      6.7 %(V)
- Flammability limit - lower (%):**                      0.9 %(V)
- Explosive limit - upper (%):**                      No data available.
- Explosive limit - lower (%):**                      No data available.
- Vapor pressure:**                              2.1 mmHg (20 °C 68 °F)
- Vapor density:**                              Vapors are heavier than air and may travel along the floor and in the bottom of containers.
- Relative density:**                              1.13
- Solubility(ies)**

<b>Solubility in water:</b>	Practically Insoluble
<b>Solubility (other):</b>	No data available.
<b>Partition coefficient (n-octanol/water):</b>	No data available.
<b>Auto-ignition temperature:</b>	No data available.
<b>Decomposition temperature:</b>	No data available.
<b>Viscosity:</b>	No data available.

**10. Stability and reactivity**

<b>Reactivity:</b>	No data available.
<b>Chemical Stability:</b>	Material is stable under normal conditions.
<b>Possibility of Hazardous Reactions:</b>	No data available.
<b>Conditions to Avoid:</b>	Heat, sparks, flames.
<b>Incompatible Materials:</b>	Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases.
<b>Hazardous Decomposition Products:</b>	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

**11. Toxicological information****Information on likely routes of exposure**

<b>Ingestion:</b>	May be ingested by accident. Ingestion may cause irritation and malaise.
<b>Inhalation:</b>	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
<b>Skin Contact:</b>	May be harmful in contact with skin.
<b>Eye contact:</b>	Causes serious eye irritation.

**Information on toxicological effects****Acute toxicity (list all possible routes of exposure)**

<b>Oral</b>	
<b>Product:</b>	ATEmix: 19,212.4 mg/kg
<b>Dermal</b>	
<b>Product:</b>	ATEmix: 2,257.92 mg/kg
<b>Inhalation</b>	
<b>Product:</b>	ATEmix: 2.3 mg/l

<b>Repeated dose toxicity</b>	
<b>Product:</b>	No data available.

**Skin Corrosion/Irritation****Product:** No data available.**Serious Eye Damage/Eye Irritation****Product:** No data available.**Specified substance(s):**

Asphalt	in vivo (Rabbit, 24 hrs): Not irritating
Stoddard solvent (Mineral Spirits)	Irritating
Aluminum	in vivo (Rabbit, 24 hrs): Not irritating
Magnesite	In vitro (Reconstituted Corneal Epithelium model, 10 min): Not irritating

**Respiratory or Skin Sensitization****Product:** No data available.**Carcinogenicity****Product:** May cause cancer.**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

Asphalt	Overall evaluation: Possibly carcinogenic to humans.
Talc	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Possibly carcinogenic to humans.
Fibrous Glass	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Possibly carcinogenic to humans. Overall evaluation: Possibly carcinogenic to humans.

**US. National Toxicology Program (NTP) Report on Carcinogens:**

Fibrous Glass	Reasonably Anticipated to be a Human Carcinogen. Reasonably Anticipated to be a Human Carcinogen.
---------------	---

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):**

No carcinogenic components identified

**Germ Cell Mutagenicity****In vitro****Product:** No data available.**In vivo****Product:** No data available.**Reproductive toxicity****Product:** No data available.

**Specific Target Organ Toxicity - Single Exposure**

**Product:** No data available.

**Specific Target Organ Toxicity - Repeated Exposure**

**Product:** No data available.

**Aspiration Hazard**

**Product:** No data available.

**Other effects:** No data available.

<b>12. Ecological information</b>
-----------------------------------

**Ecotoxicity:**

**Acute hazards to the aquatic environment:**

**Fish**

**Product:** No data available.

**Specified substance(s):**

Aluminum LC 50 (Rainbow trout, donaldson trout (*Oncorhynchus mykiss*), 96 h): 0.31 mg/l Mortality

**Aquatic Invertebrates**

**Product:** No data available.

**Specified substance(s):**

Aluminum  
 LC 50 (Water flea (*Daphnia magna*), 24 h): 3.5 mg/l Mortality  
 LC 50 (Rotifer (*Brachionus calyciflorus*), 24 h): > 3 mg/l Mortality  
 LC 50 (Ridged-beak peaclam (*Pisidium compressum*), 96 h): > 0.4 mg/l Mortality  
 LC 50 (Scud (*Hyalella azteca*), 96 h): > 1 mg/l Mortality  
 LC 50 (Snail (*Amnicola limosa*), 96 h): > 1 mg/l Mortality

**Chronic hazards to the aquatic environment:**

**Fish**

**Product:** No data available.

**Specified substance(s):**

Asphalt NOAEL (*Oncorhynchus mykiss*, 28 d): >= 1,000 mg/l interpreted

Aluminum  
 LOAEL (*Pimephales promelas*, 28 d): 11.9 mg/l experimental result  
 EC 50 (*Pimephales promelas*, 7 d): 0.695 mg/l experimental result  
 LOAEL (*Salvelinus fontinalis*, 30 d): 0.169 mg/l experimental result  
 EC 50 (*Pimephales promelas*, 7 d): 3.999 mg/l experimental result  
 EC 10 (*Pimephales promelas*, 7 d): 0.726 mg/l experimental result

**Aquatic Invertebrates**

**Product:** No data available.

**Toxicity to Aquatic Plants**  
**Product:** No data available.

**Persistence and Degradability**

**Biodegradation**  
**Product:** No data available.

**BOD/COD Ratio**  
**Product:** No data available.

**Bioaccumulative Potential**

**Bioconcentration Factor (BCF)**  
**Product:** No data available.

**Specified substance(s):**  
Aluminum Brook trout (*Salvelinus fontinalis*), Bioconcentration Factor (BCF): 36 (Flow through)

**Partition Coefficient n-octanol / water (log Kow)**  
**Product:** No data available.

**Specified substance(s):**  
Stoddard solvent (Mineral Spirits) Log Kow: 3.16 - 7.15

**Mobility in Soil:** No data available.

**Other Adverse Effects:** Toxic to aquatic organisms.

<b>13. Disposal considerations</b>
------------------------------------

**Disposal instructions:** Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

**Contaminated Packaging:** No data available.

<b>14. Transport information</b>
----------------------------------

**TDG:**

Not Regulated

**CFR / DOT:**

Not Regulated

**IMDG:**

000000016278

UN1139, COATING SOLUTION, 3, PG III

**Further Information:**

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

**15. Regulatory information**

**US Federal Regulations**

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

None present or none present in regulated quantities.

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

None present or none present in regulated quantities.

**CERCLA Hazardous Substance List (40 CFR 302.4):**

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Asphalt	100 lbs.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories**

- Fire Hazard
- Immediate (Acute) Health Hazards
- Delayed (Chronic) Health Hazard

**SARA 302 Extremely Hazardous Substance**

None present or none present in regulated quantities.

**SARA 304 Emergency Release Notification**

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Asphalt	100 lbs.

**SARA 311/312 Hazardous Chemical**

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Asphalt	500 lbs
Stoddard solvent (Mineral Spirits)	500 lbs
Talc	500 lbs
Aluminum	500 lbs
Magnesite	500 lbs
Fibrous Glass	500 lbs
Cellulose	500 lbs
Silicon dioxide, amorphous	500 lbs

**SARA 313 (TRI Reporting)**

<u>Chemical Identity</u>
Aluminum

**Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)**

None present or none present in regulated quantities.

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):**

None present or none present in regulated quantities.

## US State Regulations

### US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

### US. New Jersey Worker and Community Right-to-Know Act

#### Chemical Identity

Asphalt  
Stoddard solvent (Mineral Spirits)  
Talc  
Aluminum  
Magnesite  
Fibrous Glass  
Cellulose

### US. Massachusetts RTK - Substance List

#### Chemical Identity

Asphalt  
Stoddard solvent (Mineral Spirits)  
Talc  
Aluminum  
Magnesite  
Fibrous Glass  
Cellulose

### US. Pennsylvania RTK - Hazardous Substances

#### Chemical Identity

Asphalt  
Stoddard solvent (Mineral Spirits)  
Talc  
Aluminum  
Fibrous Glass  
Cellulose

### US. Rhode Island RTK

#### Chemical Identity

Aluminum

## Other Regulations:

<b>Regulatory VOC (less water and exempt solvent):</b>	295 g/l
<b>VOC Method 310:</b>	26.07 %

## Inventory Status:

Australia AICS:	All components in this product are listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.

Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	All components in this product are listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	All components in this product are listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	All components in this product are listed on or exempt from the Inventory.
US TSCA Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	All components in this product are listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.

**16. Other information, including date of preparation or last revision**

<b>Revision Date:</b>	08/04/2015
<b>Version #:</b>	1.0
<b>Further Information:</b>	No data available.
<b>Disclaimer:</b>	For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.