

LEED DATA SHEET

DATE:	
PROJECT NAME:	
PROJECT LOCATION:	
NAME OF PRODUCT:	BURmastic ® Adhesive
DESCRIPTION:	Cold Applied Adhesive For Use With BURmastic Ply Sheets
PRODUCT/MATERIAL COST: \$	

SOLAR REFLECTIVITY INDEX (SRI)

PAVING & SLOPED ROOF >2:12 MUST BE AT LEAST 29:	N/A
LOW SLOPED ROOF MATERIALS MUST BE AT LEAST 78:	N/A

RECYCLED CONTENT

PRE-CONSUMER:	0	%
POST CONSUMER:	0	%

${\bf REGIONAL\ QUALIFICATIONS\ FOR\ PRODUCT/MATERIALS:}$

		DISTANCE FROM PROJECT:	MILES
LOCATION OF PROCESS:		DISTANCE FROM PROJECT:	MILES
LOCATION OF MANUFACTURE:	Cleveland, OH	DISTANCE FROM PROJECT:	MILES

LOW EMITTING MATERIALS:

COATING VOC (GRAMS/L)	SEALANT VOC (GRAMS/L)	ADHESIVE VOC (GRAMS/L)	USE OF MATERIAL	
		396 g/L		

RAPIDLY RENEWABLE MATERIAL:

PERCENT RENEWABLE:	0	%
COST: \$		

PREPARED BY:	

^{*}Extraction/Process/Manufacture is defined as the assembly of a final product not including on-site assembly or installation.

^{**}Due to several sources of raw materials for this product, specifying the origin of the component materials may not be possible.