

LEED DATA SHEET

DATE:	
PROJECT NAME:	
PROJECT LOCATION:	
NAME OF PRODUCT:	PowerPly Plus HT FR
DESCRIPTION:	A Fire Rated, Granule Surfaced, High Tensile Fiberglass Reinforced SBS/SEBS/SIS Modified Bitumen Membrane
PRODUCT/MATERIAL COST: \$	

SOLAR REFLECTIVITY INDEX (SRI)

PAVING & SLOPED ROOF >2:12 MUST BE AT LEAST 29:	
LOW SLOPED ROOF MATERIALS MUST BE AT LEAST 78:	

RECYCLED CONTENT

PRE-CONSUMER:		%
POST CONSUMER:		%

REGIONAL QUALIFICATIONS FOR PRODUCT/MATERIALS:

LOCATION OF EXTRACTION:		DISTANCE FROM PROJECT:		MILES
LOCATION OF PROCESS:		DISTANCE FROM PROJECT:		MILES
LOCATION OF MANUFACTURE:	Cleveland, OH	DISTANCE FROM PROJECT:		MILES

LOW EMITTING MATERIALS:

ADHESIVE VOC <small>(GRAMS/L)</small>	SEALANT VOC <small>(GRAMS/L)</small>	USE OF MATERIAL

RAPIDLY RENEWABLE MATERIAL:

PERCENT RENEWABLE:		%
COST:	\$	

PREPARED BY:	
--------------	--

*Extraction/Process/Manufacture is defined as the assembly of a final product not including on-site assembly or installation.

**Due to several sources of raw materials for this product, specifying the origin of the component materials may not be possible.