

LEED DATA SHEET

| | | |
|---------------------------|-----------------------------------------------------------------------------------------|--|
| DATE: | | |
| PROJECT NAME: | | |
| PROJECT LOCATION: | | |
| NAME OF PRODUCT: | POWERply Rubberized Cold Adhesive | |
| DESCRIPTION: | Cold Applied Rubberized Adhesive for use with the POWERply Modified Bitumen Roof System | |
| PRODUCT/MATERIAL COST: \$ | | |

SOLAR REFLECTIVITY INDEX (SRI)

| | |
|-------------------------------------------------|-----|
| PAVING & SLOPED ROOF >2:12 MUST BE AT LEAST 29: | N/A |
| LOW SLOPED ROOF MATERIALS MUST BE AT LEAST 78: | N/A |

RECYCLED CONTENT

| | | |
|----------------|---|---|
| PRE-CONSUMER: | 0 | % |
| POST CONSUMER: | 4 | % |

REGIONAL QUALIFICATIONS FOR PRODUCT/MATERIALS:

| | | | | |
|--------------------------|-------------|------------------------|--|-------|
| LOCATION OF EXTRACTION: | | DISTANCE FROM PROJECT: | | MILES |
| LOCATION OF PROCESS: | | DISTANCE FROM PROJECT: | | MILES |
| LOCATION OF MANUFACTURE: | Toronto, ON | DISTANCE FROM PROJECT: | | MILES |

LOW EMITTING MATERIALS:

| | | | |
|-----------------------------------------|-----------------------------------------|------------------------------------------|-----------------|
| COATING VOC <small>(GRAMS/L)</small> | SEALANT VOC <small>(GRAMS/L)</small> | ADHESIVE VOC <small>(GRAMS/L)</small> | USE OF MATERIAL |
| | | 246 g/L | |

RAPIDLY RENEWABLE MATERIAL:

| | | |
|--------------------|----|---|
| PERCENT RENEWABLE: | 0 | % |
| COST: | \$ | |

| | |
|--------------|--|
| PREPARED BY: | |
|--------------|--|

**Extraction/Process/Manufacture is defined as the assembly of a final product not including on-site assembly or installation.
 **Due to several sources of raw materials for this product, specifying the origin of the component materials may not be possible.*