

# SAFETY DATA SHEET

## 1. Identification

**Material name:** REGLET JOINT SEALANT 30 CTG CS

**Material:** 367400 323

**Recommended use and restriction on use**

**Recommended use:** Coatings

**Restrictions on use:** Not known.

**Manufacturer/Importer/Supplier/Distributor Information**

Tremco U.S. Roofing  
3735 Green Road  
Beachwood OH 44122  
US

**Contact person:**

EH&S Department

**Telephone:**

216-292-5000

**Emergency telephone number:**

1-800-424-9300 (US); 1-613-996-6666 (Canada)

## 2. Hazard(s) identification

### Hazard Classification

#### Health Hazards

Acute toxicity (Inhalation - dust and mist)	Category 4
Respiratory sensitizer	Category 1
Skin sensitizer	Category 1
Germ Cell Mutagenicity	Category 1B
Carcinogenicity	Category 1A

#### Unknown toxicity - Health

Acute toxicity, oral	10.93 %
Acute toxicity, dermal	18.39 %
Acute toxicity, inhalation, vapor	99.99 %
Acute toxicity, inhalation, dust or mist	58.66 %

### Label Elements

**Hazard Symbol:**



<b>Signal Word:</b>	Danger
<b>Hazard Statement:</b>	Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause genetic defects. May cause cancer.
<b>Precautionary Statements</b>	
<b>Prevention:</b>	Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
<b>Response:</b>	IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Call a POISON CENTER/doctor if you feel unwell. Specific treatment (see on this label). Wash contaminated clothing before reuse.
<b>Storage:</b>	Store locked up.
<b>Disposal:</b>	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
<b>Hazard(s) not otherwise classified (HNOC):</b>	None.

### 3. Composition/information on ingredients

#### Mixtures

Chemical Identity	CAS number	Content in percent (%)*
-------------------	------------	-------------------------

Aromatic process oil	64741-62-4	40 - 70%
Calcium Carbonate (Limestone)	1317-65-3	10 - 30%
Carbon Black	1333-86-4	7 - 13%
Calcium oxide	1305-78-8	3 - 7%
Stoddard solvent (Mineral Spirits)	8052-41-3	0.5 - 1.5%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%
Tosyl isocyanate	4083-64-1	0.1 - 1%
2,4-Toluene diisocyanate	584-84-9	0.1 - 1%
Dibutyl tin dilaurate	77-58-7	0.1 - 1%

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

#### 4. First-aid measures

<b>Ingestion:</b>	Rinse mouth thoroughly.
<b>Inhalation:</b>	Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
<b>Skin Contact:</b>	Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.
<b>Eye contact:</b>	Rinse immediately with plenty of water.
<b>Most important symptoms/effects, acute and delayed</b>	
<b>Symptoms:</b>	May cause skin and eye irritation.
<b>Indication of immediate medical attention and special treatment needed</b>	
<b>Treatment:</b>	Symptoms may be delayed.

#### 5. Fire-fighting measures

<b>General Fire Hazards:</b>	No unusual fire or explosion hazards noted.
<b>Suitable (and unsuitable) extinguishing media</b>	
<b>Suitable extinguishing media:</b>	Use fire-extinguishing media appropriate for surrounding materials.
<b>Unsuitable extinguishing media:</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical:</b>	During fire, gases hazardous to health may be formed.

## Special protective equipment and precautions for firefighters

<b>Special fire fighting procedures:</b>	No data available.
<b>Special protective equipment for fire-fighters:</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures:</b>	Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.
<b>Methods and material for containment and cleaning up:</b>	Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.
<b>Notification Procedures:</b>	In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.
<b>Environmental Precautions:</b>	Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water sources or sewer. Environmental manager must be informed of all major spillages.

## 7. Handling and storage

<b>Precautions for safe handling:</b>	Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
<b>Conditions for safe storage, including any incompatibilities:</b>	Store locked up.

## 8. Exposure controls/personal protection

### Control Parameters

#### Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (2011)
Carbon Black	PEL	3.5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)

	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stoddard solvent (Mineral Spirits)	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	500 ppm 2,900 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
2,4-Toluene diisocyanate - Inhalable fraction and vapor.	STEL	0.005 ppm	US. ACGIH Threshold Limit Values (03 2016)
	TWA	0.001 ppm	US. ACGIH Threshold Limit Values (03 2016)
2,4-Toluene diisocyanate	Ceiling	0.02 ppm 0.14 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	Type	Exposure Limit Values	Source
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Carbon Black - Inhalable	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Carbon Black	TWA	3.5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWA	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation

			296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Hydrotreated heavy naphthenic distillate - Mist.	STEL	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
2,4-Toluene diisocyanate	CEILING	0.01 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.005 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
2,4-Toluene diisocyanate	TWA	0.005 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	CEV	0.02 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
2,4-Toluene diisocyanate	TWA	0.005 ppm 0.036 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	STEL	0.02 ppm 0.14 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

#### Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
2,4-Toluene diisocyanate (Toluene diamine (sum of 2,4- and 2,6-isomers), with hydrolysis: Sampling time: End of shift.)	5 µg/g (Creatinine in urine)	ACGIH BEI (03 2016)

#### Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

#### Individual protection measures, such as personal protective equipment

**General information:** Use personal protective equipment as required.

**Eye/face protection:** Wear goggles/face shield.

#### Skin Protection

**Hand Protection:** Use suitable protective gloves if risk of skin contact.

**Other:** Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.

**Respiratory Protection:** If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.

**Hygiene measures:** Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

## 9. Physical and chemical properties

### Appearance

**Physical state:** solid  
**Form:** Paste  
**Color:** Dark brown

**Odor:** Mild petroleum/solvent

**Odor threshold:** No data available.

**pH:** No data available.

**Melting point/freezing point:** No data available.

**Initial boiling point and boiling range:** No data available.

**Flash Point:** > 93 °C > 199 °F

**Evaporation rate:** Slower than Ether

**Flammability (solid, gas):** No

### Upper/lower limit on flammability or explosive limits

**Flammability limit - upper (%):** No data available.

**Flammability limit - lower (%):** No data available.

**Explosive limit - upper (%):** No data available.

**Explosive limit - lower (%):** No data available.

**Vapor pressure:** No data available.

**Vapor density:** Vapors are heavier than air and may travel along the floor and in the bottom of containers.

**Relative density:** 1.21

### Solubility(ies)

**Solubility in water:** Practically Insoluble

**Solubility (other):** No data available.

**Partition coefficient (n-octanol/water):** No data available.

**Auto-ignition temperature:** No data available.

**Decomposition temperature:** No data available.

**Viscosity:** No data available.

## 10. Stability and reactivity

**Reactivity:** No data available.

---

<b>Chemical Stability:</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions:</b>	No data available.
<b>Conditions to avoid:</b>	Avoid heat or contamination.
<b>Incompatible Materials:</b>	Alcohols. Amines. Strong acids. Strong bases. Water, moisture.
<b>Hazardous Decomposition Products:</b>	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

**11. Toxicological information****Information on likely routes of exposure**

<b>Inhalation:</b>	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
<b>Skin Contact:</b>	May cause an allergic skin reaction.
<b>Eye contact:</b>	Eye contact is possible and should be avoided.
<b>Ingestion:</b>	May be ingested by accident. Ingestion may cause irritation and malaise.

**Symptoms related to the physical, chemical and toxicological characteristics**

<b>Inhalation:</b>	No data available.
<b>Skin Contact:</b>	No data available.
<b>Eye contact:</b>	No data available.
<b>Ingestion:</b>	No data available.

**Information on toxicological effects****Acute toxicity (list all possible routes of exposure)**

<b>Oral Product:</b>	Not classified for acute toxicity based on available data.
----------------------	--



<b>Specified substance(s):</b>	
Aromatic process oil	LD 50 (Rat): 4,320 mg/kg
Carbon Black	LD 50 (Rat): > 8,000 mg/kg
Calcium oxide	LD 50 (Rat): 790 mg/kg
Hydrotreated heavy naphthenic distillate	LD 50 (Rat): > 5,000 mg/kg
Tosyl isocyanate	LD 50 (Rat): 2,330 mg/kg
2,4-Toluene diisocyanate	LD 50 (Rat): 4,130 mg/kg
Dibutyl tin dilaurate	LD 50 (Rat): 2,071 mg/kg
<b>Dermal</b>	
<b>Product:</b>	ATEmix: 9,752.84 mg/kg
<b>Inhalation</b>	
<b>Product:</b>	ATEmix: 3.6 mg/l
<b>Repeated dose toxicity</b>	
<b>Product:</b>	No data available.
<b>Skin Corrosion/Irritation</b>	
<b>Product:</b>	No data available.
<b>Specified substance(s):</b>	
Carbon Black	in vivo (Rabbit): Not irritant Experimental result, Key study
Calcium oxide	in vivo (Rabbit): Irritating Read-across from supporting substance (structural analogue or surrogate), Key study
Hydrotreated heavy naphthenic distillate	in vivo (Rabbit): Not irritant Experimental result, Key study
2,4-Toluene diisocyanate	in vivo (Rabbit): Moderately irritating Experimental result, Supporting study
Dibutyl tin dilaurate	In vitro (Human, in vitro reconstituted epidermis model): Not irritant Experimental result, Supporting study

**Serious Eye Damage/Eye Irritation****Product:** No data available.**Specified substance(s):**

Carbon Black	Rabbit, 24 - 72 hrs: Not irritating
Hydrotreated heavy naphthenic distillate	Rabbit, 24 hrs: Not irritating
2,4-Toluene diisocyanate	Rabbit, 24 - 72 hrs: Category 2
Dibutyl tin dilaurate	Rabbit, 24 hrs: Highly irritating

**Respiratory or Skin Sensitization****Product:** May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
May cause sensitization by inhalation.**Carcinogenicity****Product:** No data available.**IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:**

Aromatic process oil	Overall evaluation: Possibly carcinogenic to humans.
Carbon Black	Overall evaluation: Possibly carcinogenic to humans.
Hydrotreated heavy naphthenic distillate	Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.
2,4-Toluene diisocyanate	Overall evaluation: Possibly carcinogenic to humans.

**US. National Toxicology Program (NTP) Report on Carcinogens:**

Hydrotreated heavy naphthenic distillate	Known To Be Human Carcinogen.
2,4-Toluene diisocyanate	Reasonably Anticipated to be a Human Carcinogen.

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):**

No carcinogenic components identified

**Germ Cell Mutagenicity****In vitro****Product:** No data available.**In vivo****Product:** No data available.**Reproductive toxicity**

**Product:** No data available.

**Specific Target Organ Toxicity - Single Exposure**

**Product:** No data available.

**Specific Target Organ Toxicity - Repeated Exposure**

**Product:** No data available.

**Aspiration Hazard**

**Product:** No data available.

**Other effects:** No data available.

## 12. Ecological information

**Ecotoxicity:**

**Acute hazards to the aquatic environment:**

**Fish**

**Product:** No data available.

**Specified substance(s):**

2,4-Toluene diisocyanate LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 108.8 - 240.4 mg/l Mortality

Dibutyl tin dilaurate LC 50 (Ide, silver or golden orfe (*Leuciscus idus*), 48 h): 2 mg/l Mortality

**Aquatic Invertebrates**

**Product:** No data available.

**Specified substance(s):**

Dibutyl tin dilaurate EC 50 (Water flea (*Daphnia magna*), 24 h): 0.66 mg/l Intoxication

**Chronic hazards to the aquatic environment:**

**Fish**

**Product:** No data available.

**Specified substance(s):**

Aromatic process oil NOAEL (*Oncorhynchus mykiss*, 28 d): 0.1 mg/l QSAR QSAR, Key study

Hydrotreated heavy naphthenic distillate NOAEL (*Oncorhynchus mykiss*, 14 d):  $\geq 1,000$  mg/l QSAR QSAR, Supporting study

**Aquatic Invertebrates**

**Product:** No data available.

**Toxicity to Aquatic Plants****Product:** No data available.**Persistence and Degradability****Biodegradation****Product:** No data available.**BOD/COD Ratio****Product:** No data available.**Bioaccumulative potential****Bioconcentration Factor (BCF)****Product:** No data available.**Partition Coefficient n-octanol / water (log Kow)****Product:** No data available.**Specified substance(s):**

Stoddard solvent (Mineral Spirits) Log Kow: 3.16 - 7.15

Dibutyl tin dilaurate Log Kow: 3.12

**Mobility in soil:** No data available.**Other adverse effects:** No data available.**13. Disposal considerations****Disposal instructions:** Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.**Contaminated Packaging:** No data available.**14. Transport information****TDG:**

Not Regulated

**CFR / DOT:**

Not Regulated

**IMDG:**

Not Regulated

**15. Regulatory information**

**US Federal Regulations**

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

<u>Chemical Identity</u>	<u>Reportable quantity</u>
2,4-Toluene diisocyanate	De minimis concentration: TSCA 5(a)(2)% One-Time Export Notification only.

**US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

None present or none present in regulated quantities.

**CERCLA Hazardous Substance List (40 CFR 302.4):**

<u>Chemical Identity</u>	<u>Reportable quantity</u>
2,4-Toluene diisocyanate	100 lbs.
Chrysene	100 lbs.
Toluene-2,6-Diisocyanate	100 lbs.
Benzo(a)pyrene	1 lbs.
Naphthalene	100 lbs.
Cumene	5000 lbs.
Ethylbenzene	1000 lbs.
Chlorobenzene	100 lbs.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**Hazard categories**

Immediate (Acute) Health Hazards  
Delayed (Chronic) Health Hazard

**SARA 302 Extremely Hazardous Substance**

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
2,4-Toluene diisocyanate	100 lbs.	500 lbs.
Toluene-2,6-Diisocyanate	100 lbs.	100 lbs.

**SARA 304 Emergency Release Notification**

<u>Chemical Identity</u>	<u>Reportable quantity</u>
2,4-Toluene diisocyanate	100 lbs.
Chrysene	100 lbs.
Toluene-2,6-Diisocyanate	100 lbs.
Benzo(a)pyrene	1 lbs.
Naphthalene	100 lbs.
Cumene	5000 lbs.
Ethylbenzene	1000 lbs.
Chlorobenzene	100 lbs.

## SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
2,4-Toluene diisocyanate	500lbs
Toluene-2,6-Diisocyanate	100lbs
Aromatic process oil	10000 lbs
Calcium Carbonate (Limestone)	10000 lbs
Carbon Black	10000 lbs
Calcium oxide	10000 lbs
Stoddard solvent (Mineral Spirits)	10000 lbs
Hydrotreated heavy naphthenic distillate	10000 lbs
Tosyl isocyanate	10000 lbs
Dibutyl tin dilaurate	10000 lbs

## SARA 313 (TRI Reporting)

<u>Chemical Identity</u>
2,4-Toluene diisocyanate

## Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

<u>Chemical Identity</u>	<u>Reportable quantity</u>
2,4-Toluene diisocyanate	lbs
Toluene-2,6-Diisocyanate	lbs

## Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

## US State Regulations

### US. California Proposition 65



#### WARNING

Cancer - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

### US. New Jersey Worker and Community Right-to-Know Act

<u>Chemical Identity</u>
Calcium Carbonate (Limestone)
Carbon Black
Calcium oxide
Hydrotreated heavy naphthenic distillate
2,4-Toluene diisocyanate

### US. Massachusetts RTK - Substance List

<u>Chemical Identity</u>
Calcium Carbonate (Limestone)
Carbon Black
Calcium oxide
2,4-Toluene diisocyanate
Chrysene
Toluene-2,6-Diisocyanate
Benzo(a)pyrene
Crystalline Silica (Quartz)/ Silica Sand

---

**US. Pennsylvania RTK - Hazardous Substances**

**Chemical Identity**

Calcium Carbonate (Limestone)  
Carbon Black  
Calcium oxide  
2,4-Toluene diisocyanate

**US. Rhode Island RTK**

**Chemical Identity**

Calcium Carbonate (Limestone)  
Carbon Black  
Calcium oxide

**International regulations**

**Montreal protocol**

Not applicable

**Stockholm convention**

Not applicable

**Rotterdam convention**

Not applicable

**Kyoto protocol**

Not applicable

**VOC:**

Regulatory VOC (less water and  
exempt solvent) : 55 g/l

VOC Method 310 : 4.92 %

**Inventory Status:**

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	All components in this product are listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	All components in this product are listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	All components in this product are listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.

**16. Other information, including date of preparation or last revision**

**Revision Date:** 07/21/2018  
**Version #:** 1.2  
**Further Information:** No data available.



---

**Disclaimer:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

