

N/A

LEED DATA SHEET

DATE:					
PROJECT NAME	i:				
PROJECT LOCA	TION:				
		•			
NAME OF PROD	UCT:	BURmasti	c® Adhesive SF		
DESCRIPTION:		Cold Applied Adhesive for use with BURmastic Ply Sheets and POWERply® MB Membranes.			
PRODUCT/MATERIAL COST		COST: \$			
THOSE COMMITTEE IN THE		,021.0			
		•			
SOLAR REFLECTIVITY INDEX (SRI)					
		PAV	TNG & SLOPED ROOF >2:12 MUST BE AT LEAST 29: N/A		

LOW SLOPED ROOF MATERIALS MUST BE AT LEAST 78:

RECYCLED CONTENT

PRE-CONSUMER:	0	%
POST CONSUMER:	0	%

REGIONAL QUALIFICATIONS FOR PRODUCT/MATERIALS:

LOCATION OF EXTRACTION:		DISTANCE FROM PROJECT:	MILES
LOCATION OF PROCESS:		DISTANCE FROM PROJECT:	MILES
LOCATION OF MANUFACTURE:	Cleveland, OH	DISTANCE FROM PROJECT:	MILES

LOW EMITTING MATERIALS:

COATING VOC (GRAMS/L)	SEALANT VOC (GRAMS/L)	ADHESIVE VOC (GRAMS/L)	USE OF MATERIAL	
		53 g/L		

RAPIDLY RENEWABLE MATERIAL:

PERCENT RENEWABLE:	0	%
COST: \$		

PREPARED BY:	

 $^{{\}bf *Extraction/Process/Manufacture}\ is\ defined\ as\ the\ assembly\ of\ a\ final\ product\ not\ including\ on\ -site\ assembly\ or\ installation.$

^{**}Due to several sources of raw materials for this product, specifying the origin of the component materials may not be possible.