

# LEED DATA SHEET

DATE:	
PROJECT NAME:	
PROJECT LOCATION:	
NAME OF PRODUCT:	Sheeting Bond
DESCRIPTION:	A Trowel Grade Elastomeric Adhesive for Tremco Elastomeric Sheeting
PRODUCT/MATERIAL	COST: \$

#### SOLAR REFLECTIVITY INDEX (SRI)

PAVING & SLOPED ROOF >2:12 MUST BE AT LEAST 29:	
LOW SLOPED ROOF MATERIALS MUST BE AT LEAST 78:	

### **RECYCLED CONTENT**

PRE-CONSUMER:	%	
POST CONSUMER:	%	

### **REGIONAL QUALIFICATIONS FOR PRODUCT/MATERIALS:**

LOCATION OF EXTRACTION:		DISTANCE FROM PROJECT:	MILES
LOCATION OF PROCESS:		DISTANCE FROM PROJECT:	MILES
LOCATION OF MANUFACTURE:	Toronto, ON	DISTANCE FROM PROJECT:	MILES

#### LOW EMITTING MATERIALS:

ADHESIVE VOC (GRAMS/L)	SEALANT VOC (GRAMS/L)	USE OF MATERIAL
<250		Adhesive for Elastomeric Sheeting

## **RAPIDLY RENEWABLE MATERIAL:**

PERCENT RENEWABLE:	%
COST: \$	

PREPARED BY:

\*Extraction/Process/Manufacture is defined as the assembly of a final product not including on-site assembly or installation. \*\*Due to several sources of raw materials for this product, specifying the origin of the component materials may not be possible.

