

# TPA Walkway Roll

## *A Thermoplastic Tri-Polymer Alloy Walkway Roll*

### FEATURES

Thermoplastic

Serrated Surface

Packaged as a Roll

Chemically resistant

### BENEFITS

- Quickly installed by heat welding
- Non slip traffic pad
- Custom cut to roof areas
- Resists environmental pollution, acid rain, and minor oil exposure

### DESCRIPTION

TPA Walkway Roll is a thermoplastic membrane which is comprised of an elastomeric tri-polymer alloy based on Elvaloy® and blended with CPE and PVC. TPA Walkway Roll is reinforced with a high strength, wick resistant polyester fabric and has a serrated, slip-resistant surface.

### BASIC USES

TPA Walkway Rolls are recommended to protect TPA and TPA FB Single Ply roof from potential damage as a result of light foot traffic and light tool or equipment handling. TPA Walkway Rolls are also compatible for installation to PVC roof membrane systems. Works well as roof top service pathways, around roof top equipment and under light equipment supports.

Available as a single roll or in pallets, with 20 rolls per pallet.

### PACKAGING

3' x 60' x 0.080 (914 mm x 18.29 meters), easily field cut to desired size.

### DIMENSIONS

COLOR	THICKNESS	WEIGHT
Gray	0.072" (2 mm nominal)	99 lbs (45 kg)
Yellow	0.156" (4 mm nominal)	129 lbs (58 kg)

### APPLICATION

The following application information is designed to serve as a general guide. Your local Tremco Representative will prepare detailed specifications based upon your roofs conditions.

Spot weld TPA Walkway Roll to roof membrane. Attachment of walkway roll should not impede drainage. Field test heat welded spots to assure proper construction. Properly constructed heat welds will not separate at the lap interface when tested.

### LIMITATIONS

Not intended for use over PIB, TPO, EPDM, or BUR/MB roof membranes.

### PHYSICAL PROPERTIES

PROPERTY	TYPICAL VALUE	TEST METHOD
Tensile, Grab	200 lbf (890 N)	ASTM D751-A
Tear Strength, Tongue	45 lbf (200 N)	ASTM D751-B
Coefficient of Friction	Dry 1 .0 units, Wet 1.3 units	ASTM CI028
Low Temp Flex	-40°F (-40°C)	ASTM D 1204

## MAINTENANCE

## PRECAUTIONS

## TECHNICAL SUPPORT

# TPA Walkway Roll

Your local Tremco Roofing Representative can provide you with effective maintenance procedures which may vary, depending upon specific conditions. Periodic inspections, early repairs and preventative maintenance are all part of a sound roof program.

Users must read container labels and Safety Data Sheets for health and safety precautions prior to use.

Your local Tremco Representative, working with the Technical Service Staff, can help analyze conditions and needs to develop recommendations for special applications. The services of the Tremco Research Center, which has earned a unique reputation in weatherproofing technology, complement and extend the service of the Tremco Service Staff.



**www.tremcoroofing.com**  
3735 Green Road  
Beachwood, Ohio 44122  
1.800.852.6013

220 Wicksteed Avenue  
Toronto, Ontario, M4H 1G7  
1.800.668.9879

Tremco Roofing and Building  
Maintenance is part of Tremco  
Construction Products Group.

Tremco is a US Registered trademark of Tremco CPG Inc.

The information provided on this data page supersedes all previous data concerning this product and its application. The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Tremco DOES NOT MAKE NOR DOES IT AUTHORIZE ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO TREMCO'S PRODUCT SAMPLE. Buyer and user accept the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handling, storage or use of the product, whether or not it is handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCE SHALL TREMCO BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY. IN ALL CASES, TREMCO'S LIABILITY IS LIMITED, AT TREMCO'S OPTION, TO THE REPLACEMENT OF GOODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING.