

# TremPly® TPO Flashing Strip



## An Accessory Designed for TremPly TPO Single Ply Roof System

### FEATURES

Cost effective

Factory-built accessories

Uniform look

### BENEFITS

Reliability is built in

Improved reliability, reduces risk of leaks and callbacks

Improved aesthetics

### DESCRIPTION:

TremPly® TPO Flashing Strip provides roofing contractors with an easy-to-install, factory-built detail. This accessory is used to strip-in coated metal flanges and at areas that require a reinforced membrane for flashing. TremPly TPO Flashing Strip is constructed using Tremco's proven, durable TremPly TPO.

### BASIC USES:

The membrane in TremPly TPO Flashing Strip is reinforced, so it's durable and versatile and is manufactured to strict specifications, designed for ease of installation and used in a variety of flashing details, including stripping-in coated metal.

### COLORS:

White, Tan, Gray

### PACKAGING:

8" x 100' (203 mm x 30.5 m); Weight, 18 lbs (8.2 kg) per roll.

### APPLICATION:

TremPly TPO Flashing Strip is designed for use with TremPly TPO. The 45 mil utility flashing membrane may be installed on TremPly TPO 45, 60, and 80 mil mechanically attached or fully adhered roofing systems. See published application and specifications manual for detailed instructions.

### MAINTENANCE:

Your local Tremco Roofing representative can provide you with effective maintenance procedures, which may vary depending upon specific conditions. Periodic inspections, early repairs and preventive maintenance are all part of a sound roof program.

### TECHNICAL SERVICES:

Your local Tremco Roofing representative, working with the Technical Service Staff, can help analyze conditions and needs to develop recommendations for special applications.



7141  
3/20/18

[www.tremcoroofing.com](http://www.tremcoroofing.com)  
3735 Green Road  
Beachwood, Ohio 44122  
1.800.852.6013



50 Beth Neelson Drive  
Toronto, Ontario M4H 1M6  
1.800.668.9879

TremPly is a U.S. registered trademark of Tremco Incorporated.

The information provided on this data sheet is effective as of December 2017 and supersedes all previous data concerning this product and its application.

The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Tremco DOES NOT MAKE NOR DOES IT AUTHORIZE ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO TREMCO'S PRODUCT SAMPLE. Buyer and user accept the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handling, storage or use of the product, whether or not it is handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCES SHALL TREMCO BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY. IN ALL CASES, TREMCO'S LIABILITY IS LIMITED, AT TREMCO'S OPTION, TO THE REPLACEMENT OF GOODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING.