

# TremPly® TPO Bonding Adhesive



## An Accessory Designed for TremPly TPO Single Ply Roof System

### FEATURES

Excellent coverage

Fast-drying solvent system

Multiple application options

High initial tack

### BENEFITS

Up to 70 sq ft/gallon of bonded membrane

Quicker application

Easy with roller or brush, spray application also possible

Quick and easy application

### DESCRIPTION:

TremPly® TPO Bonding Adhesive is a contact-type bonding adhesive specially designed for bonding TPO single ply roofing membranes and flashings to various roofing substrates.

### BASIC USES:

TremPly® TPO Bonding Adhesive is a general purpose, rubber-based bonding adhesive for attaching TPO-based single-ply membranes to various substrates, including polyisocyanurate insulation and gypsum-based cover boards.

### COLORS:

Yellow

### PACKAGING:

5 gallon pails. Weight, 37 lbs per pail; 45 pails per pallet

### PHYSICAL PROPERTIES:

**Base:** Synthetic polymer  
**Solvent:** Hydrocarbon blend  
**Flash point:** 0°F (-18°C)  
**Weight/Gallon:** 7.4 lbs  
**Viscosity:** 2,300 - 2,700 cps  
**Coverage:** 50-70 sq. ft./gallon  
**Total Solids:** 25% +/- 2.5%  
**Voc:** <704 g/l  
**Shelf Life:** 1 year, unopened  
**Open Time:** Up to 60 minutes  
**Dry Time:** 5 – 15 minutes  
**Application:** Roller, brush, or spray

### MAINTENANCE:

Your local Tremco Roofing representative can provide you with effective maintenance procedures, which may vary depending upon specific conditions. Periodic inspections, early repairs and preventive maintenance are all part of a sound roof program.

### TECHNICAL SERVICES:

Your local Tremco Roofing representative, working with the Technical Service Staff, can help analyze conditions and needs to develop recommendations for special applications.



7137  
3/20/18

[www.tremcoroofing.com](http://www.tremcoroofing.com)  
3735 Green Road  
Beachwood, Ohio 44122  
1.800.852.6013



50 Beth Neelson Drive  
Toronto, Ontario M4H 1M6  
1.800.668.9879

TremPly is a U.S. registered trademark of Tremco Incorporated.

The information provided on this data sheet is effective as of December 2017 and supersedes all previous data concerning this product and its application.

The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Tremco DOES NOT MAKE NOR DOES IT AUTHORIZE ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO TREMCO'S PRODUCT SAMPLE. Buyer and user accept the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handling, storage or use of the product, whether or not it is handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCES SHALL TREMCO BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY. IN ALL CASES, TREMCO'S LIABILITY IS LIMITED, AT TREMCO'S OPTION, TO THE REPLACEMENT OF GOODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING.