

TremPly® TPO Walkway Roll


An Accessory Designed for TremPly TPO Single Ply Roof System

FEATURES

- Diamond plate design
- Smooth edges
- Manufactured using recycled TPO

BENEFITS

- Great traction
- Easy weldability
- Excellent weatherability built in



DESCRIPTION

TremPly® TPO Walkway Roll provides roofing contractors with an easy-to-install, factory-built detail. It is manufactured using proven, durable TremPly TPO as well as recycled TPO.

BASIC USES

TremPly TPO Walkway Roll is designed to protect the membrane in areas exposed to rooftop traffic for maintenance access or other uses. These areas include HVAC, roof hatches, access doors, etc. TremPly TPO Walkway Roll is required on a Tremco-warranted roofing system. "Safety" Yellow Walkway Rolls are great for sensitive areas of a roof, such as perimeters, around skylights, or in areas of low clearance.

COLORS

Gray and Safety Yellow.

SIZE

34" x 50' (864 mm x 15.24 m); diamond pattern measures 30" [762 mm] with 2" [51 mm] smooth on both edges. 125 mil thickness. 79 lb.(34.02 kg) per roll (nominal).

APPLICATION

Heat weld: Heat-weld TremPly TPO Walkway Roll to the roof membrane surface continuously around the walkway roll perimeter. Walkway rolls must be spaced 6" apart (152 mm) to allow for drainage.

- First, roll or brush TPO primer on the back of the TPO roll along the edges and down the middle length of the roll.
- Clean and prime the roof membrane where the roll will be installed.
- Install tape to the back of the roll where cleaned (edges and middle) and roll-in with a silicone hand roller.
- Remove the release paper and install the taped rolls directly onto the roof membrane. Secure the rolls by rolling into place.

TremPly® TPO Walkway Roll

MAINTENANCE:

Your local Tremco Roofing representative can provide you with effective maintenance procedures, which may vary depending upon specific conditions. Periodic inspections, early repairs and preventive maintenance are all part of a sound roof program.

TECHNICAL SUPPORT

Your local Tremco Representative, working with the Technical Service Staff, can help analyze conditions and needs to develop recommendations for special applications. The services of the Tremco Research Center, which has earned a unique reputation in weatherproofing technology, complement and extend the service of the Tremco Service Staff.



www.tremcoroofing.com
3735 Green Road
Beachwood, Ohio 44122
1.800.852.6013

220 Wicksteed Avenue
Toronto, Ontario, M4H 1G7
1.800.668.9879

Tremco Roofing and Building
Maintenance is part of Tremco
Construction Products Group.

Tremco is a US Registered trademark of Tremco CPG Inc.

The information provided on this data page supersedes all previous data concerning this product and its application.

The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Tremco DOES NOT MAKE NOR DOES IT AUTHORIZE ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO TREMCO'S PRODUCT SAMPLE. Buyer and user accept the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handling, storage or use of the product, whether or not it is handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCE SHALL TREMCO BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY. IN ALL CASES, TREMCO'S LIABILITY IS LIMITED, AT TREMCO'S OPTION, TO THE REPLACEMENT OF GOODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING.