

TREMprime QD

Composition: TREMprime QD is formulated from refined select asphalt and penetrating oils to produce an effective priming base for application of Tremco Roofing Systems. TREMprime QD is asbestos free.

Basic Uses: TREMprime QD promotes adhesion of Tremco systems to a variety of surfaces (including weathered bituminous, concrete and metal).

Limitations:

- TREMprime QD is not intended to be used as a final coating.
- Do not apply when rain appears imminent.

Grade: Brush/Roll/Spray

Packaging: TREMprime QD is available in 18.9 L (5 U.S. Gal.) container.

Storage Life: One year

Application: Remove all loose dust, dirt, rotted felt and foreign matter. Surface must be clean and dry.

When spraying TREMprime QD take necessary precautions to prevent overspray.

Allow TREMprime QD to become touch dry before overcoating.

Coverage: Coverage will vary depending upon actual surface and application conditions.

Approximately 2.5 - 3.7 m²/L (100 - 150 sq. ft./U.S. Gal.).

Cleaning: Equipment may be cleaned immediately after use with Xylol or Mineral Spirits.

Precautions: Use Primers with adequate ventilation. Users must read container labels and Material Safety Data Sheets for health and safety precautions prior to use.

Availability/Cost: Immediately available from Tremco Ltd. at strategic locations throughout Canada.

Cost data is available from your local Tremco Representative. For name and telephone number of your local Tremco Representative, call 416/421-3300 in Toronto, 514/521-9555 in Montreal or 800/263-6046. In the U.S. call 216/292-5000 or 800/852-6013.

Guarantee/Warranty: We warrant our products to be free of defects and manufactured to meet published physical properties when cured and tested according to ASTM, CGSB and Tremco standards. Under this warranty, we will provide, at no charge, additional product to replace any product proved to be defective when applied in accordance with our written instructions and in applications recommended by us as suitable for this product.

All claims concerning product defect must be made within twelve (12) months of shipment. Absence of such claims in writing during this period will constitute a waiver of all claims with respect to such product.

This warranty is in lieu of any and all other warranties expressed or implied.

Maintenance During Warranty Period: Written notice to Tremco within thirty (30) days is required after any alleged defect is noticed.

Technical Services: Your local Tremco Representative, in conjunction with Tremco Engineering Service Department, provides problem analysis and assistance in developing recommendations for special applications. On-site instruction can generally be provided at a nominal charge. Their services are complemented and extended by Tremco's Research and Development Laboratory, which has earned a unique reputation in weatherproofing technology.

Product Advantages	
Features	Benefits
Non-fibrated	<ul style="list-style-type: none">• Allows maximum penetration of dried felts and porous substrates
Penetrating oils	<ul style="list-style-type: none">• Conditions asphalts and felts to provide a highly receptive surface for protective treatments
Quick drying formula	<ul style="list-style-type: none">• Minimizes wait for curing
Readily workable consistency	<ul style="list-style-type: none">• Easily brushes substrates providing more uniform surfaces• Can be used on metalwork and other surfaces

TREMCO

Roofing & Weatherproofing Peace of Mind™

Statement of Policy and Responsibility: Tremco takes responsibility for the furnishing of quality materials, and providing specifications and recommendations for their proper installation.

Tremco does not, either itself or through its representatives, practice architecture or structural engineering. Tremco offers no opinion on, and expressly disclaims any responsibility for, the structural soundness of any substrate on which its products may be applied.

Opinions of competent structural engineers should be obtained as to the structural soundness of the substrate, or its ability to properly support the contemplated installation. Tremco accepts no liability for any structural failure or for resultant damages, and no Tremco Representative is authorized to vary this disclaimer.

Physical/Performance Characteristics		
TREMPRIME QD		
Property	Typical Value	Test Method
Viscosity @ 25°C (Ford cup B1)	14.5 s	ASTM D 1200-82
Solids by weight	44%	ASTM D 1644-75
Density	(7.8 lb/gal)	ASTM D 1475-85
Flash point	38°C (100°F)	ASTM D 3278-82

TREMCO

3735 Green Road
Beachwood, OH 44122
216-292-5000

An **RPM** Company

220 Wicksteed Ave
Toronto, ONT M4H 1G7
416-421-3300

10042E
Printed in USA

Rev. 8/03