

TREMprime™ QD Low Odor

FEATURES

- Non-fibrated
- Low Odor
- Quick drying formula
- Readily workable consistency
- Multi-purpose

BENEFITS

- Allows maximum penetration of dried felts and porous substrates
- Minimizes disruption to building occupants.
- Minimizes wait for curing
- Easily brushes into rougher substrates providing more uniform surfaces
- Can be used on metal work and other surfaces

DESCRIPTION

TREMprime™ QD Low Odor is formulated from refined select asphalt to produce an effective priming base for the application of Tremco Roofing Systems. TREMprime QD Low Odor is asbestos free.

BASIC USES

TREMprime QD Low Odor promotes adhesion between weathered surfaces and Tremco coatings, adhesives, and maintenance systems. TREMprime QD Low Odor is also used as a metal primer to enhance the adhesion of asphalt cements and flashing adhesives.

PACKAGING

TREMprime QD Low Odor is available in 5 and 55 gallon containers.

GRADE

Brush, Roll, Spray.

STORAGE LIFE

One year.

APPLICATION

Recommended spray equipment: Minimum 11:1 ratio pump with 0.015" to 0.021" spray tip.

Application: Remove all loose dust, dirt, rotted felt, and foreign matter. Surface must be clean and dry.

When spraying TREMprime QD Low Odor take necessary precautions to prevent overspray.

COVERAGE

Coverage will vary depending upon actual surface and application conditions. Approximately 200-400 ft²/gal(4.9-9.8 m²/L).

CLEAN UP

Mineral Spirits.

LIMITATIONS

- TREMprime QD is not intended to be used as a final coating.
- Do not apply when rain appears imminent.

PHYSICAL PROPERTIES

PROPERTY	TYPICAL VALUE	TEST METHOD
Asbestos content	None	ASTM D 276-87
Density @ 77°F (25°C)	7.8 lb/gal (934.8 kg/m ³)	ASTM D 1475-90
Non-Volatile Content	52%	ASTM D 1644-88 (1981)
Flash point	>100°F	ASTM D 3278-82
Odor	Faint/Slight petroleum	
Vapor density	4.9-Mineral Spirits	

MAINTENANCE

Your local Tremco Roofing sales representative can provide you with effective maintenance procedures which may vary, depending upon specific conditions. Periodic inspections, early repairs and preventative maintenance are all part of a sound roof program.

TREMPPrime™ QD Low Odor

PRECAUTIONS

Users must read container labels and Safety Data Sheets for health and safety precautions prior to use.

TECHNICAL SUPPORT

Your local Tremco Roofing sales representative, working with the Technical Service Staff, can help analyze conditions and needs to develop recommendations for special applications.



Roofing & Building Maintenance

www.tremcoroofing.com

3735 Green Road
Beachwood, Ohio 44122
1.800.852.6013

220 Wicksteed Avenue
Toronto, Ontario, M4H 1G7
1.800.668.9879

Tremco Roofing and Building
Maintenance is part of Tremco
Construction Products Group.

Tremco is a US Registered trademark of Tremco CPG Inc.

The information provided on this data page supersedes all previous data concerning this product and its application.

The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Tremco DOES NOT MAKE NOR DOES IT AUTHORIZE ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO TREMCO'S PRODUCT SAMPLE. Buyer and user accept the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handling, storage or use of the product, whether or not it is handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCE SHALL TREMCO BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY. IN ALL CASES, TREMCO'S LIABILITY IS LIMITED, AT TREMCO'S OPTION, TO THE REPLACEMENT OF GOODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING.