

SAFETY DATA SHEET

1. Identification

Material name: TREM-LAR LRM-H 5 US GL

Material: 351506 805

Recommended use and restriction on use

Recommended use: Coatings

Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco Incorporated
3735 Green Road
BEACHWOOD OH 44122
US

Contact person:

EH&S Department

Telephone:

216-292-5000

Emergency telephone number:

1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable liquids Category 4

Health Hazards

Acute toxicity (Inhalation - dust and mist) Category 4

Respiratory sensitizer Category 1

Germ Cell Mutagenicity Category 1B

Carcinogenicity Category 1A

Unknown toxicity - Health

Acute toxicity, oral 30.23 %

Acute toxicity, dermal 41.78 %

Acute toxicity, inhalation, vapor 99.96 %

Acute toxicity, inhalation, dust or mist 72.49 %

Label Elements

Hazard Symbol:



Signal Word:	Danger
Hazard Statement:	Combustible liquid. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause genetic defects. May cause cancer.
Precautionary Statements	
Prevention:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. [In case of inadequate ventilation] wear respiratory protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. Call a POISON CENTER/doctor if you feel unwell. In case of fire: Use... to extinguish.
Storage:	Store in a well-ventilated place. Keep cool. Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Hazard(s) not otherwise classified (HNOC):	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

3. Composition/information on ingredients
--

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
-------------------	------------	-------------------------

Aromatic process oil	64741-62-4	15 - 40%
Calcium Carbonate (Limestone)	1317-65-3	15 - 40%
Calcium oxide	1305-78-8	3 - 7%
Stoddard solvent (Mineral Spirits)	8052-41-3	3 - 7%
Carbon Black	1333-86-4	1 - 5%
Hydrotreated heavy naphthenic distillate	64742-52-5	0.5 - 1.5%
Tosyl isocyanate	4083-64-1	0.1 - 1%
1,2,4-Trimethylbenzene	95-63-6	0.1 - 1%
Trimethyl benzene (mixed isomers)	25551-13-7	0.1 - 1%
Dibutyl tin dilaurate	77-58-7	0.1 - 1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Rinse mouth thoroughly.
Inhalation:	Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give oxygen.
Skin Contact:	Remove contaminated clothing and wash the skin thoroughly with soap and water after work.
Eye contact:	Rinse immediately with plenty of water.
Most important symptoms/effects, acute and delayed	
Symptoms:	Respiratory tract irritation.
Indication of immediate medical attention and special treatment needed	
Treatment:	Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards:	Move containers from fire area if you can do so without risk.
Suitable (and unsuitable) extinguishing media	
Suitable extinguishing media:	Use fire-extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media:	Avoid water in straight hose stream; will scatter and spread fire.
Specific hazards arising from the chemical:	During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away.

Methods and material for containment and cleaning up: Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures: In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions: Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling: Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe dust/fume/gas/mist/vapors/spray. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities: Store locked up. Store in a well-ventilated place. Store in a cool place.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Stoddard solvent (Mineral Spirits)	TWA	100 ppm	US. ACGIH Threshold Limit Values (2011)

	PEL	500 ppm 2,900 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values (2011)
Carbon Black	PEL	3.5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values (03 2014)
Hydrotreated heavy naphthenic distillate	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Hydrotreated heavy naphthenic distillate - Mist.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
1,2,4-Trimethylbenzene	REL	25 ppm 125 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	TWA	25 ppm 125 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	25 ppm 125 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	AN ESL	25 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	ST ESL	140 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (02 2013)
	ST ESL	700 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (02 2013)
	AN ESL	125 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (07 2011)
	TWA PEL	25 ppm 125 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (08 2010)
	TWA	25 ppm	US. ACGIH Threshold Limit Values (2011)
Trimethyl benzene (mixed isomers)	TWA	25 ppm	US. ACGIH Threshold Limit Values (2011)
Dibutyl tin dilaurate - as Sn	STEL	0.2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	TWA	0.1 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	0.1 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	Type	Exposure Limit Values	Source
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)

Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Calcium oxide	TWA	2 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWA	2 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Stoddard solvent (Mineral Spirits)	STEL	580 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	290 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Stoddard solvent (Mineral Spirits)	TWA	100 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Stoddard solvent (Mineral Spirits)	TWA	100 ppm 525 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Carbon Black - Inhalable	TWA	3 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (09 2011)
Carbon Black - Inhalable fraction.	TWA	3 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Carbon Black	TWA	3.5 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
	TWA	1 mg/m ³	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Inhalable fraction.	TWA	5 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
	TWA	5 mg/m ³	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (06 2015)
Hydrotreated heavy naphthenic distillate - Mist.	STEL	10 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	TWA	5 mg/m ³	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

1,2,4-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) (07 2009)
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
1,2,4-Trimethylbenzene	TWA	25 ppm	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
1,2,4-Trimethylbenzene	TWA	25 ppm 123 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Appropriate Engineering Controls Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

General information: Use personal protective equipment as required.

Eye/face protection: Wear goggles/face shield.

Skin Protection

Hand Protection: Use suitable protective gloves if risk of skin contact.

Other: No data available.

Respiratory Protection: If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or manufacturer for specific information.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. When using do not smoke.

9. Physical and chemical properties

Appearance

Physical state: liquid

Form: liquid

Color: Black

Odor: Mild petroleum/solvent

Odor threshold: No data available.

pH: No data available.

Melting point/freezing point: No data available.

Initial boiling point and boiling range: No data available.

Flash Point: 66 °C 150 °F (Setaflash Closed Cup)

Evaporation rate: Slower than Ether

Flammability (solid, gas): No

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.
Relative density:	1.35
Solubility(ies)	
Solubility in water:	Practically Insoluble
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Heat, sparks, flames.
Incompatible Materials:	Alcohols. Amines. Strong acids. Strong bases. Water, moisture.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information**Information on likely routes of exposure**

Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.
Skin Contact:	Moderately irritating to skin with prolonged exposure.
Eye contact:	Eye contact is possible and should be avoided.
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix: 15,516.36 mg/kg

Dermal

Product: ATEmix: 10,453.37 mg/kg

Inhalation

Product: ATEmix: 3.6 mg/l

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Calcium oxide in vivo (Rabbit): Irritating Read-across from supporting substance (structural analogue or surrogate), Key study

Carbon Black in vivo (Rabbit): Not irritant Experimental result, Key study

Hydrotreated heavy naphthenic distillate in vivo (Rabbit): Not irritant Experimental result, Key study

1,2,4-Trimethylbenzene in vivo (Rabbit): Irritating Read-across from supporting substance (structural analogue or surrogate), Key study

Dibutyl tin dilaurate In vitro (Human, in vitro reconstituted epidermis model): Not irritant Experimental result, Supporting study

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Carbon Black Rabbit, 24 - 72 hrs: Not irritating

Hydrotreated heavy naphthenic distillate Rabbit, 24 hrs: Not irritating

1,2,4-Trimethylbenzene Rabbit, 30 min: Not irritating

Dibutyl tin dilaurate Rabbit, 24 hrs: Highly irritating

Respiratory or Skin Sensitization

Product: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause sensitization by inhalation.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Aromatic process oil Overall evaluation: Possibly carcinogenic to humans. Overall evaluation: Possibly carcinogenic to humans.

Carbon Black Overall evaluation: Possibly carcinogenic to humans.

Hydrotreated heavy naphthenic distillate Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall evaluation: Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Hydrotreated heavy naphthenic distillate Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro
Product: No data available.

In vivo
Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

1,2,4-Trimethylbenzene LC 50 (Fathead minnow (*Pimephales promelas*), 96 h): 7.19 - 8.28 mg/l Mortality

Dibutyl tin dilaurate LC 50 (Ide, silver or golden orfe (*Leuciscus idus*), 48 h): 2 mg/l Mortality

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Trimethyl benzene LC 50 (Daggerblade grass shrimp (*Palaemonetes pugio*), 24 h): 7 mg/l Mortality (mixed isomers)

Dibutyl tin dilaurate EC 50 (Water flea (*Daphnia magna*), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Aromatic process oil NOAEL (*Oncorhynchus mykiss*, 28 d): 0.1 mg/l QSAR QSAR, Key study

Hydrotreated heavy naphthenic distillate NOAEL (*Oncorhynchus mykiss*, 14 d): >= 1,000 mg/l QSAR QSAR, Supporting study

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Stoddard solvent (Mineral Spirits) Log Kow: 3.16 - 7.15

Dibutyl tin dilaurate Log Kow: 3.12

Mobility in soil: No data available.

Other adverse effects: No data available.

13. Disposal considerations

Disposal instructions: Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Chemical Identity

P-chlorobenzotrifluoride

Reportable quantity

De minimis concentration: TSCA 4% One-Time Export Notification only.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
2,4-Toluene diisocyanate	100 lbs.
Chrysene	100 lbs.
Cumene	5000 lbs.
Naphthalene	100 lbs.
Toluene-2,6-Diisocyanate	100 lbs.
Benzo(a)pyrene	1 lbs.
Ethylbenzene	1000 lbs.
Chlorobenzene	100 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)**Hazard categories**Fire Hazard
Immediate (Acute) Health Hazards
Delayed (Chronic) Health Hazard**SARA 302 Extremely Hazardous Substance**

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
2,4-Toluene diisocyanate	100 lbs.	500 lbs.
Toluene-2,6-Diisocyanate	100 lbs.	100 lbs.

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
2,4-Toluene diisocyanate	100 lbs.
Chrysene	100 lbs.
Cumene	5000 lbs.
Naphthalene	100 lbs.
Toluene-2,6-Diisocyanate	100 lbs.
Benzo(a)pyrene	1 lbs.
Ethylbenzene	1000 lbs.
Chlorobenzene	100 lbs.

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
2,4-Toluene diisocyanate	500lbs
Toluene-2,6-Diisocyanate	100lbs
Aromatic process oil	10000 lbs
Calcium Carbonate (Limestone)	10000 lbs
Calcium oxide	10000 lbs
Stoddard solvent (Mineral Spirits)	10000 lbs
Carbon Black	10000 lbs
Hydrotreated heavy naphthenic distillate	10000 lbs
Tosyl isocyanate	10000 lbs
1,2,4-Trimethylbenzene	10000 lbs
Trimethyl benzene (mixed isomers)	10000 lbs
Dibutyl tin dilaurate	10000 lbs

SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

<u>Chemical Identity</u>	<u>Reportable quantity</u>
2,4-Toluene diisocyanate	lbs
Toluene-2,6-Diisocyanate	lbs

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65



WARNING
Cancer - www.P65Warnings.ca.gov

US. New Jersey Worker and Community Right-to-Know Act

<u>Chemical Identity</u>
Aromatic process oil
Calcium Carbonate (Limestone)
P-chlorobenzotrifluoride
Calcium oxide
Stoddard solvent (Mineral Spirits)
Carbon Black
Hydrotreated heavy naphthenic distillate

US. Massachusetts RTK - Substance List**Chemical Identity**

Calcium Carbonate (Limestone)
Calcium oxide
Stoddard solvent (Mineral Spirits)
Carbon Black
2,4-Toluene diisocyanate
Chrysene
Toluene-2,6-Diisocyanate
Benzo(a)pyrene
Crystalline Silica (Quartz)/ Silica Sand

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Calcium Carbonate (Limestone)
Calcium oxide
Stoddard solvent (Mineral Spirits)
Carbon Black

US. Rhode Island RTK**Chemical Identity**

Calcium Carbonate (Limestone)
Calcium oxide
Stoddard solvent (Mineral Spirits)
Carbon Black

International regulations**Montreal protocol**

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

VOC:

Regulatory VOC (less water and
exempt solvent) : 95 g/l
VOC Method 310 : 6.36 %

Inventory Status:

Australia AICS:	One or more components in this product are not listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	All components in this product are listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	One or more components in this product are not listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	All components in this product are listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	One or more components in this product are not listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	All components in this product are listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.

16. Other information, including date of preparation or last revision

Revision Date:	11/30/2018
Version #:	1.2
Further Information:	No data available.

Disclaimer:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

