

Version 1. Print Date 04/11/2011

REVISION DATE: 03/30/2011

SECTION 1 - PRODUCT IDENTIFICATION

Trade name : LOW RISE FOAM INSUL. ADHESIVE PART "A"

Product code : 362300A405

COMPANY : Tremco Incorporated

3735 Green Road Cleveland, OH 44122

Telephone : (216) 292-5000 8:30 - 5:00 EST Emergency Phone: : (216) 765-6727 8:30 - 5:00 EST

After Hours: Chemtrec 1-800-424-9300

Product use : Joint filler

SECTION 2 - HAZARDS IDENTIFICATION

Emergency Overview

Brown to Black. Liquid solution. Vapor and/or mist may irritate nose and throat. May cause allergic respiratory sensitization. Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

Acute Potential Health Effects/ Routes of Entry

Inhalation : Vapor and/or mist may irritate nose and throat. May cause allergic respiratory

sensitization.

Eyes : Vapor and/or mist may cause eye irritation. May cause sensitization.

Ingestion : May cause irritation to the mouth, throat and stomach. May cause gastrointestinal

irritation, nausea, and vomiting.

Skin : May cause sensitization resulting in irritation, itching and redness.

Aggravated Medical Conditions

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Overexposure may cause dermatitis, asthma, skin and respiratory sensitization and decreased lung function. Diphenylmethane diisocyanate (methylene bisphenyl isocyanate) caused an increased incidence of lung tumors in experimental animals following long term inhalation at concentrations in excess of 100 times the exposure limit. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

Target Organs: Lung, Skin, Eye

SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %	
4,4'-Methylene bis(phenylisocyanate)	101-68-8	40.0 - 70.0	
Polymethylene polyphenyl isocyanate	9016-87-9	40.0 - 70.0	
Diphenylmethane diisocyanate	26447-40-5	3.0 - 7.0	



Version 1. Print Date 04/11/2011

REVISION DATE: 03/30/2011

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

Inhalation : Move to fresh air. If required, artificial respiration or administration of oxygen can be

performed by trained personnel. Leave area to breathe fresh air. Avoid further

overexposure. If symptoms persist, get medical attention.

Eye contact : Flush with water for at least 15 minutes while holding eye lids apart. Get medical

attention immediately.

Skin contact : Wash area of contact thoroughly with hand cleaner followed by soap and water. If

irritation, rash or other disorders develop, get medical attention immediately.

Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control

Center or Physician immediately.

SECTION 5 - FIRE FIGHTING MEASURES

Flash point : $> 350 \, ^{\circ}\text{F}, > 177 \, ^{\circ}\text{C}$

Method : Pensky-Martens Closed Cup

Lower explosion limit : Not available.

Upper explosion limit : Not available.

Autoignition temperature : Not available.

Extinguishing media : If water fog is ineffective, use carbon dioxide, dry chemical or foam.

Hazardous combustion

products

Carbon monoxide and carbon dioxide can form. Smoke, fumes. Hydrocyanic acid and nitrogen oxides can form.

Protective equipment for

firefighters

Use accepted fire fighting techniques. Wear full firefighting protective

clothing, including self-contained breathing apparatus (SCBA).

Fire and explosion conditions : This product not expected to ignite under normal conditions of use.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Absorb spill in sand, earth or other suitable material. Transfer to appropriate container for disposal.

SECTION 7 - HANDLING AND STORAGE

Store under normal warehouse conditions. Change soiled work clothes frequently. Clean hands thoroughly after handling. Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection equipment





Version 1. Print Date 04/11/2011

REVISION DATE: 03/30/2011

Respiratory protection : Use full engineering controls before relying on personal protective

equipment. Wear appropriate, properly fitted air purifying respirator with combination particulate filter and vapor/gas removing cartridge when airborne contaminant level(s) exceed exposure limits indicated on the MSDS, or

product is spray applied.

Hand protection : Use suitable impervious nitrile or neoprene gloves and protective apparel to

reduce exposure.

Eye protection : Wear appropriate eye protection. Wear chemical safety goggles and/or face

shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily

available.

Skin and body protection : Prevent contact with shoes and clothing.

Protective measures : Use professional judgment in the selection, care, and use.

Engineering measures : Use only in well ventilated areas. Provide maximum ventilation in enclosed

areas.Use general ventilation and/ or local exhaust to reduce the airborne contaminant concentration below the exposure limit listed in the MSDS

Exposure Limits

Chemical Name	CAS Number	Regulation	<u>Limit</u>	<u>Form</u>
4,4'-Methylene	101-68-8	ACGIH TWA:	0.005 ppm	
bis(phenylisocyanate)				
Polymethylene	9016-87-9	ACGIH TWA:	0.005 ppm	
polyphenyl isocyanate				

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form : Liquid solution Color : Brown to Black Odor **Faint Aromatic** Not available. рΗ Vapour pressure Not available. Vapor density : Heavier than air : Not available. Melting point/range Freezing point : Not available. Boiling point/range : Not available. Water solubility : Reacts with water

Specific Gravity : 1.22 % Volatile Weight : 0 %

SECTION 10 - REACTIVITY / STABILITY

Substances to avoid : Strong acids. Strong bases. Amines. Water or moisture. Alcohols.

Stability : Material is stable under normal storage, handling, and use.

An RPIT Company 3/5



Version 1. Print Date 04/11/2011

REVISION DATE: 03/30/2011

Hazardous polymerization : Will not occur under normal conditions.

SECTION 11 - TOXICOLOGICAL INFORMATION

4,4'-Methylene bis(phenylisocyanate), CAS-No.: 101-68-8

Acute inhalation toxicity (LC-50) 0.369 mg/l for 4 h (Rat) 0.38 mg/l for 4 h (Rat)

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Method : Subject to hazardous waste treatment, storage, and disposal requirements under

RCRA. Recycle or incinerate waste at EPA approved facility or dispose of in

compliance with federal, state and local regulations.

SECTION 14 - TRANSPORTATION / SHIPPING DATA

TDG / DOT Shipping Description:

NOT REGULATED

SECTION 15 - REGULATORY INFORMATION

North American Inventories:

All components are listed or exempt from the TSCA inventory.

This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

U.S. Federal Regulations:

SARA 313 Components : 4,4'-Methylene bis(phenylisocyanate) 101-68-8

Polymethylene polyphenyl isocyanate 9016-87-9

SARA 311/312 Hazards : Acute Health Hazard

OSHA Hazardous Components:

4,4'-Methylene bis(phenylisocyanate) 101-68-8 Polymethylene polyphenyl isocyanate 9016-87-9

OSHA Status: Considered : Irritant hazardous based on the Sensitizer

following criteria:

OSHA Flammability : IIIB

When appropriately mixed with the other part, product has a VOC less water and exempt solvent of:

0 a/l





101-68-8

101-68-8

LOW RISE FOAM INSUL. ADHESIVE PART "A"

Version 1. Print Date 04/11/2011

REVISION DATE: 03/30/2011

Regulatory VOC (less water and : 0 g/l

exempt solvent)

VOC Method 310 : 0 %

U.S. State Regulations:

MASS RTK Components : 4,4'-Methylene bis(phenylisocyanate) 101-68-8

Polymethylene polyphenyl isocyanate 9016-87-9

Penn RTK Components : 4,4'-Methylene bis(phenylisocyanate)

Polymethylene polyphenyl isocyanate 9016-87-9 Diphenylmethane diisocyanate 26447-40-5

NJ RTK Components : 4,4'-Methylene bis(phenylisocyanate)

Polymethylene polyphenyl isocyanate 9016-87-9 Diphenylmethane diisocyanate 26447-40-5

Components under California Proposition 65:

None known.

SECTION 16 - OTHER INFORMATION

HMIS Rating:

Health	1	0 = Minimum
Flammability	1	1 = Slight
Reactivity	0	2 = Moderate
PPE		3 = Serious
		4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

Legend

ACGIH - American Conference of Governmental Hygienists

CERCLA - Comprehensive Environmental Response, Compensation, and

iability Act

DOT - Department of Transportation

DSL - Domestic Substance List

EPA - Environmental Protection Agency HMIS - Hazardous Materials Information System

IADO Laternational Assess to December One

IARC - International Agency for Research on Cancer

MSHA - Mine Safety Health Administration

NDSL - Non-Domestic Substance List

NIOSH - National Institute for Occupational Safety and Health

NTP - National Toxicology Program

OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit

RCRA - Resource Conservation and Recovery Act

RTK - Right To Know

SARA - Superfund Amendments and Reauthorization Act

STEL - Short Term Exposure Limit

TLV - Threshold Limit Value
TSCA - Toxic Substances Control Act

TWA - Time Weighted Average

V - Volume

VOC - Volatile Organic Compound

WHMIS - Workplace Hazardous Materials Information

System

