



SUBMITTAL SHEET

Rigid Jumbo Corner Bead



Stock #	Length	Pcs/Box
RJ08	8'	35
RJ10	10'	35

Rigid Jumbo Archway Corner Bead



Stock #	Length	Pcs/Box	
RJA10	10'	35	

Product(s): Rigid Jumbo Corner Bead & Archway

Description: Trim-Tex Rigid Jumbo Corner Bead features patented I-Beam technology and extra wide mud legs. The I-Beam also creates a sharp distinctive outside corner that is easier to mud and creates clean lines for paint transitions. Also available in archway for curved surfaces that can finish a 16" inside or up to 24" outside radius.

Advantages: Qualifies for LEED® points. Made from rust proof, dent resistant PVC to reduce job site and handling damage. Safer than sharp square metal corners. The clean, crisp mud bump is consistent across a complete line of Trim-Tex Architectural Series Beads to meet your drywall finishing needs.

Limitations: Product is designed for interior use.

Applicable Standards: Rigid PVC products made by Trim-Tex meet ASTM specifications D3678-97, D1784-03, C1047-99 and achieve a Class A rating for flame spread and smoke developed when tested under ASTM E84-10.

Surface Characteristics: Trim-Tex products are made from PVC. PVC does not support combustion and is self extinguishing when the source of flame or heat is removed.

Installation: Snip the bead to length and dry fit. Install with Trim-Tex 847 Spray Adhesive and $\frac{1}{2}$ " divergent staples. Detailed installation instructions are included with each product.

Finishing: To improve the bondability of drywall compounds, textures, & plaster products to any bead, use MUD-MAX Drywall Compound Additive. For texture finishes, TEX11 Texture Prep is recommended on beads with exposed PVC surfaces such as Bullnose, Super L Beads and Fast Caps. Priming is not required. Always use a high quality paint. North Safety Products are distributed by Trim-Tex.

Job Name			
Contractor	<u></u>	Date	
	Approvals (Signa	atures or Stamps	3)