

SECTION 09 51 00 – USG COMPÄSSO™ TRANSITIONS ALUMINUM PERIMETER TRIM

Product Summary:

- USG Compässo™ Elite Transitions are extruded aluminum trims for creating elevation change fascias between differing ceiling planes.
- Easier to install than conventional drywall fascias.
- Compatible with all USG Donn® Brand Suspension Systems and USG Drywall Suspension Systems.
- Works with USG Compässo™ Elite attachment clips and splice plates.
- Call <insert product representative here> or 800.874.4968 for technical questions.

Note to Specifier:

- This document is not intended to function as a standalone specification. It is intended to assist the specifier in inserting the proper language into the following recommended specification sections:
 - 09 51 13 Acoustical Panel Ceilings, Accessories.
 - 09 51 23 Acoustical Tile Ceilings, Accessories.
 - 09 51 33 Acoustical Metal Pan Ceilings, Accessories.
 - 09 54 23 Linear Metal Ceilings, Accessories.

2.6 METAL EDGE ACOUSTICAL TO ACOUSTICAL TILE TRIM <Insert material designation>.

- A. Provide USG Compässo™ Elite AAS Transitions extruded aluminum edge moldings and trim: where indicated. The aluminum trim will feature smooth visible face. The non-visible face shall include extruded bosses to accommodate Compässo™ Elite attachment clips that attach trim to adjacent ceiling grid. At vertical butt joints between adjacent trim pieces, utilize Compässo™ splice clips. Prefabricated corner pieces accommodate inwards and outwards 90 degree corners.
- B. Acoustical to Acoustical transition trim basis of design: Subject to compliance with project requirements, the design is based on the following: USG Interiors, LLC, “USG COMPÄSSO™ ELITE AAS ALUMINUM TRIM”.
1. Trim Height: [ALSFTACAC210 2” (51 mm)] [ALSFTACAC310 3” (75 mm)] [ALSFTACAC410 4” (102 mm)] [ALSFTACAC510 5” (125 mm)] [ALSFTACAC610 6” (152 mm)]
 2. Trim Depth: 0.68” (17 mm).
 3. Trim Length: 10’-0” (3048 mm).
 4. Color: Standard flat white 050.
- C. Accessories:
1. Compässo™ Elite Attachment Clip; attaches grid to backside bosses on Compässo™ Elite Trim.
 2. Splice Plate: steel in finish to match trim pans; formed for snap-fit into pan ends, for use at cut ends of metal ceilings.
 3. 90° corner trim pieces: to match Compässo™ Elite AAS Suspension Trim.
 - a. USG Ceilings Compässo™ Elite Transitions Suspension Trim, 90 degree Inside Corner: [AAS 2”] [AAS 3”] [AAS 4”] [AAS 5”] [AAS 6”] <insert color here>.
 - b. USG Ceilings Compässo™ Elite Transitions Suspension Trim, 90 degree Outside Corner: [AAS 2”] [AAS 3”] [AAS 4”] [AAS 5”] [AAS 6”] <insert color here>.

2.7 METAL EDGE DRYWALL LOWER TO ACOUSTICAL UPPER TRIM <Insert material designation>.

- A. Provide USG Compässo™ Elite DAS Transitions extruded aluminum edge moldings and trim: where indicated. The aluminum trim will feature smooth visible face with drywall bead trim on lower face. The non-visible face shall include extruded bosses to accommodate Compässo™ Elite attachment clips that attach trim to adjacent ceiling grid. At vertical butt joints between adjacent trim pieces, utilize Compässo™ splice clips. Prefabricated corner pieces accommodate inwards and outwards 90 degree corners.
- B. Drywall lower to acoustical upper transition trim basis of design: Subject to compliance with project requirements, the design is based on the following: USG Interiors, LLC, “USG COMPÄSSO™ ELITE DAS ALUMINUM TRIM”.
1. Trim Height: [ALSFTDWAC210 2” (51 mm)] [ALSFTDWAC410 4” (102 mm)] [ALSFTDWAC610 6” (152 mm)].
 2. Trim Depth: N/A.
 3. Trim Length: 10’-0” (3048 mm).
 4. Color: standard flat white 050.
- C. Accessories:
1. Compässo™ Elite Attachment Clip; attaches grid to backside bosses on Compässo™ Elite Trim.
 2. Splice Plate: steel in finish to match trim pans; formed for snap-fit into pan ends, for use at cut ends of metal ceilings.
 3. 90° corner trim pieces: to match Compässo™ Elite DAS Suspension Trim.
 - a. USG Ceilings Compässo™ Elite Transitions Suspension Trim, 90 degree Inside Corner: [DAS 2”] [DAS 4”] [DAS 6”] <insert color here>.
 - b. USG Ceilings Compässo™ Elite Transitions Suspension Trim, 90 degree Outside Corner: [DAS 2”] [DAS 4”] [DAS 6”] <insert color here>.

END OF SECTION

Disclaimer: The USG Product Specifications contained herein are intended for use as product reference material by architects, engineers, other design professionals, contractors, building code officials, or other competent construction industry trade professionals having an interest in the selection, specification and use of products manufactured by the subsidiaries of USG Corporation. The Specifications are intended solely as technical support incident to the sale and use of USG products and not intended to be a substitute for the design review and approval of the licensed design professionals for the project. These materials may be printed and/or transferred electronically solely as needed by the user. Because electronic text files can be modified by other parties, without notice or indication of such modifications, modification of USG Product Guide Specifications and Drawings is the sole responsibility of the Design Professional.