USG Ceiling Solutions

USG DONN[®] BRAND ADVANCESPAN[™]

USG DONN[®] BRAND DXAS[™] AND DXTAS[™] PROFILES



FEATURES AND BENEFITS

- Spans up to 8' with no hanger wires.
- Ideal for healthcare, hospitality and multifamily applications with crowded plenum spaces.
- Seismic installation designs validated in ICC-ES Evaluation Report ESR-5136.
- Approved by OSHPD/HCAi for seismic applications.
- USG Donn[®] Brand DX[®]-15/16" and USG Donn[®] Brand Centricitee[™] DXT[™]-9/16" face profiles available.
- Reversible structural wall channel works with both USG DX® and DXT[™] profiles.
- Compatible with all standard USG DX[®] and DXT[™] cross tees.
- Available with End Splice detail to speed up installation.
- USG Donn[®] Brand AdvanceSpan[™] Suspension System is part of the Ecoblueprint™ portfolio — meeting today's sustainability standards. For sustainability documentation go to USG.com or CGCInc.com.

APPLICATIONS

- Schools
- Hospitals
- Multifamily dwellings
- Hotels
- General interior use applications



























Shadowline Beveled

Square Edge

USG DONN[®] BRAND DXTAS[™] EDGE PROFILES







Fineline: Bevel



Fineline



USG DONN[®] BRAND ADVANCESPAN[®]

USG DONN[®] BRAND DXAS[™] AND DXTAS[™] PROFILES



TECHNICAL SERVICES 800 USG.4YOU (874-4968) FOR MOST UP-TO-DATE TECHNICAL INFORMATION AND LEED REPORT TOOL usgdesignstudio.com cgcdesignstudio.com

YEAR LIMITED SYSTEM WARRANTY • No Visible Sag • Mold/Mildew Protection

30



Declare* Labels on select finishes, see usg.com for more details and documentation.

			Max Unsupported Span at Rated Load						
	Item No	Fire Rating	Intermediate Duty (12 lb./LF)	Heavy Duty (16 lb./LF)	Recycled Content	Face Profile	Height	Standard Lengths	Color
					3				
MAIN TEE	DXAS	Class A	8'-0"	7'-0"	HRC	15/16"	2-3/4"	8'-6" 10'-6" 12'-6"	Flat White 05
	DXTAS	Class A	8'-0"	7'-0"	HRC	9/16"	2-3/4"	8'-6" 10'-6" 12'-6"	Flat White 05
	DXTAS-ES	Class A	8'-0"	7'-0"	HRC	9/16"	2-3/4"	10'-0" 12'-0"	Flat White 05
	DXAS-ES	Class A	8'-0"	7'-0"	HRC	15/16"	2-3/4"	10'-0" 12'-0"	Flat White 05
LLL CHANNEL MOLDING	US44	Class A	- modified.	-	HRC	Reversible for 15/16" or 9/16"	2-7/8"	10'	Flat White 05
	Low Emis	sions (VOC)		High Recycled Cont		nt as greater that	50% Total	ecycled content	is based
ACCESSODIES	CDPH 013 on select finis more details a	50 v1.2-2017 co hes, see usg.cor Ind documentat	mpliance for on p	USG classifies High R roduct composition TC guidelines.	ecycled Conte of postconsum		mer (postino	dustrial) recycled	
ACCESSORIES	CDPH 013 on select finis	50 v1.2-2017 co hes, see usg.cor Ind documentat	mpliance for on p	USG classifies High R roduct composition	ecycled Conte of postconsum			dustrial) recycled	
ACCESSORIES USG DONN® BRAND ADVANCESPAN™ MAIN TEE DETAILS	CDPH 013 on select finis more details a ASMTSP Splice	550 v1.2-2017 co hes, see usg.cor ind documentat Plate	mpliance on p in for on p per F	USG classifies High R roduct composition of TC guidelines.	tecycled Conte of postconsum ip		mer (postino	s Brace Clip	d content
USG DONN* BRAND ADVANCESPAN™	CDPH 013 on select finis more details a ASMTSP Splice	550 v1.2-2017 co hes, see usg.cor ind documentat	mpliance on p rion. per F	USG classifies High R roduct composition of TC guidelines. US44CC Channel Cl 0 0 126", & 150" Standard Ler	tecycled Conte of postconsum ip		mer (postino	s Brace Clip	d content

© 2023 USG Corporation and/or its affiliates. All rights reserved. Printed in U.S.A.
 Manufactured by
 The trademarks USG, CGC, ADVANCESPAN, CENTRICITEE, DONN, USG Interiors, LLC
 DX, DXAS, DXT, DXTAS, ECOBLUEPRINT, MARS, IT'S YOUR WORLD

 550 West Adams Street
 BUILD IT, the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate persona protective equipment. Read SDS and literature before specification and installation.

