

# USG DONN® BRAND DXSS™ ACOUSTICAL SUSPENSION SYSTEM


USG Donn® Brand DXSS™  
Acoustical Suspension System/  
USG Sheetrock® Brand Lay-In  
Acoustical Ceiling Panels with  
ClimaPlus™ Performance

TO ORDER SAMPLES, GO TO [USG.COM](http://USG.COM) OR [CGCINC.COM](http://CGCINC.COM)




Stainless  
Steel

#### PROFILE



#### EDGE DETAIL



#### FEATURES AND BENEFITS

- 15/16" stainless steel grid system with stainless steel cap.
- Resistant to direct and indirect contact with many corrosive agents.
- Stainless steel Quick-Release™ clips on cross tees.
- Nonmagnetic.
- Cross-tee override-ends resist twisting.
- Meets USDA/FSIS requirements.
- Cap material is protected with removable film, reducing post construction cleaning.

#### APPLICATIONS

- Food processing areas
- Industrial applications
- Laboratories

# USG DONN® BRAND DXSS™ ACOUSTICAL SUSPENSION SYSTEM


ORDER SAMPLES/LITERATURE  
USG: usg.com or samplitt@usg.com  
CGC: contact Sales Representative

TECHNICAL SERVICES  
800.USG.4YOU (874-4968)


FOR MOST UP-TO-DATE  
TECHNICAL INFORMATION  
AND LEED REPORT TOOL  
usgdesignstudio.com  
cgcdesignstudio.com

30 YEAR LIMITED SYSTEM  
WARRANTY  
• No Visible Sag  
• Mold/Mildew Protection


## 15/16" TEE SYSTEM Main Tee 1-1/2"



## Cross Tee 1-1/2"



## MOLDING



## PHYSICAL DATA/ FOOTNOTES

ASTM Class	Length	Height	Item No.	Fire Rating	Color	Recycled Content	Minimum Load Carrying Capabilities—Main tee¹		
							2' Hanger Spacing	3' Hanger Spacing	4' Hanger Spacing
Light Duty	12'	1-1/2" 38 mm	DXSS24	Class A	Stainless Steel	up to 50%	70 lb./LF	28.6 lb./LF	12 lb./LF
	2'	1-1/2" 38 mm	DXSS224	Class A	Stainless Steel	up to 50%			
	4'	1-1/2" 38 mm	DXSS424	Class A	Stainless Steel	up to 50%			
Wall Angle	Length	Item No.		Color	Recycled Content				
	12'	M7SS		Stainless Steel	up to 50%				

**Product literature and samples**  
Data sheet: AC3068  
Sample: 215671

**Material**  
Double-web Type 304 chromium-nickel austenitic alloy stainless steel body, cap and clip. This cap material is protected by PVC, which should be removed after installation.

**Online tools**  
usgdesignstudio.com or cgcdesignstudio.com

**Installation**  
Install according to ASTM C636, ASTM E580, CISCA and USG requirements. Alternate installation methods may be used when approved by the authority having jurisdiction.

**ASTM Load Compliance**  
Classified as Light, Intermediate or Heavy Duty when tested in accordance with ASTM C635.

**Notes**  
1. Rated Load expressed in lb./LF based on simple span tests in accordance with ASTM E3090 with deflection limit of L/360. Duty rating is assigned based on rated load per ASTM C635.

**Notice**  
The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

AC3068/rev. 10-23  
© 2023 USG Corporation and/or its affiliates. All rights reserved. Printed in U.S.A.

Manufactured by USG Interiors, LLC  
550 West Adams Street  
Chicago, IL 60661

The trademarks USG, CGC, CLIMAPLUS, DONN, DXSS, QUICKRELEASE, SHEETROCK, IT'S YOUR WORLD. BUILD IT., the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

