

# USG DONN® BRAND DXW™ ACOUSTICAL SUSPENSION SYSTEM


USG Donn® Brand DXW™  
Acoustical Suspension System/  
USG Eclipse™ Acoustical Panels with  
ClimaPlus™ Performance

TO ORDER SAMPLES, GO TO [USG.COM](http://USG.COM) OR [CGCINC.COM](http://CGCINC.COM)

## STANDARD COLORS



## POWDER-COATED FINISH




## FEATURES AND BENEFITS

- 1-1/2" exposed grid system. Design alternative for high-bay areas and large panel modules.
- Cross-tee override-ends resist twisting.
- Complies with all national code requirements.
- Proprietary Quick-Release™ cross tees.
- Custom colors available.
- ICC-ES evaluated for seismic installations (ESR-1222).


## APPLICATIONS

- Interior general-use areas
- High-bay areas
- Large-module ceilings

## PROFILE



## EDGE DETAIL



# USG DONN® BRAND DXW™ ACOUSTICAL SUSPENSION SYSTEM

ORDER SAMPLES/LITERATURE  
USG: usg.com or samplitt@usg.com  
CGC: contact Sales Representative


TECHNICAL SERVICES  
800.USG.4YOU (874-4968)

FOR MOST UP-TO-DATE  
TECHNICAL INFORMATION  
AND LEED REPORT TOOL  
usgdesignstudio.com  
cgcdesignstudio.com




**Declare.** Declare® Labels on select finishes, see usg.com for more details and documentation.

## 1-1/2" TEE SYSTEM



## MOLDING<sup>4,5</sup>



## PHYSICAL DATA/ FOOTNOTES

ASTM Class	Length	Height	Item No.	Fire Rating	Color <sup>3</sup>	Seismic Design Category <sup>1,6</sup>		Rated Load <sup>2</sup>		
						IBC	ICC-ES Evaluated Installation	4' Hanger Spacing	5' Hanger Spacing	6' Hanger Spacing
Heavy Duty	12'	1-1/2" 38 mm	DXW26	Class A	Standard	A-F	7/8" Molding ACM7 Clip	16 lb./LF	8.5 lb./LF	5 lb./LF
	2'	1-1/2" 38 mm	DXW224	Class A	Standard	—	—	36.7 lb./LF	—	—
	4'	1-1/2" 38 mm	DXW424	Class A	Standard	—	—	13.8 lb./LF	—	—
Wall Angle	Length	Item No.	Color	Wall Angle	Length	Item No.	Color			
	12'	M7	Standard		10' 3000 mm	M20	Flat White			
	12'	M12	Standard							

**Low Emissions (VOC)**  
CDPH 01350 v1.2-2017 compliance on select finishes, see usg.com for more details and documentation.

**Product literature and samples**  
Data sheet: AC3037  
Sample: 219168

**Material**  
Min. G30 hot-dipped galvanized steel body and cap. Baked-on polyester paint or powder-coated finish.

**Installation**  
Install according to ASTM C636, ASTM E580, Cisca and USG requirements. Alternate installation methods may be used when approved by the authority having jurisdiction.

**Online tools**  
usgdesignstudio.com or cgcdesignstudio.com

**ICC Evaluation Service, LLC Report Compliance**  
For areas under ICC jurisdiction, see ICC-ES Evaluation Report ESR-1222 for allowable values and conditions of use. Reports are subject to reexamination, revision and possible cancellation. Refer to usg.com for most current version.

**ASTM Load Compliance**  
Classified as Heavy Duty when tested in accordance with ASTM C635.

- Notes**
- All USG main tees, cross tees and main tee-hanger wire connections meet AC 368 and ASTM E580 requirements for tension and compression strength, as tested per ASTM E3090.
  - Rated Load expressed in lb./LF based on simple span tests in accordance with ASTM E3090 with deflection limit of L/360. Duty rating is assigned based on rated load per ASTM C635.
  - Custom colors available.
  - For more information on moldings, see Perimeter Interface selector.
  - Panels must be field-cut to size at the perimeter.
  - Seismically tested in accordance with ASTM E3118.

**Notice**  
The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

AC3037/rev. 10-23  
© 2023 USG Corporation and/or its affiliates. All rights reserved. Printed in U.S.A.

Manufactured by USG Interiors, LLC  
550 West Adams Street  
Chicago, IL 60661

The trademarks USG, CGC, CLIMAPLUS, DONN, DXW, ECLIPSE, QUICK-RELEASE, IT'S YOUR WORLD, BUILD IT!, the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

