

USG DUROCK® BRAND CEMENT BOARD WITH EDGEGUARD™ WE HAVE YOUR BACK.

For more than 30 years, USG Durock® Brand Cement Board with EdgeGuard™ panels have set the standard for proven performance in the backerboard category. They're water durable, mold resistant and provide a tile bond superior to both fiber-cement boards and bare plywood. And, with an enhanced, proprietary edge performance that prevents spin out and crumbling, USG Durock® Brand Cement Board with EdgeGuard™ is the perfect choice for a wide variety of interior and exterior applications.

APPLICATIONS:

- Approved for interior and exterior use
- 1/4" for floors and countertops
- 1/2" and 5/8" for walls, countertops and ceilings
- Baths, tubs, gang showers, kitchens, laundry rooms, steam rooms, and indoor pool areas

BASE MATERIAL

Aggregated Portland Cement with polymer-coated fiber-glass mesh completely encompassing edges, back and front surfaces.

WEIGHT PER SQ. FT.

1/4" : 1.9 lbs. psf
1/2" : 2.4 lbs. psf
5/8" : 3.0 lbs. psf

AVAILABLE SIZES (True Thickness)

1/4" x 3' x 5' 5/8" x 3' x 5'
1/2" x 3' x 5' 5/8" x 4' x 8'
1/2" x 4' x 8'

WARRANTY

Interiors : Lifetime (30-year) limited warranty*
Exteriors: 10-year, limited

**This warranty runs for the lifetime for the installation of the product up to a period of thirty (30) years beginning on the date of installation of the product. See usg.com for all terms and conditions.*

800 USG.4YOU
800 (874-4968)
usg.com

United States Gypsum Company
550 West Adams Street
Chicago, IL 60661

CB319271-USA-ENG/11-22
© 2022 USG Corporation and/or its affiliates.
All rights reserved. Printed in U.S.A.

USG FIBEROCK® BRAND TILE BACKERBOARD AND UNDERLAYMENT WE HAVE YOUR BACK.

USG Fiberock® Brand Tile Backerboard and Underlayment is an innovative alternative to traditional cement backers and is easy to install, has superior tile bond and is wet-area approved. The unique, fiber-reinforced, uniform composition gives the panels strength and water resistance through to the core with no risk of delamination.

APPLICATIONS:

- Approved for interior use for floors and countertops including kitchens and bathrooms
- 1/4" and 3/8" for floors and countertops
- .42" & 5/8" for walls, countertops and ceilings
- Approved for use under tile, stone, vinyl, hardwood, laminate and carpet flooring



BASE MATERIAL

An environmentally sustainable, specially engineered combination of gypsum and cellulose fibers.

WEIGHT PER SQ. FT.

- 1/4" : 1.4 lbs. psf
- 3/8" : 1.9 lbs. psf
- .42" : 2.1 lbs. psf
- 5/8" : 3.1 lbs. psf

AVAILABLE SIZES (True Thickness)

- | | |
|----------------|----------------|
| 1/4" x 3' x 5' | .42" x 3' x 5' |
| 1/4" x 4' x 4' | .42" x 4' x 8' |
| 3/8" x 4' x 4' | 5/8" x 3' x 5' |
| 3/8" x 4' x 8' | 5/8" x 4' x 8' |
| 3/8" x 3' x 5' | |

WARRANTY

20-year, limited. See usg.com for all terms and conditions.

800 USG.4YOU
800 (874-4968)
usg.com

United States Gypsum Company
550 West Adams Street
Chicago, IL 60661

CB319271-USA-ENG/11-22
© 2022 USG Corporation and/or its affiliates.
All rights reserved. Printed in U.S.A.