USG ECLIPSE™ ILLUSION™ ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE



USG ECLIPSE™ ILLUSION™ ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE

Panel Size

2'x4'x3/4"

2'x4'x3/4"

Fire

Rating

0

Class A

Class A



Edge

SLT^{3,6}

ILT^{4,6}



Item No.

78785

78085



NRC

0.70

0.70

(UL) UL Classified

CAC

Min.

35

35

ORDER SAMPLES/LITERATURE USG: usg.com or samplit@usg.com CGC: contact Sales Representative

800 USG.4YOU (874-4968)

TECHNICAL INFORMATION AND LEED REPORT TOOL TECHNICAL SERVICES

Recycled

Content¹

82%

82%

usgdesignstudio.com cgcdesignstudio.com usg.ecomedes.com

Panel

\$

\$\$

\$\$

Cost

FOR MOST UP-TO-DATE



VOC

Low

Low

Emissions

Grid

Α

R

Options



Anti-Mold

1

& Mildew

USG ECLIPSE™ ILLUSION™ **TWO/24 PANELS**

PATTERNS

PRODUCT CERTIFIED


FOR LOW CHEMICAL EMISSIONS: UL.COM/GG UI. 2818

USG Eclipse™ Illusion™ Two/24 The look of 2'x2' panels



Low Emissions (VOC)

Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.2 - 2017 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.ecomedes.com and at spot.ul.com.



LR²

0.86

0.86

Color

White


White

Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

High Recycled Content

USG classifies High Recycled Content as greater than 50%. Total recycled content is based on product composition of pre-consumer (post-industrial) and post-consumer recycled content per FTC guidelines.

GRID PROFILE OPTIONS



PHYSICAL DATA

Product literature

ASTM E1264 classification

ASTM E1264-22 Type III, Form 1, Pattern E, I, & K ASTM E1264-23 Type A, Form A1.1, Pattern E, I, & K

ASTM E84 and CAN/ULC S102 surface-burning characteristics

Class A Flame spread: 25 or less Smoke developed: 50 or less

Weight 1.10 lb./sa. ft.

usgdesignstudio.com, cgcdesignstudio.com or usg.ecomedes.com

Thermal resistance

R-2.0

Maximum backloading See *USG 30-Year Limited System Warranty*

Commercial Applications (SC2102).

Can be cleaned easily with a soft brush or vacuum

Metric sizes available

Contact sales for minimum quantities and lead times.

- For details, see USG Sustainability tool at usgdesignstudio.com or cgcdesignstudio.com
- 3. Panels have a 15/16" routing
- 4. Panels have a 9/16" routing.
- 5. Panel face and back surfaces treated with a proprietary, broad-spectrum antimicrobial additive that inhibits and retards the growth of mold/mildew For details, see USG 30-Year Limited System Warranty Commercial Applications (SC2102).
- 6. SLT & ILT Illusion™ edges have a different reveal depth from SLT or FLB edge details. Please reference the System Interface, located in the SC2000, before installing

Notice

The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

SC1846/rev. 3-25

