# **SAFETY DATA SHEET**



1. Identification

Product identifier FIBEROCK® Aqua-Tough™ Underlayment Panels

Other means of identification

**SDS number** 56000000004

Synonyms Fiber-Reinforced Gypsum Panels, Gypsum Fiber Panels (GFP), Gypsum Panels, Drywall,

Plasterboard, Wallboard

Recommended use Interior use

**Recommended restrictions**Use in accordance with manufacturer's recommendations.

Manufacturer / Importer / Supplier / Distributor information

Company name United States Gypsum Company

Address 550 West Adams Street

Chicago, Illinois 60661-3637

Telephone 1-800-874-4968
Website www.usg.com
Emergency phone number 1-800-507-8899

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Not classified.

OSHA defined hazards Not classified.

Label elements

Hazard symbol None.
Signal word None.
Hazard statement None.

**Precautionary statement** 

PreventionObserve good industrial hygiene practices.ResponseGet medical attention/advice if you feel unwell.

**Storage** Store as indicated in Section 7.

**Disposal** Dispose of in accordance with local, state, and federal regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

### 3. Composition/information on ingredients

## **Mixtures**

Chemical name	CAS number	%	
Calcium sulfate dihydrate (alternative CAS 10101-41-4)	13397-24-5	> 90	
Cellulose	9004-34-6	< 10	

**Composition comments** All concentrations are in percent by weight unless ingredient is a gas.

Results of an industrial hygiene study found no airborne respirable crystalline silica in the breathing zones of workers during the normal activities associated with the use of this product. However, job site air monitoring should be conducted when permissible exposure limits may be exceeded.

4. First-aid measures

**Inhalation** Dust irritates the respiratory system, and may cause coughing and difficulties in breathing. Move

injured person into fresh air and keep person calm under observation. Get medical attention if

symptoms persist.

**Skin contact**Contact with dust: Rinse area with plenty of water. Get medical attention if irritation develops or

persists

**Eye contact**Dust in the eyes: Do not rub eyes. Flush thoroughly with water. If irritation occurs, get medical

assistance.

**Ingestion** Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and

delayed

Under normal conditions of intended use, this material does not pose a risk to health. Dust may

irritate throat and respiratory system and cause coughing.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically.

**General information** Ensure that medical personnel are aware of the material(s) involved.

## 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Use fire-extinguishing media appropriate for surrounding materials.

Not applicable.

Specific hazards arising from

the chemical

Not a fire hazard.

Special protective equipment and precautions for firefighters

Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire-fighting

equipment/instructions

Use standard firefighting procedures and consider the hazards of other involved materials.

**Specific methods**Cool material exposed to heat with water spray and remove it if no risk is involved.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

See Section 8 of the SDS for Personal Protective Equipment.

Methods and materials for containment and cleaning up

No specific clean-up procedure noted. For waste disposal, see Section 13 of the SDS.

**Environmental precautions** Avoid discharge to drains, sewers, and other water systems.

# 7. Handling and storage

Precautions for safe handling

Use work methods like "score and snap" to minimize dust production. Avoid inhalation of dust and contact with skin and eyes. Wear appropriate personal protective equipment. Wash hands after handling. Observe good industrial hygiene practices. When moving board with a forklift or similar equipment, it is essential that the equipment be rated capable of handling the loads. The forks should always be long enough to extend completely through the width of the load. Fork spacing between supports should be one half the length of the panels or base being handled so that a maximum of 3' extends beyond the supports on either end.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well-ventilated place. Store away from incompatible materials. Protect product from physical damage. Protect from weather and prevent exposure to sustained moisture. FIBEROCK® panels should be stored flat.

### 8. Exposure controls/personal protection

#### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Calcium sulfate dihydrate (alternative CAS 10101-41-4) (CAS 13397-24-5)	PEL	5 mg/m3	Respirable fraction.
,		15 mg/m3	Total dust.
Cellulose (CAS 9004-34-6)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
US. ACGIH Threshold Limit Values	5		
Components	Туре	Value	Form
Calcium sulfate dihydrate (alternative CAS 10101-41-4) (CAS 13397-24-5)	TWA	10 mg/m3	Inhalable fraction.
Cellulose (CAS 9004-34-6)	TWA	10 mg/m3	

#### **US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Туре	Value	Form	
Calcium sulfate dihydrate (alternative CAS 10101-41-4) (CAS 13397-24-5)	TWA	5 mg/m3	Respirable.	
Cellulose (CAS 9004-34-6)	TWA	10 mg/m3 5 mg/m3	Total Respirable.	
Gendlese (6/10 3004 04 0)	1 ***	10 mg/m3	Total	

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Provide sufficient ventilation for operations causing dust formation. Observe occupational

exposure limits and minimize the risk of exposure.

Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear approved safety goggles.

Skin protection

Hand protection It is a good industrial hygiene practice to minimize skin contact. For prolonged or repeated skin

contact use suitable protective gloves.

Other Normal work clothing (long sleeved shirts and long pants) is recommended.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a NIOSH/MSHA approved air purifying respirator as needed to control exposure. Consult with respirator manufacturer to determine respirator selection, use, and limitations. Use positive pressure, air-supplied respirator for uncontrolled releases or when air purifying respirator limitations may be exceeded. Follow respirator protection program requirements (OSHA 1910.134 and ANSI Z88.2) for all respirator use. Observe any medical surveillance requirements.

ase. Observe any medical surveillance re

Thermal hazards None.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment separately from regular wash. Observe any medical surveillance requirements.

# 9. Physical and chemical properties

**Appearance** 

Physical state Solid.
Form Panel.

ColorOff-white to tan.OdorLow to no odor.Odor thresholdNot applicable.

**pH** 6-8

Melting point/freezing point Not applicable.

Initial boiling point and boiling Not applicable.

range

Flash point

Evaporation rate

Flammability (solid, gas)

Not applicable.

Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower Not applicable.

(%)

Flammability limit - upper Not applicable.

(%)

Explosive limit - lower (%) Not applicable.

Explosive limit - upper (%) Not applicable.

Vapor pressureNot applicable.Vapor densityNot applicable.

Relative density 0.9 - 1 (Gypsum) (H2O=1)

Solubility(ies)

Solubility (water) Insoluble

Partition coefficient Not applicable.

(n-octanol/water)

Auto-ignition temperatureNot applicable.Decomposition temperature2642 °F (1450 °C)ViscosityNot applicable.

Other information

Bulk density 54 - 62 lb/ft³
Particle size Varies.

VOC (Weight %) 0 %

### 10. Stability and reactivity

**Reactivity** Not available.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidizing agents. Strong acids.

Hazardous decomposition

products

Calcium oxides, carbon dioxide, and carbon monoxide.

# 11. Toxicological information

Information on likely routes of exposure

**Ingestion** Not likely, due to the form of the product.

**Inhalation** Inhalation of dusts may cause respiratory irritation.

**Skin contact** Under normal conditions of intended use, this material does not pose a skin hazard.

**Eye contact** Mechanical processing may generate dust. Direct contact with eyes may cause temporary

irritation (1).

Symptoms related to the physical, chemical and toxicological characteristics

Under normal conditions of intended use, this material does not pose a risk to health.

Information on toxicological effects

Acute toxicity Not expected to be a hazard under normal conditions of intended use.

**Skin corrosion/irritation** Gypsum was not found to be a skin irritant.

Serious eye damage/eye

irritation

Gypsum does not cause serious eye damage or irritation.

Respiratory or skin sensitization

Respiratory sensitization No data available, but based on results from the skin sensitization study, calcium sulfate is not

expected to be a respiratory sensitizer.

**Skin sensitization** Not a skin sensitizer (2).

Germ cell mutagenicity

No evidence of mutagenic potential exists (3,4,5).

Carcinogenicity

No evidence of carcinogenic potential exists (6).

Reproductive toxicity

No evidence of reproductive toxicity exists (2).

Specific target organ toxicity -

single exposure

No data available, but none expected.

Specific target organ toxicity -

repeated exposure

No data available, but none expected.

**Aspiration hazard**Due to the physical form of the product it is not an aspiration hazard.

Chronic effects No specific acute or chronic health impact noted.

### 12. Ecological information

**Ecotoxicity**The product components are not classified as environmentally hazardous. However, this does not

exclude the possibility that large or frequent spills can have a harmful or damaging effect on the

environment.

Components Species Test Results

Calcium sulfate dihydrate (alternative CAS 10101-41-4) (CAS 13397-24-5)

Aquatic

Fish LC50 Fathead minnow (Pimephales promelas) > 1970 mg/l, 96 hours

Persistence and degradability Not applicable for the salt of inorganic compounds. Calcium sulfate dissolves in water without

undergoing chemical degradation.

Bioaccumulative potential Bioaccumulation is not expected.

FIBEROCK® Aqua-Tough™ Underlayment Panels

2)16911 Version #: 01 Revision date: - Issue date: 12-February-2014

Mobility in soil Calcium sulfate has a low potential for adsorption to soil. If water is applied, gypsum dissolves and

the calcium and sulfate ions are mobile and penetrate the subsoil (6).

Other adverse effects None expected.

### 13. Disposal considerations

**Disposal instructions**Dispose in accordance with applicable federal, state, and local regulations. Recycle responsibly.

**Local disposal regulations** Dispose of in accordance with local regulations.

Hazardous waste code Not regulated.

Waste from residues / unused

products

Dispose of in accordance with local regulations.

**Contaminated packaging** Dispose of in accordance with local regulations.

#### 14. Transport information

#### DOT

Not regulated as dangerous goods.

#### ΙΔΤΔ

Not regulated as dangerous goods.

#### **IMDG**

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable. This product is a solid. Therefore, bulk transport is governed by IMSBC code.

### 15. Regulatory information

**US federal regulations** This product is not hazardous according to OSHA 29CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Not listed.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

#### SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

### SARA 313 (TRI reporting)

Not regulated.

#### Other federal regulations

# Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

# Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act N

Not regulated.

(SDWA)
US state regulations

# US. Massachusetts RTK - Substance List

Calcium sulfate dihydrate (alternative CAS 10101-41-4) (CAS 13397-24-5)

Cellulose (CAS 9004-34-6)

# US. New Jersey Worker and Community Right-to-Know Act

Calcium sulfate dihydrate (alternative CAS 10101-41-4) (CAS 13397-24-5)

Cellulose (CAS 9004-34-6)

# US. Pennsylvania Worker and Community Right-to-Know Law

Calcium sulfate dihydrate (alternative CAS 10101-41-4) (CAS 13397-24-5)

Cellulose (CAS 9004-34-6)

FIBEROCK® Aqua-Tough™ Underlayment Panels

SDS US

#### **US. Rhode Island RTK**

Not regulated.

# **US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer.

#### US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Not listed.

#### International Inventories

Country(s) or region Inventory name

On inventory (yes/no)\*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Yes

\*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

**Issue date** 12-February-2014

Revision date - 01

**Further information** 

Crystalline silica: Raw materials in this product may contain respirable crystalline silica. Exposures to respirable crystalline silica are not expected during the normal use of this product. However, actual levels must be determined by workplace hygiene testing. Prolonged and repeated exposure to airborne free respirable crystalline silica can result in lung disease (i.e., silicosis) and/or lung cancer.

NFPA Ratings: Health: 1 Flammability: 0 Physical hazard: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

**NFPA Ratings** 



### List of abbreviations

NFPA: National Fire Protection Association.

References

US National Library of Medicine (NLM) (1998). Hazardous Substances Data Bank (HSDB).
 Tested by LG Life Science/Toxicology Center, Korea (2002). National Institute of Environmental

Research (NIER).

- 3. Dopp E et al. (1995). Environ. Health Perspect. 103(3), 268-271.
- 4. Cremer H.H. et al. (1988). Wiss. Umwelt. 4, 202-205.
- 5. Fujita H et al. (1988). Kenkya Nenpo-Tokyo-Toritsu Eisei Kenkynsho. 39, 343-350.

6. Shainberg et al. (1989). Advanced Soil Sci. 9, 1-111.

Disclaimer

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard

workers and the environment.