

USG HALCYON™ LOGIX™ ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE



USG Halcyon™ Acoustical Panels with ClimaPlus™ Performance, and USG Donn® Brand Centricitee™ DXT™ Logix™ Acoustical Suspension System, Maricopa County Southwest Justice Center in Avondale, AZ, Architect: Architekton, Photo: ©Leland Gebhardt Photography

TO ORDER SAMPLES, GO TO USG.COM OR CGCINC.COM



Flat White
050



Limited color options available.
See Ceiling Solutions Color
Program for details.

FEATURES AND BENEFITS

- Compatible with USG Logix™ Integrated System.
- Monolithic, structured ceiling visual using standard components.
- High light-reflective finish (LR-0.90) reduces light fixtures and energy use.
- Washable and scrubbable finish—impact and scratch resistant.
- Coordinates visually with USG Mars™ Logix™ Acoustical Panels for open/closed-plan applications.
- ClimaPlus™ 30-year limited system warranty against visible sag, mold and mildew.
- High sound absorption with an NRC of up to 0.95 and an AC of up to 200.

APPLICATIONS

- Open-plan Offices
- Conference Rooms
- Reception and Lobby Areas
- Media Centers and Libraries
- Airports
- Spaces with Indirect or Natural Lighting

SUBSTRATE

- Fiberglass

Fine-Textured Panel

USG HALCYON™ LOGIX™ ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE

ORDER SAMPLES/LITERATURE
USG: usg.com or samplitt@usg.com
CGC: contact Sales Representative

TECHNICAL SERVICES
800 USG.4YOU (874-4968)

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com
usg.ecomedes.com

30 YEAR LIMITED SYSTEM WARRANTY

- No Visible Sag
- Mold/Mildew Protection

UL Classified

USG HALCYON™ LOGIX™ FIELD PANELS

Edge	Panel Size ⁵	Fire Rating	Item No.	NRC	CAC Min.	LR ²	Color	Grid Options	Anti-Mold & Mildew/Sag Resistance	Recycled Content ¹	Panel Cost
SQ 	20"x54"x1"	Class A	97407	0.95	20	0.90	White	A		40%	\$\$\$\$
	20"x56"x1"	Class A	97408	0.95	20	0.90	White	A		40%	\$\$\$\$
	20"x60"x1"	Class A	98261	0.95	20	0.90	White	A		40%	\$\$\$\$
	21"x24"x1"	Class A	97411	0.95	20	0.90	White	A, B		40%	\$\$\$\$
	22"x24"x1"	Class A	97413	0.95	20	0.90	White	A, B		40%	\$\$\$\$
	22"x48"x1"	Class A	97414	0.95	20	0.90	White	A		40%	\$\$\$\$
	24"x24"x1"	Class A	98221	0.95	20	0.90	White	A, B		40%	\$\$\$\$
	24"x42"x1"	Class A	97277	0.95	20	0.90	White	A		40%	\$\$\$\$
	24"x48"x1"	Class A	98241	0.95	20	0.90	White	A		40%	\$\$\$\$
	24"x72"x1"	Class A	99234	0.95	20	0.90	White	A		40%	\$\$\$\$
	24"x96"x1"	Class A	98351	0.95	20	0.90	White	A		40%	\$\$\$\$
	27"x60"x1"	Class A	97418	0.95	20	0.90	White	A		40%	\$\$\$\$
	30"x30"x1"	Class A	98331	0.95	20	0.90	White	A		40%	\$\$\$\$
	30"x60"x1"	Class A	97266	0.95	20	0.90	White	A		40%	\$\$\$\$
	48"x48"x1"	Class A	98441	0.95	20	0.90	White	A		40%	\$\$\$\$
	48"x54"x1"	Class A	97428	0.95	20	0.90	White	A		40%	\$\$\$\$
	48"x96"x1"	Class A	98481	0.95	20	0.90	White	A		40%	\$\$\$\$
SQ 	4"x48"x1"	Class A	97402	0.95 ⁸	20 ⁹	0.90	White	A		40%	\$\$\$\$
	4"x60"x1"	Class A	97403	0.95 ⁸	20 ⁹	0.90	White	A		40%	\$\$\$\$
	4"x72"x1"	Class A	97404	0.95 ⁸	20 ⁹	0.90	White	A		40%	\$\$\$\$
	6"x48"x1"	Class A	97227	0.95	20	0.90	White	A		40%	\$\$\$\$
	6"x60"x1"	Class A	97228	0.95	20	0.90	White	A		40%	\$\$\$\$
	12"x48"x1"	Class A	97491	0.95	20	0.90	White	A		40%	\$\$\$\$
SL 	20"x54"x1"	Class A	97436	0.95	20	0.90	White	C		40%	\$\$\$\$
	20"x56"x1"	Class A	97437	0.95	20	0.90	White	C		40%	\$\$\$\$
	20"x60"x1"	Class A	99267	0.95	20	0.90	White	C		40%	\$\$\$\$
	21"x24"x1"	Class A	98220	0.95	20	0.90	White	C		40%	\$\$\$\$

ClimaPlus™ Warranty Performance³

Fiberglass substrate is inherently resistant to the growth of mold and mildew. Includes sag-resistance performance.

USG HALCYON™ LOGIX™ ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE

ORDER SAMPLES/LITERATURE
USG: usg.com or samplit@usg.com
CGC: contact Sales Representative

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com
usg.ecomedes.com

TECHNICAL SERVICES
800.USG.4YOU (874-4968)

30 YEAR LIMITED SYSTEM
WARRANTY
• No Visible Sag
• Mold/Mildew Protection

UL Classified

Edge	Panel Size ⁵	Fire Rating	Item No.	NRC	CAC Min.	LR ²	Color	Grid Options	Anti-Mold & Mildew/Sag Resistance	Recycled Content ¹	Panel Cost
											
SL 	22"x24"x1"	Class A	97440	0.95	20	0.90	White	C		40%	\$\$\$\$
	22"x48"x1"	Class A	97441	0.95	20	0.90	White	C		40%	\$\$\$\$
	24"x24"x1"	Class A	98223	0.95	20	0.90	White	C		40%	\$\$\$\$
	24"x42"x1"	Class A	97443	0.95	20	0.90	White	C		40%	\$\$\$\$
	24"x48"x1"	Class A	98243	0.95	20	0.90	White	C		40%	\$\$\$\$
	24"x72"x1"	Class A	99268	0.95	20	0.90	White	C		40%	\$\$\$\$
	24"x96"x1"	Class A	99269	0.95	20	0.90	White	C		40%	\$\$\$\$
	27"x60"x1"	Class A	97448	0.95	20	0.90	White	C		40%	\$\$\$\$
	30"x30"x1"	Class A	98333	0.95	20	0.90	White	C		40%	\$\$\$\$
	30"x60"x1"	Class A	99270	0.95	20	0.90	White	C		40%	\$\$\$\$
	48"x48"x1"	Class A	98443	0.95	20	0.90	White	C		40%	\$\$\$\$
	48"x54"x1"	Class A	97458	0.95	20	0.90	White	C		40%	\$\$\$\$
	48"x96"x1"	Class A	98483	0.95	20	0.90	White	C		40%	\$\$\$\$
SL 	4"x48"x1"	Class A	97430	0.95 ⁸	20 ⁹	0.90	White	C		40%	\$\$\$\$
	4"x60"x1"	Class A	97431	0.95 ⁸	20 ⁹	0.90	White	C		40%	\$\$\$\$
	4"x72"x1"	Class A	97432	0.95 ⁸	20 ⁹	0.90	White	C		40%	\$\$\$\$
	6"x48"x1"	Class A	99271	0.95	20	0.90	White	C		40%	\$\$\$\$
	6"x60"x1"	Class A	99272	0.95	20	0.90	White	C		40%	\$\$\$\$
	12"x24"x1"	Class A	99263	0.95	20	0.90	White	C		40%	\$\$\$\$
	12"x48"x1"	Class A	97571	0.95	20	0.90	White	C		40%	\$\$\$\$
FL 	20"x54"x1"	Class A	98360	0.95	20	0.90	White	D,E,F		40%	\$\$\$\$
	20"x56"x1"	Class A	97464	0.95	20	0.90	White	D,E,F		40%	\$\$\$\$
	20"x60"x1"	Class A	98194	0.95	20	0.90	White	D,E,F		40%	\$\$\$\$
	21"x24"x1"	Class A	98195	0.95	20	0.90	White	D,E,F		40%	\$\$\$\$
	22"x24"x1"	Class A	97467	0.95	20	0.90	White	D,E,F		40%	\$\$\$\$
	22"x48"x1"	Class A	97468	0.95	20	0.90	White	D,E,F		40%	\$\$\$\$
	24"x24"x1"	Class A	98225	0.95	20	0.90	White	D,E,F		40%	\$\$\$\$

 ClimaPlus™ Warranty Performance³

Fiberglass substrate is inherently resistant to the growth of mold and mildew. Includes sag-resistance performance.

USG HALCYON™ LOGIX™ ACOUSTICAL PANELS
CLIMAPLUS™ PERFORMANCE

ORDER SAMPLES/LITERATURE
USG: usg.com or samplitt@usg.com
CGC: contact Sales Representative

TECHNICAL SERVICES
800.USG.4YOU (874-4968)

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com
usg.ecomedes.com

30 YEAR LIMITED SYSTEM
WARRANTY

- No Visible Sag
- Mold/Mildew Protection

UL Classified

Edge	Panel Size ⁵	Fire Rating	Item No.	NRC	CAC Min.	LR ²	Color	Grid Options	Anti-Mold & Mildew/Sag Resistance	Recycled Content ¹	Panel Cost
FL 	24"x42"x1"	Class A	98196	0.95	20	0.90	White	D,E,F		40%	\$\$\$\$
	24"x48"x1"	Class A	98245	0.95	20	0.90	White	D,E,F		40%	\$\$\$\$
	24"x57"x1"	Class A	98341	0.95	20	0.90	White	D,E,F		40%	\$\$\$\$
	24"x60"x1"	Class A	96271	0.95	20	0.90	White	D,E,F		40%	\$\$\$\$
	24"x72"x1"	Class A	98348	0.95	20	0.90	White	D,E,F		40%	\$\$\$\$
	24"x96"x1"	Class A	98197	0.95	20	0.90	White	D,E,F		40%	\$\$\$\$
	27"x60"x1"	Class A	98440	0.95	20	0.90	White	D,E,F		40%	\$\$\$\$
	30"x30"x1"	Class A	98335	0.95	20	0.90	White	D,E,F		40%	\$\$\$\$
	30"x60"x1"	Class A	98336	0.95	20	0.90	White	D,E,F		40%	\$\$\$\$
	48"x48"x1"	Class A	98445	0.95	20	0.90	White	D,E,F		40%	\$\$\$\$
	48"x54"x1"	Class A	98344	0.95	20	0.90	White	D,E,F		40%	\$\$\$\$
	48"x96"x1"	Class A	97478	0.95	20	0.90	White	D,E,F		40%	\$\$\$\$
FL 	4"x48"x1"	Class A	97460	0.95 ⁸	20 ⁹	0.90	White	D,E,F		40%	\$\$\$\$
	4"x60"x1"	Class A	97461	0.95 ⁸	20 ⁹	0.90	White	D,E,F		40%	\$\$\$\$
	4"x72"x1"	Class A	97462	0.95 ⁸	20 ⁹	0.90	White	D,E,F		40%	\$\$\$\$
	6"x42"x1"	Class A	99197	0.95 ⁸	20 ⁹	0.90	White	D,E,F		40%	\$\$\$\$
	6"x48"x1"	Class A	98198	0.95	20	0.90	White	D,E,F		40%	\$\$\$\$
	6"x54"x1"	Class A	98131	0.95 ⁸	20 ⁹	0.90	White	D,E,F		40%	\$\$\$\$
	6"x60"x1"	Class A	98199	0.95	20	0.90	White	D,E,F		40%	\$\$\$\$
	6"x96"x1"	Class A	98216	0.95 ⁸	20 ⁹	0.90	White	D,E,F		40%	\$\$\$\$
	12"x24"x1"	Class A	98191	0.95	20	0.90	White	D,E,F		40%	\$\$\$\$
	12"x48"x1"	Class A	98192	0.95	20	0.90	White	D,E,F		40%	\$\$\$\$
	12"x96"x1"	Class A	99265	0.95	20	0.90	White	D,E,F		40%	\$\$\$\$

A USG DX®	B ⁴ USG Centricitee™ DXT™	C USG DX®	D USG Centricitee™ DXT™	E USG Fineline® DXF™	F USG Identitee® DXI™	ClimaPlus™ Warranty Performance ³ Fiberglass substrate is inherently resistant to the growth of mold and mildew. Includes sag- resistance performance.

Product literature
Data sheet: IS272
System guide: IS268

Online tools
usgdesignstudio.com,
cgcdesignstudio.com or
usg.ecomedes.com

ASTM E1264 classification
ASTM E1264-22 Type XII, Form 2, Pattern E & G
ASTM E1264-23 Type B, Form B2, Pattern E & G

ASTM E84 and CAN/ULC S102
surface burning characteristics
Class A
Flame spread: 25 or less
Smoke developed: 50 or less

Weight
0.47 lb./sq. ft.

Thermal resistance
R-4.4

Maintenance
Can be cleaned easily with a soft brush or vacuum. To
clean panel, use a clean white cloth with water or a mild
detergent and wipe surface.

Maximum backloading
See USG 30-Year Limited System Warranty Commercial
Applications (SC2102).

Treating field-cut reveal edges
All field-cut edges "exposed to view" should be colored to
match the factory finish. USG Halcyon™ Ceiling Touch-Up
Paint is recommended when perimeter field cuts expose
the substrate.

Notes

1. For details, see USG Sustainability tool at usgdesignstudio.com or cgcdesignstudio.com.
2. LR values are shown as averages.
3. For details, see USG 30-Year Limited System Warranty Commercial Applications (SC2102).
4. Maximum 2"x2" with SQ edge panels.
5. Stabilizer bar required if opening ≥ 60".
6. Select custom color panels are available in limited sizes and edge profiles. Minimum order quantities apply. Please contact your local sales representative for availability, pricing, minimum order quantities and lead times.
7. Additional custom size panels are available. Minimum order quantities apply. Please contact your local sales representative for availability, pricing, minimum order quantities and lead times.
8. Tested in accordance with ASTM C423 in USG Acoustical Test Facility (NVLAP Lab Code: 200132-0); not UL classified for acoustics.
9. Tested in accordance with ASTM E1414 in USG Acoustical Test Facility (NVLAP Lab Code: 200132-0); not UL classified for acoustics.

USG HALCYON™ LOGIX™
FIELD PANELS CONT.

USG HALCYON™ LOGIX™
CHANNEL PANELS

GRID PROFILE OPTIONS

PHYSICAL DATA/
FOOTNOTES

Notice

The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

IS272/rev. 7-24
© 2024 USG Corporation and/or its affiliates. All rights reserved. Printed in U.S.A.

Manufactured by
USG Interiors, LLC
550 West Adams Street
Chicago, IL 60661

The trademarks USG, CGC, CENTRICITEE, CLIMAPLUS, DONN, DX, DXF, DXI, DXT, FINELINE, HALCYON, IDENTITEE, LOGIX, MARS, IT'S YOUR WORLD. BUILD IT, the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

