

USG MICORE® 160

MINERAL FIBER BOARD

Versatile, high-performance core or substrate

- Easier to handle and superior performance than particle board
- Outstanding versatility adapts to a variety of applications
- Smooth, coated finish maintains tighter tolerance
- Exceptional tackability
- Good sound control
- Class A surface burning characteristics per ASTM E84
- GreenGuard Gold Certification; qualifies as a low VOC emitting material (meets CA 01350)

DESCRIPTION

USG Micore 160 Mineral Fiber Board offers superior performance and savings to a variety of applications. The board combines lightweight properties with the strength and stability of heavier board alternatives. USG Micore 160 also provides great acoustical performance to help reduce noise in open plan interiors while the inorganic mineral fibers resist moisture to minimize expansion and warping.

INTENDED FOR

- Use in a variety of applications including tackboards, wall panels, office dividers and baffles
- Laminate with a variety of finish materials

PRODUCT DATA

THICKNESS AND WEIGHT¹

THICKNESS ^{2,3}	WEIGHT
1/2 in. (0.500)	0.67 – 0.83 psf
5/8 in. (0.625)	0.83 – 1.04 psf
3/4 in. (0.750)	1.00 – 1.25 psf

1. Standard size is 4' x 8'. Custom sizes available. Minimum order quantities apply. 5/8" is only available in custom sizes.
2. Thickness tolerance $\pm 0.015"$
3. Width and length tolerance $\pm 1/16"$

PHYSICAL PROPERTIES

Surface burning characteristics	Flame Spread ¹	25
	Smoke developed ¹	10
Density	18 \pm 2 pcf	
Modulus of rupture²	275 lbs./psi	
Modulus of elasticity²	21,000 lbs./psi	
Tensile strength (parallel to surface)²	125 lbs./psi	
Hardness (Janka Ball)²	35 lbs.	
Hygrometric expansion (50% to 70% R.H.)	0.25%	
R-Value (1/2")²	1.27	
K factor (1/2")²	0.40	

1. Per ASTM E84.
2. Values shown are production averages.

ACOUSTICAL PERFORMANCE¹

THICKNESS	STC RATING	NRC (MIN.)
1/2"	24	0.30
5/8"	26	0.30
3/4"	26	0.50

1. Based on perforated product only. Published STC and NRC values are based on laboratory tests. Actual field acoustical performance may differ depending on acoustical performance of all other products and systems used with USG Micore 160 Mineral Fiber Board as installed.

NOTES/LIMITATIONS

1. Avoid exposure to excessive or continuous moisture. Installation and occupancy conditions should not exceed 85 °F/70% RH.
2. Not intended to be painted. Painting will impair the acoustical and fire performance and will void all manufacturer warranties.
3. Not intended for use with ceramic tile.
4. Do not stack higher than 3 pallets high.

PRODUCT INFORMATION

See usg.com for the most up-to-date product information.

GREENGUARD INFORMATION

GREENGUARD Certified products are certified to GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit ul.com/gg.

LEED INFORMATION

For the most up-to-date information on LEED rating systems, project certification and the U.S. Green Building Council, please visit usgbc.org.

DANGER

May cause cancer or damage to lungs from presence of respirable crystalline silica through prolonged or repeated exposure by inhalation. Do not handle until all safety precautions have been read and understood. Avoid breathing dust. Use only in a well-ventilated area, wear a NIOSH/MSHA-approved respirator. Cut and trim with a utility knife or hand saw to minimize dust levels. If a router is used, it must have a dust collection system. Wear protective gloves/protective clothing/eye protection. If exposed or concerned: Get medical advice/attention. If eye contact occurs, flush thoroughly with water for 15 minutes. Dispose of in accordance with local, state, and federal regulations. For more information, call Product Safety: 1-800-507-8899 or see the SDS at usg.com

KEEP OUT OF REACH OF CHILDREN.

TRADEMARKS

The trademarks USG, MICORE, IT'S YOUR WORLD. BUILD IT., the USG logo, the design elements and colors and related marks are trademarks of USG Corporation or its affiliates.

LEED is a registered trademark of U.S. Green Building Council.

NOTE

The information in this document is subject to change without notice. USG Corp. and/or its affiliates assume no responsibility for any errors that may inadvertently appear in this document. Consult your USG sales office or representative for information.

NOTICE

We shall not be liable for consequential, incidental or special damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. Our liability is expressly limited to the replacement of defective goods or a refund of the purchase price, at USG's option, and does not include costs of labor, floor-covering materials, or any other costs associated with material replacement. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

SAFETY FIRST!

Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read applicable SDSs and literature before specification and installation.



800.USG.4YOU
800 (874.4968)
usg.com

Manufactured by
United States Gypsum Company
550 West Adams Street
Chicago, IL 60661

IG307468-USG-ENG/9-22
© 2022 USG Corporation and/or
its affiliates. All rights reserved.
Printed in U.S.A.

USG
IT'S YOUR WORLD. BUILD IT.®