

USG OLYMPIA™ MICRO™ ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE

USG Olympia™ Micro™ Acoustical Panels with ClimaPlus™ Performance, and USG Donn® Brand Identitee® DXI™ Acoustical Suspension System

TO ORDER SAMPLES, GO TO USG.COM OR CGCINC.COM



Flat White
050

FEATURES AND BENEFITS

- Nondirectional pattern reduces installation time and waste.
- Economical, fine-textured panel.
- Excellent light-reflective finish (LR-0.86) reduces light fixtures and energy use.
- USDA Certified Biobased Product.⁷
- ClimaPlus™ 30-year limited system warranty against visible sag, mold and mildew.

APPLICATIONS

- Offices
- Classrooms
- Reception/Lobby Areas
- Hotels
- Conference Areas
- Retail Stores

SUBSTRATE

- Wet-formed Mineral Fiber

Fine-Textured Panel

USG OLYMPIA™ MICRO™ ACOUSTICAL PANELS
CLIMAPLUS™ PERFORMANCE

ORDER SAMPLES/LITERATURE
USG: usg.com or samplitt@usg.com
CGC: contact Sales Representative

TECHNICAL SERVICES
800 USG.4YOU (874-4968)

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com
usg.ecomedes.com



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
ULCOM/GG
UL 2818

30 YEAR LIMITED SYSTEM
WARRANTY
• No Visible Sag
• Mold/Mildew Protection

10 YEAR
AVAILABILITY
4211, 4221, 4231,
4411, 4421, 4742,
4744

HRC HIGH RECYCLED
CONTENT



USG OLYMPIA™ MICRO™
PANELS UNPERFORATED⁹

USG OLYMPIA™ MICRO™
PANELS 50 NRC⁶

USG OLYMPIA™ MICRO™
PANELS 60 NRC^{6,10}

USG OLYMPIA™
MICRO™ ILLUSION™
TWO/24 PANELS

PATTERNS

UL Classified												
Edge	Panel Size	Fire Rating	Item No.	NRC	CAC Min.	LR ²	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew	Recycled Content ¹	Panel Cost
	2'x2'x5/8"	Class A	4210	—	35	0.86	White	A,B,C	Low		66%	\$\$
	2'x4'x5/8"	Class A	4913	—	35	0.86	White	A,B	Low		66%	\$\$
	2'x2'x5/8"	Class A	4211	0.50	30	0.86	White	A,B,C	Low		66%	\$\$
	2'x4'x5/8"	Class A	4411	0.50	30	0.86	White	A,B	Low		66%	\$\$
	2'x2'x5/8"	Class A	4221	0.50	35	0.86	White	D	Low		66%	\$\$
	2'x4'x5/8"	Class A	4421	0.50	35	0.86	White	D	Low		66%	\$\$
	2'x2'x5/8"	Class A	4231	0.50	35	0.86	White	E,F,G,H	Low		66%	\$\$
	2'x4'x5/8"	Class A	4431	0.50	35	0.86	White	E,F,G,H	Low		66%	\$\$
	2'x2'x3/4"	Class A	4750	0.60	33	0.86	White	A,B,C	Low		80%	\$\$
	2'x4'x3/4"	Class A	4751	0.60	33	0.86	White	A,B	Low		80%	\$\$
	2'x2'x3/4"	Class A	4752	0.60	35	0.86	White	D	Low		80%	\$\$
	2'x4'x3/4"	Class A	4753	0.60	35	0.86	White	D	Low		80%	\$\$
	2'x2'x3/4"	Class A	4754	0.60	35	0.86	White	E,F,G,H	Low		80%	\$\$
	2'x4'x3/4"	Class A	4755	0.60	35	0.86	White	E,F,G,H	Low		80%	\$\$
	2'x4'x3/4"	Class A	4742	0.50	35	0.86	White	D	Low		66%	\$\$
	2'x4'x3/4"	Class A	4744	0.50	35	0.86	White	I	Low		66%	\$\$

USG Illusion™ Two/24



The look of 2'x2' panels

Low Emissions (VOC)

Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.2 - 2017 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.ecomedes.com and at spot.ul.com.

ClimaPlus™ Warranty Performance³

Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.

High Recycled Content

USG classifies High Recycled Content as greater than 50%. Total recycled content is based on product composition of pre-consumer (post-industrial) and post-consumer recycled content per FTC guidelines.

GRID PROFILE OPTIONS

A USG DX*	B USG DXW™	C* USG Centricitee™ DXT™	D USG DX*	E USG Centricitee™ DXT™	F USG Identitee* DXI™	G USG Fineline* DXF™	H USG Fineline* 1/8 DXFF™	I USG Centricitee™ DXT™

PHYSICAL DATA/
FOOTNOTES

Product literature
Data sheet: SC2180

ASTM E1264 classification

ASTM E1264-22 Type III, Form 2, Pattern C & E
ASTM E1264-23 Type A, Form A1.2, Pattern C & E

ASTM E84 and CAN/ULC S102
surface-burning characteristics

Class A
Flame spread: 25 or less
Smoke developed: 50 or less

Online tools

usgdesignstudio.com, cgcdesignstudio.com
or usg.ecomedes.com

Weight
0.77-1.00 lb./sq. ft.

Thermal resistance
R-1.4 (5/8" panels)
R-1.7 (3/4" panels)

Maximum backloading

See USG 30-Year Limited System
Warranty Commercial Applications
(SC2102).

Maintenance

Can be cleaned easily with a soft
brush or vacuum.

Notes

- For details, see USG Sustainability tool at usgdesignstudio.com or cgcdesignstudio.com.
- LR values are shown as averages.
- For details, see USG 30-Year Limited System Warranty Commercial Applications (SC2102).
- Panels have 15/16" routing.
- Panels have 9/16" routing.
- Mixing 0.50 and 0.60 NRC panels in the same ceiling plane is not recommended.
- This product has achieved both BioPreferred Initiatives: Federal Procurement Preference and Certified Product Labeling. See the complete listing of all USG ceiling panels on biopreferred.gov website.

8. Maximum 2'x2' with SQ edge panels.

9. Item numbers 4210 and 4913 are not UL Classified for acoustics.

10. It is not recommended to mix panels with varying NRC values in the same ceiling plane.

11. SLT & ILT Illusion™ edges have a different reveal depth from SLT or FLB edge details. Please reference the System Interface, located in the SC2000, before installing.

Notice

The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

SC2180/rev. 7-24

© 2024 USG Corporation and/or its affiliates. All rights reserved.
Printed in USA

Manufactured by
USG Interiors, LLC
550 West Adams Street
Chicago, IL 60661

The trademarks USG, CGC, CENTRICITEE, CLIMAPLUS, DONN, DX, DXF, DXFF, DXI, DXT, DXW, FINELINE, IDENTITEE, ILLUSION, MICRO, OLYMPIA, IT'S YOUR WORLD. BUILD IT., the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

