# SAFETY DATA SHEET

# 1. Identification

**Product identifier USG® Plaster Bonding Agent (Pink)** 

Other means of identification

**SDS** number 53000020003

Sealer **Synonyms** Recommended use Interior use.

**Recommended restrictions** Use in accordance with manufacturer's recommendations.

Manufacturer/Importer/Supplier/Distributor information

Company name United States Gypsum Company

Address 550 West Adams Street

Chicago, Illinois 60661-3637

1-800-874-4968 **Telephone** Website www.usg.com **Emergency phone number** 1-800-507-8899

2. Hazard(s) identification

Not classified. **Physical hazards** 

Specific target organ toxicity, repeated **Health hazards** 

Category 2 (kidney)

Category 2

exposure (oral)

**Environmental hazards** Hazardous to the aquatic environment, acute Category 1

Hazardous to the aquatic environment,

long-term hazard

**OSHA** defined hazards Not classified.

Label elements





Signal word Warning

**Hazard statement** May cause damage to organs (kidney) through prolonged or repeated exposure by ingestion. Very

toxic to aquatic life. Toxic to aquatic life with long lasting effects.

**Precautionary statement** 

Prevention Do not breathe mist/vapors. Avoid release to the environment. Get medical advice/attention if you feel unwell. Collect spillage. Response

Store away from incompatible materials. Storage

Dispose of contents/container in accordance with local/regional/national/international regulations. **Disposal** 

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

# 3. Composition/information on ingredients

## **Mixtures**

Chemical name	CAS number	%	
Ethylene glycol	107-21-1	< 3	
Zinc omadine	13463-41-7	< 0.5	

USG® Plaster Bonding Agent (Pink) SDS US 918216 Version #: 02 Revision date: 28-September-2020 Issue date: 30-March-2015

Zinc oxide 1314-13-2 < 0.5

**Composition comments** 

All concentrations are in percent by weight.

4. First-aid measures

**Inhalation** Exposure to mists may cause temporary irritation to eyes, skin, nose, throat, and upper respiratory

tract. Move injured person into fresh air and keep person calm under observation. Get medical

attention if symptoms persist.

**Skin contact** Rinse area with plenty of water. Get medical attention if irritation develops and persists.

**Eye contact** Do not rub eyes. Flush thoroughly with water. If burning, redness, itching, pain, or other symptoms

develop or persist get medical attention.

**Ingestion** Rinse mouth. Get medical attention if any discomfort occurs.

Most important symptoms/effects, acute and

symptoms/effects, acute and delayed

Indication of immediate medical attention and special

treatment needed

Under normal conditions of intended use, this product is not expected to be a health risk. Overexposure is highly unlikely at concentrations present in this product. Edema. Prolonged exposure may cause chronic effects.

Provide general supportive measures and treat symptomatically.

General information Ensure that medical personnel are aware of the material(s) involved.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Use fire-extinguishing media appropriate for surrounding materials.

Not applicable.

Specific hazards arising from the chemical

Special protective equipment

Not a fire hazard.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire. Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace.

and precautions for firefighters

Fire fighting equipment/instructions

Use standard firefighting procedures and consider the hazards of other involved materials.

**Specific methods** Cool material exposed to heat with water spray and remove it if no risk is involved.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

See Section 8 of the SDS for Personal Protective Equipment.

Methods and materials for containment and cleaning up

Prevent entry into confined areas or water systems. Dilute with water and mop or wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Dispose of waste according to local regulations.

**Environmental precautions** 

Do not contaminate water. Avoid discharge to drains, sewers, and other water systems. Inform appropriate managerial or supervisory personnel of all environmental releases.

7. Handling and storage

Precautions for safe handling

Do not breathe mist/vapors. Avoid prolonged exposure. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid release to the environment. Observe good industrial hygiene practices. Use proper lifting techniques.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry place. Store in a closed container away from incompatible materials, food, or drinking water. Protect from moisture. Keep away from heat. Do not use if material has spoiled, i.e., there is a moldy appearance or an unpleasant odor. Keep containers closed when not in use.

## 8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table 7-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Zinc oxide (CAS 1314-13-2)	PEL	5 mg/m3	Fume.
		5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.

USG® Plaster Bonding Agent (Pink)
918216 Version #: 02 Revision date: 28-September-2020 Issue date: 30-March-2015

US. ACGIH Threshold Limit Values Components	S Type	Value	Form
Ethylene glycol (CAS 107-21-1)	STEL	10 mg/m3	Aerosol, inhalable.
		50 ppm	Vapor fraction
	TWA	25 ppm	Vapor fraction
Zinc oxide (CAS 1314-13-2)	STEL	10 mg/m3	Respirable fraction.
	TWA	2 mg/m3	Respirable fraction.
US. NIOSH: Pocket Guide to Chem	nical Hazards		
Components	Туре	Value	Form
Zinc oxide (CAS 1314-13-2)	Ceiling	15 mg/m3	Dust.
	STEL	10 mg/m3	Fume.
	TWA	5 mg/m3	Dust.
		5 mg/m3	Fume.
		•	

No biological exposure limits noted for the ingredient(s). **Biological limit values** 

**Exposure guidelines** No exposure standards allocated.

Appropriate engineering Provide sufficient ventilation for operations causing mist formation. Observe occupational exposure controls

limits and minimize the risk of exposure.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear approved safety goggles.

Skin protection

It is a good industrial hygiene practice to minimize skin contact. Hand protection

Use of an impervious apron is recommended. Normal work clothing (long sleeved shirts and long Other

pants) is recommended.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Chemical

respirator with organic vapor cartridge and full facepiece.

Thermal hazards None.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Observe any medical surveillance requirements.

# 9. Physical and chemical properties

**Appearance** 

Solid. Physical state

Acrylic emulsion. **Form** Color Gray to off-white. Odor Slight acrylic. **Odor threshold** Not applicable. 8.5 - 9.5

32 °F (0 °C) Melting point/freezing point 212 °F (100 °C) Initial boiling point and boiling

range

Not applicable. Flash point **Evaporation rate** Not applicable. Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not applicable.

Flammability limit - upper Not applicable.

(%)

USG® Plaster Bonding Agent (Pink)

SDS US

918216 Version #: 02 Revision date: 28-September-2020 Issue date: 30-March-2015

Explosive limit - lower (%) Not applicable. Not applicable. Explosive limit - upper (%) Not applicable. Vapor pressure Vapor density Same as water.

Relative density Solubility(ies)

Solubility (water) Soluble in water. Partition coefficient Not applicable.

(n-octanol/water)

**Auto-ignition temperature** Not applicable. Not applicable. **Decomposition temperature Viscosity** Not applicable.

Other information

**Bulk density** 7.8 - 8.5 lb/gal Not explosive. **Explosive properties** Oxidizing properties Not oxidizing.

VOC 41.5 g/l (EPA Method 24)

# 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Stable at normal conditions. Chemical stability

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

**Hazardous decomposition** 

products

None known.

0.9 - 1 (H2O=1)

# 11. Toxicological information

#### Information on likely routes of exposure

Inhalation Spray mist may irritate the respiratory system. Prolonged inhalation may be harmful.

Skin contact Prolonged skin contact may cause temporary irritation. Direct contact with eyes may cause temporary irritation. Eve contact

Ingestion May cause discomfort if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation. Edema. Prolonged exposure may cause

chronic effects.

# Information on toxicological effects

**Acute toxicity** Low hazard for usual industrial or commercial handling by trained personnel.

Components **Species Test Results** 

Ethylene glycol (CAS 107-21-1)

Acute **Dermal** 

LD50 Rabbit 9530 mg/kg

Skin corrosion/irritation Prolonged or repeated skin contact may cause irritation. Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not classified but possible due to skin sensitization effect. Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

USG® Plaster Bonding Agent (Pink)

Carcinogenicity This product is not classified as a carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

**NTP Report on Carcinogens** 

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

No data available, but none expected.

Specific target organ toxicity -

repeated exposure

May cause damage to organs (kidney) through prolonged or repeated exposure.

**Aspiration hazard** Not an aspiration hazard.

**Chronic effects** Prolonged exposure may cause chronic effects.

12. Ecological information

**Ecotoxicity** Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Components		Species	Test Results			
Ethylene glycol (CAS	Ethylene glycol (CAS 107-21-1)					
Aquatic						
Acute						
Crustacea	EC50	Ceriodaphnia dubia	10000 mg/l, 48 Hours			
Fish	LC50	Oncorhynchus mykiss	24591 mg/l, 96 Hours			
Chronic						
Crustacea	NOEC	Ceriodaphnia dubia	3469 mg/l, 7 days			
Fish	NOEC	Oncorhynchus mykiss	14692 mg/l, 12 days			
Zinc oxide (CAS 1314	-13-2)					
Aquatic						
Crustacea	LC50	Water flea (Daphnia magna)	0.098 mg/l, 48 Hours			

Persistence and degradability

No data available.

Bioaccumulative potential No data available for this product.

Partition coefficient n-octanol / water (log Kow)

Ethylene glycol (CAS 107-21-1) -1.36

Mobility in soil No data available. Other adverse effects None expected.

13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose waste and residues in accordance with applicable

federal, state, and local regulations.

Dispose in accordance with all applicable regulations. Local disposal regulations

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

UN3082 **UN** number

**UN** proper shipping name Environmentally hazardous substances, liquid, n.o.s. (Zinc omadine, Zinc oxide)

Transport hazard class(es)

**Class** 9

SDS US USG® Plaster Bonding Agent (Pink) 5/8 Subsidiary risk Label(s) 9
Packing group III

**Environmental hazards** 

Marine pollutant Yes

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

**Special provisions** 8, 146, 335, IB3, T4, TP1, TP29

Packaging exceptions 155
Packaging non bulk 203
Packaging bulk 241

IATA

UN number UN3082

UN proper shipping name Transport hazard class(es) Environmentally hazardous substance, liquid, n.o.s. (Zinc omadine, Zinc oxide)

Class 9
Subsidiary risk Packing group III
Environmental hazards Yes
ERG Code 9L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

**IMDG** 

UN number UN3082

UN proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Zinc omadine, Zinc oxide)

Transport hazard class(es)

Class 9
Subsidiary risk Packing group III
Environmental hazards

Marine pollutant Yes EmS F-A, S-F

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

### 15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not established.

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Ethylene glycol (CAS 107-21-1) Listed.
Zinc omadine (CAS 13463-41-7) Listed.
Zinc oxide (CAS 1314-13-2) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Toxic Substances Control Act (TSCA)

All components of the mixture on the TSCA 8(b) inventory are designated

"active".

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

categories

Classified hazard Specific target organ toxicity (single or repeated exposure)

USG® Plaster Bonding Agent (Pink)
918216 Version #: 02 Revision date: 28-September-2020 Issue date: 30-March-2015

% by wt. **Chemical name CAS** number 107-21-1 Ethylene glycol < 3

#### Other federal regulations

### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Ethylene glycol (CAS 107-21-1)

### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Contains component(s) regulated under the Safe Drinking Water Act.

(SDWA)

# **US** state regulations

# **US. Massachusetts RTK - Substance List**

Ethylene glycol (CAS 107-21-1) Zinc oxide (CAS 1314-13-2)

## US. New Jersey Worker and Community Right-to-Know Act

Ethylene glycol (CAS 107-21-1) Zinc omadine (CAS 13463-41-7) Zinc oxide (CAS 1314-13-2)

#### US. Pennsylvania Worker and Community Right-to-Know Law

Ethylene glycol (CAS 107-21-1) Zinc omadine (CAS 13463-41-7) Zinc oxide (CAS 1314-13-2)

#### **US. Rhode Island RTK**

Ethylene glycol (CAS 107-21-1) Zinc oxide (CAS 1314-13-2)

### **California Proposition 65**



WARNING: This product can expose you to Ethylene glycol, which is known to the State of California to cause

birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

### California Proposition 65 - CRT: Listed date/Developmental toxin

Inventory name

Ethylene glycol (CAS 107-21-1) Listed: June 19, 2015

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Ethylene glycol (CAS 107-21-1)

#### International Inventories

Country(s) or region

Country(3) or region	inventory name	On inventory (yes/no)
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

<sup>\*</sup>A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

30-March-2015 Issue date

USG® Plaster Bonding Agent (Pink) 7/8 918216 Version #: 02 Revision date: 28-September-2020 Issue date: 30-March-2015

On inventory (yes/no)\*

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

**Revision date** 

Version #

**Further information** 

28-September-2020

Vinyl acetic monomer, formaldehyde and acetaldehyde: Trace amounts of vinyl acetate monomer and formaldehyde may be found in this product. They are present as trace residuals in many common raw materials that are used to formulate joint compounds, and any emissions from them are expected to be well below ACGIH and OSHA occupational exposure limits.

NFPA Ratings: Health: 2 Flammability: 0 Physical hazard: 0

NFPA Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

**NFPA** ratings



List of abbreviations **Disclaimer** 

NFPA: National Fire Protection Association.

United States Gypsum Company cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available. This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.

USG® Plaster Bonding Agent (Pink)

SDS US 8/8 918216 Version #: 02 Revision date: 28-September-2020 Issue date: 30-March-2015