

USG PREMIER HI-LITE™ ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE

USG Premier Hi-Lite™ Kapok Panels
with ClimaPlus™ Performance/
USG Donn® Brand DX®
Acoustical Suspension System

TO ORDER SAMPLES, GO TO USG.COM OR CGCINC.COM



Flat White
050



Flat Black
205

FEATURES AND BENEFITS

- Washable vinyl face for easy maintenance.
- Excellent noise reduction with NRC of 0.70 for greater sound control in open-plan spaces.
- Lightweight fiberglass basemat makes installation fast and easy.
- ClimaPlus™ 30-year limited system warranty against visible sag, mold and mildew.

APPLICATIONS

- Discount Stores
- Grocery Stores
- Mass Merchandisers
- Retail Stores

SUBSTRATE

- Fiberglass

Medium-Textured Panel, Kapok Perforated and Unperforated

Medium-Textured Panel, Twill Perforated and Unperforated

USG PREMIER HI-LITE™ ACOUSTICAL PANELS
CLIMAPLUS™ PERFORMANCE

ORDER SAMPLES/LITERATURE
USG: usg.com or samplitt@usg.com
CGC: contact Sales Representative
TECHNICAL SERVICES
800 USG.4YOU (874-4968)
FOR MOST UP-TO-DATE TECHNICAL INFORMATION AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com
usg.ecomedes.com

30 YEAR LIMITED SYSTEM WARRANTY
• No Visible Sag
• Mold/Mildew Protection

UL Classified

Edge	Panel Size	Fire Rating	Item No.	NRC	CAC Min.	LR²	Color⁴	Grid Options	Anti-Mold & Mildew/ Sag Resistance	Recycled Content¹	Panel Cost
SQ 	2'x2'x5/8" Perforated	Class A	7050G	0.70	20	0.76	White	A, B, C, D		42%	\$
	2'x2'x5/8" Unperforated	Class A	7052G	0.50	20	0.76	White	A, B, C, D		42%	\$
	2'x4'x5/8" Perforated	Class A	7051G	0.70	20	0.76	White	A, B, C, D		42%	\$
	2'x4'x5/8" Unperforated	Class A	7053G	0.50	20	0.76	White	A, B, C, D		42%	\$
SQ 	2'x2'x5/8" Perforated	Class A	7054G	0.70	20	0.76	White and Black	A, B, C, D		42%	\$
	2'x2'x5/8" Unperforated	Class A	7056G	0.50	20	0.76	White and Black	A, B, C, D		42%	\$
	2'x4'x5/8" Perforated	Class A	7055G	0.70	20	0.76	White and Black	A, B, C, D		42%	\$
	2'x4'x5/8" Unperforated	Class A	7057G	0.50	20	0.76	White and Black	A, B, C, D		42%	\$

ClimaPlus™ Warranty Performance⁵
Fiberglass substrate is inherently resistant to the growth of mold and mildew. Includes sag-resistance performance.

A USG DX®	B USG DXW™	C USG ZXLA™	D USG AX™

Product literature
Data sheet: SC1838

ASTM E1264 classification
ASTM E1264-22 Type XII, Form 1, Pattern C & E (perforated), Pattern E (unperforated)
ASTM E1264-23 Type B, Form B1, Pattern C & E (perforated), Pattern E (unperforated)*

ASTM E84 and CAN/ULC S102 surface-burning characteristics
Class A
Flame spread: 25 or less
Smoke developed: 50 or less

Online tools
usgdesignstudio.com, cgcdesignstudio.com or usg.ecomedes.com

Weight
0.18 lb./sq. ft.

Thermal resistance
R-2.7

Maximum backloading
See USG 30-Year Limited System Warranty Commercial Applications (SC2102).

Maintenance
Can be cleaned easily with a damp sponge.

Metric sizes available
Contact sales for minimum quantities and lead times.

Notes
1. For details, see USG Sustainability tool at usgdesignstudio.com or cgcdesignstudio.com.
2. LR values are shown as averages. Published values are representative for White panels only.
3. For details, see USG 30-Year Limited System Warranty Commercial Applications (SC2102).
4. See Colors selector for more information.

Notice
The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

SC1838/rev. 7-24
© 2024 USG Corporation and/or its affiliates. All rights reserved. Printed in USA