

# USG PREMIER NUBBY™ ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE

USG Premier Nubby™ Acoustical Panels with ClimaPlus™ Performance, and USG Donn® Brand DX® Acoustical Suspension System

TO ORDER SAMPLES, GO TO [USG.COM](http://USG.COM) OR [CGCINC.COM](http://CGCINC.COM)



Flat White  
050

## FEATURES AND BENEFITS

- High-quality nubby cloth facing offers consistent, fine-textured appearance.
- Excellent noise reduction with NRC of 0.85 or 0.90 meets the demanding sound-control needs of open-plan spaces.
- Lightweight fiberglass basemat makes installation fast and easy.
- ClimaPlus™ 30-year limited system warranty against visible sag, mold and mildew.

## APPLICATIONS

- Conference rooms and executive areas
- Gymnasiums and auditoriums
- Open-office plans
- Retail stores

## SUBSTRATE

- Fiberglass

Lightly Textured Panel

# USG PREMIER NUBBY™ ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE

**ORDER SAMPLES/LITERATURE**  
 USG: usg.com or samplitt@usg.com  
 CGC: contact Sales Representative

**TECHNICAL SERVICES**  
 800.USG.4YOU (874-4968)

**FOR MOST UP-TO-DATE TECHNICAL INFORMATION AND LEED REPORT TOOL**  
 usgdesignstudio.com  
 cgcdesignstudio.com

**30** YEAR LIMITED SYSTEM WARRANTY  
 • No Visible Sag  
 • Mold/Mildew Protection

UL Classified

Edge	Panel Size	Fire Rating	Item No.	NRC	CAC Min.	LR <sup>2</sup>	Color	Grid Options	Anti-Mold & Mildew	Recycled Content <sup>1</sup>	Panel Cost
SQ 	2'x2'x3/4"	Class A	7000G	0.85	—	0.82	White	A,B,C		29%	\$\$\$
	2'x2'x1"	Class A	7002G	0.90	—	0.82	White	A,B,C		32%	\$\$\$
	2'x2'x1" Foil-Back	Class A	7012G	0.90	25	0.82	White	A,B,C		32%	\$\$\$
	2'x4'x1"	Class A	7003G	0.90	—	0.82	White	A,B		32%	\$\$\$
	2'x4'x1" Foil-Back	Class A	7013G	0.90	25	0.82	White	A,B		32%	\$\$\$

**ClimaPlus™ Warranty Performance<sup>3</sup>**  
 Fiberglass substrate is inherently resistant to the growth of mold and mildew. Includes sag-resistance performance.

## GRID PROFILE OPTIONS

A USG DX*	B USG DXW™	C <sup>4</sup> USG Centricitee™ DXT™

## PHYSICAL DATA/ FOOTNOTES

**Product literature**  
 Data sheet: SC1839

**ASTM E1264 classification**  
 Type XII, Form 2, Pattern E

**ASTM E84 and CAN/ULC S102 surface-burning characteristics**  
 Class A  
 Flame spread: 25 or less  
 Smoke developed: 50 or less

**Weight**  
 0.188-0.25 lb./sq. ft.

**Online tools**  
 usgdesignstudio.com or cgcdesignstudio.com

**AC information**  
 170 for item #7003G,  
 190 for item #7013G.

**Thermal resistance**  
 R-3.3 (3/4" panels)  
 R-4.4 (1" panels)

**Maximum backloading**  
 See *USG 30-Year Limited System Warranty Commercial Applications* (SC2102).

**Maintenance**  
 Can be cleaned easily with a soft brush or vacuum.

**Metric sizes available**  
 Contact sales for minimum quantities and lead times.

- Notes**
- For details, see USG Sustainability tool at usgdesignstudio.com or cgcdesignstudio.com.
  - LR values are shown as averages.
  - For details, see *USG 30-Year Limited System Warranty Commercial Applications* (SC2102).
  - Maximum 2'x2' with SQ edge panels.

**Notice**  
 The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

**SC1839/rev. 2-23**  
 © 2023 USG Corporation and/or its affiliates. All rights reserved. Printed in USA

Manufactured by USG Interiors, LLC  
 550 West Adams Street  
 Chicago, IL 60661

The trademarks USG, CGC, CENTRICITEE, CLIMAPLUS, DONN, DX, DXT, DXW, PREMIER NUBBY, IT'S YOUR WORLD. BUILD IT., the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

