

USG PREMIER NUBBY™ ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE

USG Premier Nubby™ Acoustical Panels with ClimaPlus™ Performance, and USG Donn® Brand DX® Acoustical Suspension System

TO ORDER SAMPLES, GO TO USG.COM OR CGCINC.COM



Flat White
050

FEATURES AND BENEFITS

- High-quality nubby cloth facing offers consistent, fine-textured appearance.
- Excellent noise reduction with NRC of 0.85 or 0.90 meets the demanding sound-control needs of open-plan spaces.
- Lightweight fiberglass basemat makes installation fast and easy.
- ClimaPlus™ 30-year limited system warranty against visible sag, mold and mildew.

APPLICATIONS

- Conference Rooms and Executive Areas
- Gymnasiums and Auditoriums
- Open-office Plans
- Retail Stores

SUBSTRATE

- Fiberglass

Lightly Textured Panel

USG PREMIER NUBBY™ ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE

ORDER SAMPLES/LITERATURE
USG: usg.com or samplkit@usg.com
CGC: contact Sales Representative

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com
usg.ecomedes.com

TECHNICAL SERVICES
800 USG.4YOU (874-4968)

30

YEAR LIMITED SYSTEM WARRANTY

No Visible Sag

Mold/Mildew Protection

UL Classified

Edge	Panel Size	Fire Rating	Item No.	NRC	CAC Min.	LR ²	Color	Grid Options	Anti-Mold & Mildew	Recycled Content ¹	Panel Cost
SQ 	2'x2'x3/4"	Class A	7000G	0.85	—	0.82	White	A,B,C		29%	\$\$\$
	2'x2'x1"	Class A	7002G	0.90	—	0.82	White	A,B,C		32%	\$\$\$
	2'x2'x1" Foil-Back	Class A	7012G	0.90	25	0.82	White	A,B,C		32%	\$\$\$
	2'x4'x1"	Class A	7003G	0.90	—	0.82	White	A,B		32%	\$\$\$
	2'x4'x1" Foil-Back	Class A	7013G	0.90	25	0.82	White	A,B		32%	\$\$\$

ClimaPlus™ Warranty Performance³
Fiberglass substrate is inherently resistant to the growth of mold and mildew. Includes sag-resistance performance.

A USG DX®	B USG DXW™	C ⁴ USG Centricitee™ DXT™

<p>Product literature Data sheet: SC1839</p> <p>ASTM E1264 classification ASTM E1264-22 Type XI, Form 2, Pattern E ASTM E1264-23 Type B, Form B2, Pattern E</p> <p>ASTM E84 and CAN/ULC S102 surface-burning characteristics Class A Flame spread: 25 or less Smoke developed: 50 or less</p> <p>Weight 0.19-0.25 lb./sq. ft.</p>	<p>Online tools usgdesignstudio.com, cgcdesignstudio.com or usg.ecomedes.com</p> <p>AC information 170 for item #7003G. 190 for item #7013G.</p> <p>Thermal resistance R-3.3 (3/4" panels) R-4.4 (1" panels)</p> <p>Maximum backloading See <i>USG 30-Year Limited System Warranty Commercial Applications</i> (SC2102).</p>	<p>Maintenance Can be cleaned easily with a soft brush or vacuum.</p> <p>Metric sizes available Contact sales for minimum quantities and lead times.</p> <p>Notes</p> <ol style="list-style-type: none">For details, see USG Sustainability tool at usgdesignstudio.com or cgcdesignstudio.com.LR values are shown as averages.For details, see <i>USG 30-Year Limited System Warranty Commercial Applications</i> (SC2102).Maximum 2'x2' with SQ edge panels.
---	--	--

Notice
The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

SC1839/rev. 7-24
© 2024 USG Corporation and/or its affiliates. All rights reserved. Printed in USA