

USG RADAR™ BASIC ACOUSTICAL PANELS

USG Radar™ Basic Acoustical
Panels with USG Donn® Brand DX®
Acoustical Suspension System

TO ORDER SAMPLES, GO TO USG.COM OR CGCINC.COM



Flat White
050

FEATURES AND BENEFITS

- Nondirectional pattern with a fresh, clean appearance offers fast, efficient installation.
- Economical, all-purpose ceiling pattern offered in many sizes.
- USDA Certified Biobased Product.⁵

APPLICATIONS

- Schools
- Corridors
- Offices
- Retail Stores

SUBSTRATE

- Wet-formed Mineral Fiber

Lightly Textured Panel

USG RADAR™ BASIC ACOUSTICAL PANELS

ORDER SAMPLES/LITERATURE
USG: usg.com or samplitt@usg.com
CGC: contact Sales Representative

FOR MOST UP-TO-DATE
TECHNICAL INFORMATION
AND LEED REPORT TOOL
usgdesignstudio.com
cgcdesignstudio.com
usg.ecomedes.com

TECHNICAL SERVICES
800.USG.4YOU (874-4968)



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
ULCOM/GG
UL 2818



HIGH RECYCLED
CONTENT



Edge	Panel Size Imperial Metric (mm)	Fire Rating	Item No. Imperial Metric (mm)	NRC	CAC Min.	LR ²	Color ^{4,7}	Grid Options	VOC Emissions	Recycled Content ¹	Panel Cost
SQ 	2'x2'x5/8" 600x600x15	Class A	2110 ME2110	0.55	33	0.83	White	A,B	Low	38-46%	\$
	2'x4'x5/8" 600x1200x15	Class A	2310 ME2310	0.55	35	0.83	White	A,B	Low	38-46%	\$
	2'x5'x5/8"	Class A	2619	0.55	35	0.83	White	A,B	Low	38-46%	\$
	20"x60"x5/8" 500x1500x15	Class A	2617 ME2617	0.55	35	0.83	White	A,B	Low	38-46%	\$
	30"x60"x3/4"	Class A	2618	0.60	35	0.83	White	A,B	Low	38-46%	\$
SLT 	2'x2'x5/8" 600x600x15	Class A	2120 ME2120	0.55	33	0.83	White	C	Low	37-46%	\$
	2'x4'x5/8"	Class A	2320	0.55	35	0.83	White	C	Low	37-46%	\$
	20"x60"x5/8"	Class A	2627	0.55	35	0.83	White	C	Low	37-46%	\$
FLB 	2'x2'x5/8"	Class A	2130	0.55	33	0.83	White	D,E,F,G	Low	37-46%	\$
BESK 	12"x12"x5/8"	Class A	2990	0.50	40	0.83	White	H	Low	56%	\$\$\$
SLT ⁶ 	2'x4'x3/4"	Class A	2742	0.55	35	0.83	White	C	Low	38-46%	\$

USG RADAR™
BASIC PANEL

USG RADAR™ BASIC TILE³

USG RADAR™ ILLUSION
BASIC TWO/24 PANEL

PATTERNS

Illusion™ Two/24



The look of 2'x2' panels



Low Emissions (VOC)

Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.2 - 2017 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.ecomedes.com and at spot.ul.com.



High Recycled Content

USG classifies High Recycled Content as greater than 50%. Total recycled content is based on product composition of pre-consumer (post-industrial) and post-consumer recycled content per FTC guidelines.

GRID PROFILE OPTIONS

A USG DX [®]	B USG DXW [™]	C USG DX [®]	D USG Centricitee [™] DXT [™]	E USG Fineline [®] DXF [™]	F USG Fineline [®] 1/8 DXFF [™]	G USG Identitee [®] DXI [™]	H USG DX [®] Concealed

PHYSICAL DATA/
FOOTNOTES

Product literature

Data sheet: SC2288

ASTM E1264 classification

ASTM E1264-22 Type III, Form 2, Pattern C & E and C, E, K
ASTM E1264-23 Type A, Form A1.2, Pattern C & E and C, E, & K

ASTM E84 and CAN/ULC S102

surface-burning characteristics

Class A

Flame spread: 25 or less

Smoke developed: 50 or less

Weight

0.61-1.15 lb./sq. ft.

Online tools

usgdesignstudio.com, cgcdesignstudio.com
or usg.ecomedes.com

Thermal resistance

R-1.4 (Class A, 5/8" panels and tile)

R-1.7 (Class A, 3/4" panels)

R-1.4 (Class A, 15 mm panels)

Maximum backloading

See USG 30-Year Limited System Warranty

Commercial Applications (SC2102).

Maintenance

Can be cleaned easily with a soft brush or vacuum.

Metric sizes available

Contact sales for minimum quantities and lead times.

Footnotes

- For details, see USG Sustainability tool at usgdesignstudio.com or cgcdesignstudio.com.
- LR values are shown as averages.
- Not UL Classified for acoustics.
- No Flat Black or 'Deeptones' are available on any reveal edge or USG Radar™ Firecode® panel.
- This product has achieved both BioPreferred initiatives: Federal Procurement Preference and Certified Product Labeling. See the complete listing of all USG ceiling panels on biopreferred.gov website.
- SLT Illusion™ edges have a different reveal depth from SLT edge details. Please reference the System Interface, located in the SC2000, before installing.
- Specification is only applicable for White panels.

Notice

The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

SC2288/rev. 3-25

© 2025 USG Corporation and/or its affiliates. All rights reserved. Printed in USA

Manufactured by
USG Interiors, LLC
550 West Adams Street
Chicago, IL 60661

The trademarks USG, CGC, CENTRICITEE, DONN, DX, DXF, DXFI, DXL, DXT, DXW, FINELINE, IDENTITEE, RADAR, IT'S YOUR WORLD. BUILD IT., the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

