


USG RADAR™CERAMIC ACOUSTICAL PANELS

CLIMAPI US™ PERFORMANCE



USG RADAR CERAMIC ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE

ORDER SAMPLES/LITERATURE USG: usg.com or samplit@usg.com CGC: contact Sales Representative

> TECHNICAL SERVICES 800 USG.4YOU (874-4968)

FOR MOST UP-TO-DATE **TECHNICAL INFORMATION** AND LEED REPORT TOOL

usgdesignstudio.com cgcdesignstudio.com usg.ecomedes.com

YEAR LIMITED SYSTEM WARRANTY No Visible Sag



USG RADAR™ CERAMIC PERFORATED PANELS

PRODUCT CERTIFIED FOR LOW CHEMICAL

				<u></u> ՄՆ ՍԼ	Classified							
Edge	Panel Size	Fire Rating ⁴	Item No.	NRC	CAC Min.	LR ²	Color	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Recycled Content ¹	Panel Cost
				NRC	CAC	Ø		Ħ	3	Ø	3	\$
SQ	2'x2'x5/8"		56644	0.50	40	0.82	White	A,B	Low		51%	\$\$\$\$
	2'x4'x5/8"	Ø	56645	0.50	40	0.82	White	A,B	Low	D	51%	\$\$\$\$

Low Emissions (VOC)


Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.2 - 2017 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.ecomedes.com and at spot.ul.com.

ClimaPlus™ Warranty Performance³

Totally inorganic product; resistant to the growth of mold and mildew. Includes sag-resistance performance.



GRID PROFILE OPTIONS



PHYSICAL DATA/ FOOTNOTES

Product literature Data sheet: SC2293

ASTM E1264 classification

ASTM E1264-22 Type XX, Pattern C, E, & G ASTM E1264-23 Type XX - Mineral fiber with bonded ceramic finish, Pattern C, E, & G

ASTM E84 and CAN/ULC S102 surface-burning characteristics

Class A Flame spread: 0 Smoke developed: 0

UL Type

Online tools

usgdesignstudio.com, cgcdesignstudio.com usg.ecomedes.com

Weight

Thermal resistance

Maximum backloading See *USG 30-Year Limited System Warranty Commercial Applications* (SC2102).

Maintenance
Can be cleaned easily with a damp sponge.

U.S. Coast Guard acceptance
Approved for use on merchant ships (No. 164.009/212/0).

Metric sizes available

Contact sales for minimum quantities and lead times.

- 1. For details, see USG Sustainability tool at usgdesignstudio.com or
- 2. LR values are shown as averages.
- 3. For details, see USG 30-Year Limited System Warranty Commercial Applications (SC2102).
- 4. Firecode® products are approved for use in fireresistance rated UL designs. where the designs allow for the UL Type Designation
- It is not recommended to mix Radar™ Ceramic and other Radar™ panels in the same ceiling plane.

Notice

Notice
The information in this document is subject to change without notice.
CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

