


# USG RADAR™ ILLUSION™ ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE


USG Radar™ Illusion™ Two/24 Panels  
with ClimaPlus™ Performance, and  
USG Donn® Brand DX® Acoustical  
Suspension System

TO ORDER SAMPLES, GO TO [USG.COM](http://USG.COM) OR [CGCINC.COM](http://CGCINC.COM)

#### STANDARD COLORS



#### ADVANTAGE COLORS



#### FEATURES AND BENEFITS

- Nondirectional pattern offers fast, efficient installation.
- Face scores create illusion of a smaller-scaled ceiling system.
- ClimaPlus™ 30-year limited system warranty against visible sag, mold and mildew.
- Optional Firecode® product designed to meet life-safety codes.

#### APPLICATIONS

- Schools
- Corridors
- General offices
- Retail stores

#### SUBSTRATE

- Wet-formed mineral fiber

Lightly Textured Panel

# USG RADAR™ ILLUSION™ ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE

ORDER SAMPLES/LITERATURE  
 USG: usg.com or samplitt@usg.com  
 CGC: contact Sales Representative

TECHNICAL SERVICES  
 800.USG.4YOU (874-4968)

FOR MOST UP-TO-DATE  
 TECHNICAL INFORMATION  
 AND LEED REPORT TOOL  
 usgdesignstudio.com  
 cgcdesignstudio.com



PRODUCT CERTIFIED  
 FOR LOW CHEMICAL  
 EMISSIONS:  
 UL/COM/GG  
 UL2818

30 YEAR LIMITED SYSTEM  
 WARRANTY  
 • No Visible Sag  
 • Mold/Mildew Protection

10 YEAR  
 AVAILABILITY  
 2942, 2952, 2862,  
 2882

HRC HIGH RECYCLED  
 CONTENT

UL Classified

Edge	Panel Size	Fire Rating <sup>2</sup>	Item No.	NRC	CAC Min.	LR <sup>3</sup>	Color <sup>5</sup>	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Recycled Content <sup>1</sup>	Panel Cost
USG RADAR™ ILLUSION™ TWO/24 PANELS	SLT <sup>6</sup>	Class A	2842	0.55	35	0.84	Standard colors (Flat Black and Charcoal not available) Advantage: Beige, Mist and Silvertone only.	A	Low		26-27%	\$\$
			2'x4'x3/4"	2846	0.55	35	0.84	White	A	Low		58%
USG RADAR™ ILLUSION™ FOUR/48 PANELS	ILT <sup>7</sup>	Class A	2844	0.55	35	0.84	White	B,C	Low		26%	\$\$
	SLT <sup>6</sup>		2'x4'x3/4"	2882	0.50	35	0.84	White	A	Low		26%
USG RADAR™ ILLUSION™ EIGHT/12 PANELS	ILT <sup>7</sup>	Class A	2884	0.50	35	0.84	White	B,C	Low		26%	\$\$
	SLT <sup>6</sup>		2'x4'x3/4"	2852	0.55	35	0.84	White	A	Low		26%
USG RADAR™ ILLUSION™ 32/6 PANELS	ILT <sup>7</sup>	Class A	2854	0.55	35	0.84	White	B,C	Low		26%	\$\$
	SLT <sup>6</sup>		2'x4'x3/4"	2862	0.50	35	0.84	White	A	Low		26%
	ILT <sup>7</sup>	Class A	2864	0.50	35	0.84	White	B,C	Low		26%	\$\$

## PATTERNS

Illusion™ Two/24	Illusion™ Four/48	Illusion™ Eight/12	Illusion™ 32/6
The look of 2'x2' panels	The look of 48"x6" linear strips	The look of 12"x12" tile	The look of 6"x6" tile

<p><b>Low Emissions (VOC)</b>                  Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.2 - 2017 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.com and at spot.ul.com.</p>	<p><b>ClimaPlus™ Warranty Performance*</b>                  Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sag-resistance performance.</p>	<p><b>High Recycled Content</b>                  USG classifies High Recycled Content as greater than 50%. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.</p>	<p><b>Firecode®</b></p>
--	---	---	-------------------------

## GRID PROFILE OPTIONS

A USG DX*	B USG Centricitee™ DXT™	C USG Identitee® DXI™

## PHYSICAL DATA/ FOOTNOTES

<p><b>Product literature</b>                  Data sheet: SC2126</p> <p><b>ASTM E1264 classification</b>                  Type III, Form 2, Pattern CEK</p> <p><b>ASTM E84 and CAN/ULC S102 surface-burning characteristics</b>                  Class A                  Flame spread: 25 or less                  Smoke developed: 50 or less</p> <p><b>UL Type</b>                  FR-83</p> <p><b>Weight</b>                  0.760-1.28 lb./sq. ft.</p>	<p><b>Online tools</b>                  usgdesignstudio.com or cgcdesignstudio.com</p> <p><b>Thermal resistance</b>                  R-1.7 (Class A)                  R-1.9 (Firecode®)</p> <p><b>Maximum backloading</b>                  See USG 30-Year Limited System Warranty Commercial Applications (SC2102).</p> <p><b>Maintenance</b>                  Can be cleaned easily with a soft brush or vacuum.</p> <p><b>Metric sizes available</b>                  Contact sales for minimum quantities and lead times.</p>	<p><b>Notes</b></p> <ol style="list-style-type: none"> <li>For details, see USG Sustainability tool at usgdesignstudio.com or cgcdesignstudio.com.</li> <li>Fire-rated items: see UL design details.</li> <li>LR values are shown as averages.</li> <li>For details, see USG 30-Year Limited System Warranty Commercial Applications (SC2102).</li> <li>See Colors selector for more information. No Flat Black or "Deeptones" are available on reveal edge or USG Radar™ Firecode® panel.</li> <li>Panels have a 15/16" routing.</li> <li>Panels have a 9/16" routing.</li> </ol>
---	---	--

**Notice**  
 The information in this document is subject to change without notice. CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

SC2126/rev. 2-23  
 © 2023 USG Corporation and/or its affiliates. All rights reserved. Printed in USA

Manufactured by USG Interiors, LLC  
 550 West Adams Street  
 Chicago, IL 60661

The trademarks USG, CGC, CENTRICITEE, CLIMAPLUS, DONN, DX, DXT, FIRECODE, IDENTITEE, ILLUSION, RADAR, IT'S YOUR WORLD, BUILD IT., the USG/CGC logo, the design elements and colors, and related marks are trademarks of USG Corporation or its affiliates.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification and installation.

