
USG RADAR™ OPEN PLAN ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE



USG RADAR™ OPEN PLAN ACOUSTICAL PANELS

CLIMAPLUS™ PERFORMANCE





ORDER SAMPLES/LITERATURE USG: usg.com or samplit@usg.com

CGC: contact Sales Representative TECHNICAL SERVICES 800 USG.4YOU (874-4968)

FOR MOST UP-TO-DATE **TECHNICAL INFORMATION** AND LEED REPORT TOOL

usgdesignstudio.com cgcdesignstudio.com usg.ecomedes.com

USG RADAR™ OPEN **PLAN PANELS**

PRODUCT CERTIFIED FOR LOW CHEMICAL

				(I) UL Classified								
Edge	Panel Size	Fire Rating	Item No.	NRC ⁶	CAC Min.	LR ²	Color ⁴	Grid Options	VOC Emissions	Anti-Mold & Mildew/Sag Resistance	Recycled Content ¹	Panel Cost
		Ø		NRC	CAC	Ø		Ħ	1	O	HRC	\$
SQ	2'x2'x7/8"	Class A	22320	0.75	35	0.84	White	A,B,C	Low		52%	\$\$
	2'x4'x7/8"	Class A	22325	0.75	35	0.84	White	A,C	Low		52%	\$\$
SLT	2'x2'x7/8"	Class A	22340	0.75	35	0.84	White	D	Low		52%	\$\$
	2'x4'x7/8"	Class A	22345	0.75	35	0.84	White	D	Low		52%	\$\$
FLB	2'x2'x7/8"	Class A	22330	0.75	35	0.84	White	E,F,G,H	Low		52%	\$\$
	2'x4'x7/8"	Class A	22335	0.75	35	0.84	White	E,F,G,H	Low		52%	\$\$

Low Emissions (VOC)

Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.2 - 2017 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.ecomedes.com and at spot.ul.com.

USG DXW™

ClimaPlus™ Warranty Performance3

Contains a broad-spectrum antimicrobial additive on the face and back of the panel that provides resistance against the growth of mold and mildew. Includes sagresistance performance.

USG Fineline®

1/8 DXFF™

USG Identitee*

DXI™

GRID PROFILE OPTIONS

PHYSICAL DATA/ **FOOTNOTES**

Product literature Data sheet: SC2565

A USG

DX*

ASTM F1264 classification

ASTM E1264-22 Type III, Form 2, Pattern C & E ASTM E1264-23 Type A, Form A1.2, Pattern C & E

USG Centricitee™

DXT™

ASTM E84 and CAN/ULC S102 surface-burning characteristics Class A Flame spread: 25 or less

Smoke developed: 50 or less

Weight

0.85 lb./sq. ft.

Online tools

usgdesignstudio.com, cgcdesignstudio.com or usg.ecomedes.com

Thermal resistance R-1.8 (7/8" panels)

USG

DX*

Maximum backloading See USG 30-Year Limited System Warranty Commercial Applications (SC2102).

Maintenance

Panels can be cleaned easily with a soft brush or vacuum.

Metric sizes available

Contact sales for minimum quantities and lead times.

Notes

USG Centricitee

DXT™

- For details, see USG Sustainability tool at usgdesignstudio.com or cgcdesignstudio.com
- 2. LR values are shown as averages.

USG Fineline®

DXF™

- 3. For details, see USG 30-Year Limited System Warranty Commercial Applications (SC2102).
- 4. No Flat Black or "Deeptones" are available on any reveal edge USG Radar™ panel
- 5. Maximum 2'x2' with SQ edge panels.
- 6. It is not recommended to mix panels with varying NRC values in the same ceiling plane.

Notice

Notice
The information in this document is subject to change without notice.
CGC Inc. or USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document.

